



ILLUSTRATION. CONCEPT ONLY.
NOT FOR CONSTRUCTION.

SHARONVILLE FIRE STATION 87 RENOVATION

CITY OF SHARONVILLE

11210 READING RD
SHARONVILLE OH 45241



PROJECT DIRECTORY

OWNER



CITY OF SHARONVILLE
10900 READING ROAD
CINCINNATI, OH 45241

ARCHITECT AND STRUCTURAL ENGINEER



CT CONSULTANTS, INC.
INTEGRITY TOWER BUILDING
4420 COOPER ROAD
SUITE 200
CINCINNATI OH 45242
(p) 513.791.1700

MECHANICAL, ELECTRICAL, PLUMBING, FIRE PROTECTION, AND COMMUNICATION TECHNOLOGY ENGINEERING



KLH ENGINEERS
1538 ALEXANDRIA PIKE
FT. THOMAS, KY 41075
(p) 859.442.8050

VICINITY MAP



DRAWING INDEX


SHEET #	SHEET TITLE	REV				DATE				DESCRIPTION			
		0	1	2	3	0	1	2	3	MAND	ISSUE FOR BIDDING AND PERMIT		
G001	COVER SHEET												
S001	STRUCTURAL GENERAL NOTES												
S002	SPECIAL INSPECTIONS												
S101	FOUNDATION PLANS												
S201	FRAMING PLANS												
S501	TYPICAL CONCRETE DETAILS												
S601	TYPICAL MASONRY DETAILS												
S701	TYPICAL STEEL DETAILS												
S801	TYPICAL LIGHT GAUGE DETAILS												
A001	ABBREVIATIONS AND SYMBOLS												
A002	LIFE SAFETY PLANS												
A003	SIGNAGE												
A004	ARCHITECTURAL SITE AND SLAB DEMO PLANS												
A101	DEMOLITION PLANS AND SECTIONS												
A102	FIRST FLOOR PLAN												
A103	SECOND FLOOR PLAN												
A104	MEZZANINE FLOOR PLAN AND STAIR DETAILS												
A105	REFLECTED CEILING PLANS												
A106	ROOF PLAN AND MURAL WALL DETAILS												
A201	BUILDING ELEVATIONS												
A301	BUILDING SECTIONS												
A302	BUILDING AND WALL SECTIONS												
A303	WALL SECTIONS												
A401	ENLARGED RESTROOM PLANS AND DETAILS												
A402	ENLARGED RESTROOM PLANS AND DETAILS												
A403	INTERIOR ELEVATIONS AND TYPICAL DETAILS												
A404	INTERIOR ELEVATIONS												
A501	ROOM FINISH SCHEDULE AND WALL TYPES												
A601	DOOR SCHEDULE AND WINDOW DETAILS												
A602	DETAILS												
P001	PLUMBING COVER SHEET												
P101	PLUMBING DEMOLITION PLAN												
P102	PLUMBING WATER & GAS - FIRST FLOOR												
P103	PLUMBING WATER & GAS - SECOND FLOOR												
P104	PLUMBING PLAN - ROOF												
P105	PLUMBING SANITARY PLAN - FIRST FLOOR												
P106	PLUMBING SANITARY PLAN - SECOND FLOOR												
P501	PLUMBING - DETAILS												
P601	PLUMBING - SCHEDULES												
P901	PLUMBING - WATER & GAS ISOMETRIC												
P902	PLUMBING - SANITARY & VENT ISOMETRIC												
M001	MECHANICAL COVER SHEET												
M101	MECHANICAL DEMOLITION PLAN												
M102	MECHANICAL DUCTWORK - FIRST FLOOR												
M103	MECHANICAL DUCTWORK - SECOND FLOOR												
M104	MECHANICAL DUCTWORK PLAN - ROOF												
M105	MECHANICAL PIPING - FIRST FLOOR												
M106	MECHANICAL PIPING - SECOND FLOOR												
M501	MECHANICAL - DETAILS												
M502	MECHANICAL - DETAILS												
M503	MECHANICAL - DETAILS												
M504	MECHANICAL - DETAILS												
M505	MECHANICAL - DETAILS												
M506	MECHANICAL - DETAILS												
M601	MECHANICAL - SCHEDULES												
M602	MECHANICAL - SCHEDULES												
M701	MECHANICAL - ENERGY COMPLIANCE												
E001	ELECTRICAL COVER SHEET												
ES101	ELECTRIC SITE PLAN												
E101	ELECTRIC DEMOLITION PLAN												
EL102	ELECTRIC LIGHTING - FIRST FLOOR												
EL103	ELECTRIC LIGHTING - SECOND FLOOR												
EL601	ELECTRIC LIGHTING - LUMINAIRE SCHEDULE												
EP102	ELECTRIC POWER - FIRST FLOOR												
EP103	ELECTRIC POWER - SECOND FLOOR												
EP104	ELECTRIC POWER - ROOF												
EP501	ELECTRIC POWER - DETAILS												
EP502	ELECTRIC POWER - DETAILS												
EP601	ELECTRIC POWER - SINGLE LINE DIAGRAM												
EP602	ELECTRIC POWER - PANEL SCHEDULES												
EP603	ELECTRIC POWER - PANEL SCHEDULES												
EP604	ELECTRIC POWER - SCHEDULES												
T001	TECHNOLOGY COVER SHEET												
T101	TECHNOLOGY DEMOLITION PLAN												
T102	TECHNOLOGY PLAN - FIRST FLOOR												
T103	TECHNOLOGY PLAN - SECOND FLOOR												
T401	TECHNOLOGY PLAN - ENLARGED												
T501	TECHNOLOGY - DETAILS												
T511	TECHNOLOGY - DETAILS												
T512	TECHNOLOGY - DETAILS												
T701	TECHNOLOGY - ROUGH-IN												
T702	TECHNOLOGY - ROUGH-IN												


SHARONVILLE FIRE STATION 87 RENOVATION

CITY OF SHARONVILLE
11210 READING RD SHARONVILLE, OH 45241

COVER SHEET


SCALE: 12" = 1'-0"
HORIZ:
VERT:
CONTRACT NO:
170636
SHEET
G001









1 **ROOF FRAMING PLAN**
S201 SCALE: 3/8" = 1'-0"



2 **THIRD FLOOR FRAMING PLAN**
S201 SCALE: 3/8" = 1'-0"




3 **SECOND FLOOR FRAMING PLAN**
S201 SCALE: 3/8" = 1'-0"



4 **FOUNDATION PLAN**
S201 SCALE: 3/8" = 1'-0"

THIS FIRE TRAINING TOWER IS ADD ALTERNATE #2




NOTE:

AT THE FIRE TRAINING TOWER FOUNDATIONS ONLY, OVEREXCAVATE DOWN TO 5'+/- BELOW EXISTING GRADE. REMOVE EXISTING FILL W/ DEBRIS. IF OVEREXCAVATION IS FILLED WITH ODOT LOW STRENGTH MORTAR UP TO BOTTOM OF FOOTING, OVEREXCAVATION SHALL BE 3' WIDE. IF OVEREXCAVATION IS FILLED WITH COMPACTED BACKFILL UP TO BOTTOM OF FOOTING, OVEREXCAVATION SHALL BE 6' WIDE, CENTERED ON THE FOOTING.

5 **FIRE TRAINING TOWER FOUNDATION**
S201 SCALE: 1" = 1'-0"

ENGINEER/ARCHITECT
SEAL/SIGNATURE




DATE	BY	REVISIONS	REV	DATE	BY	DATE	BY
1/17/2019	MAND	ISSUE FOR BIDDING AND PERMIT	0	10/17/2019	AP	10/17/2019	AP
					PCP		PCP
					APPROVED BY:		PG.
					F.B. NO.		


SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD SHARONVILLE, OH 45241
FRAMING PLANS

SCALE:	As indicated
HORIZ:	
VERT:	
CONTRACT NO:	170636
SHEET	S201


11/19/2019 10:04:49 AM




1 **TYP. POST EMBEDMENT**
S501 SCALE: 3/4" = 1'-0"



4 **REPLACED SLAB TO EXIST. SLAB**
S501 SCALE: N.T.S.




8 **TYP. CONTROL JOINT PATTERN**
S501 SCALE: N.T.S.




* ALL REINFORCING WHICH IS CUT BY THE OPENING SHALL BE ADDED EQUALLY TO EACH SIDE OF THE OPENING AND PLACED BETWEEN NORMAL REINFORCING @ 3" O/C.

- NOTE:
- THIS DETAIL TO BE USED FOR ANY OPENING GREATER THAN 18" DIA OR 18" SQUARE IN WALLS OR SLABS UNLESS FRAMED BY BEAMS OR WALLS.
 - L = LAP SPLICE LENGTH AS GIVEN IN LAP SPLICE TABLE ON SHEET S001.
 - ld = ANCHORAGE LENGTH AS GIVEN IN TABLE ON SHEET XXXX


2 **TYP. OPENING REINFORCING**
S501 SCALE: N.T.S.




5 **EXIST. FOOTING TO PROPOSED FOOTING DETAIL**
S501 SCALE: N.T.S.




9 **TYP. COLUMN FOOTING DETAIL**
S501 SCALE: 3/4" = 1'-0"




TYPICAL CORNER
REINFORCING EACH FACE
(WHEN SCHEDULED OR SHOWN)




TYPICAL CORNER
(REQUIRED WHEN NOT OTHERWISE SHOWN OR SCHEDULED)



TYPICAL "T" CORNER
REINFORCING EACH FACE
(WHEN SCHEDULED OR SHOWN)




TYPICAL "T" CORNER
(UNLESS NOTED OTHERWISE)



TYPICAL "CROSS" CORNER
REINFORCING EACH FACE
(WHERE NTOED OR SHOWN)


- NOTES:
- VERTICAL REINFORCING NOT SHOWN
 - L = 4'-0" UNLESS NOTED OTHERWISE
 - * = LAP SPLICE LENGTH AS GIVEN IN "MINIMUM LAP SPLICE AND ANCHORAGE TABLE" ON SHEET S001.

3 **TYP. HORIZONTAL CORNER CONCRETE REINFORCING DETAILS**
S501 SCALE: N.T.S.




NOTE: REINFORCING SHALL NOT EXTEND THRU JOINT.

6 **TYP. EXPANSION JOINT DETAIL**
S501 SCALE: N.T.S.



- NOTES:
- THE "SOFF-CUT" MACHINE BY SOFF-CUT INTERNATIONAL MAY BE USED TO CUT CONTROL JOINTS WITHIN APPROXIMATELY 2 HOURS AFTER FINAL FINISHING. THE DEPTH OF CUT SHALL BE AS RECOMMENDED BY THE MANUFACTURER.
 - IF CONTROL JOINTS ARE SAW CUT PER NOTE #1 THEY SHALL BE FLUSHED WITH CLEAN WATER, ALLOWED TO DRY AND THEN FILLED WITH A JOINT SEALANT.

7 **TYP. SLAB-ON-GRADE W/ CONTROL JOINT TYPE "CJ"**
S501 SCALE: N.T.S.



10 **EDGE CONNECTION @ DECK**
S501 SCALE: 1" = 1'-0"

ENGINEER/ARCHITECT
SEAL/SIGNATURE



DATE	BY	REVISIONS	REV	DATE	BY	DATE	BY
11/19/2019	MAND	ISSUE FOR BIDDING AND PERMIT	0	10/17/2019	AP	10/17/2019	AP
					PCP		PCP
					APPROVED BY:		APPROVED BY:
					F.B. NO.		F.B. NO.


SHARONVILLE FIRE STATION 87 RENOVATION

CITY OF SHARONVILLE


11210 READING RD SHARONVILLE, OH 45241

TYPICAL CONCRETE DETAILS


SCALE:	As indicated
HORIZ:	
VERT:	
CONTRACT NO:	170636
SHEET	S501



1 **TYP. EXT CMU WALL INFILL**
S601 SCALE: N.T.S.





2 **TYP. CMU INFILL @ SLAB INFILL**
S601 SCALE: N.T.S.



- NOTES:**
1. WHEN THE BOND BEAM CONTAINS TWO REINFORCING BARS AT THE SAME ELEVATION, ONLY ONE NEEDS TO BE LAPPED AROUND THE CORNER.
 2. AS AN ALTERNATIVE TO USING BOND BEAM UNITS AS SHOWN, STANDARD UNITS CAN BE SAW-CUT TO REMOVE PART OF THE CROSS-WEBS TO ACCOMMODATE THE HORIZONTAL REINFORCEMENT.


5 **BOND BEAM AT CORNER**
S601 SCALE: 1" = 1'-0"




- NOTES:**
1. APPLICABLE TO THE CONSTRUCTION OF ALL CONTROL JOINTS IN C.M.U. WALLS. SEE ARCH PLANS FOR C.M.U. CONSTRUCTION JOINT LOCATIONS.
 2. AS AN ALTERNATIVE TO USING BOND BEAM UNITS AS SHOWN, STANDARD UNITS CAN BE SAW-CUT TO REMOVE PART OF THE CROSS-WEBS TO ACCOMMODATE THE HORIZONTAL REINFORCEMENT.

VERTICAL CONSTRUCTION JOINT ISOMETRIC


6 **TYP. CMU INFILL @ SLAB INFILL**
S601 SCALE: 1 1/2" = 1'-0"



3 **TYP. CMU REINFORCING POSITIONERS**
S601 SCALE: 1 1/2" = 1'-0"




4 **TYP. MASONRY LINTEL**
S601 SCALE: 1 1/2" = 1'-0"



- NOTES:**
1. VERTICAL REINFORCEMENT CONSISTING OF 2 BARS SHALL BE PLACED IN SEPARATE ADJACENT CELLS.
 2. VERTICAL BARS SHALL BE OF THE SAME SIZE, EXTENT, AND ANCHORAGE AS THE TYPICAL REINFORCING IN THAT WALL UNLESS OTHERWISE INDICATED.
 3. VERTICAL BARS CAN BE PART OF NORMAL REINFORCING IN THE WALL.
 4. REINFORCEMENT AT TOP OF OPENING SHALL NOT BE LESS THAN THAT REQUIRED BY THE LINTEL SCHEDULE.
 5. SEE SCHEDULES ON 05001 FOR AND LAP LENGTHS REQUIRED FOR REINFORCEMENT IN CMU WALLS.

REINFORCEMENT AROUND OPENING IN CMU


7 **TYP. CMU INFILL @ SLAB INFILL**
S601 SCALE: N.T.S.



11 **TYP. COMPOSITE DECK SUPPORT**
S601 SCALE: 1 1/2" = 1'-0"

TYP. ROOF DECK TO MASONRY WALL CONNECTION

8 **TYP. CMU INFILL @ SLAB INFILL**
S601 SCALE: N.T.S.



12 **TYP. DECK EDGE SUPPORT @ SLAB**
S601 SCALE: 1 1/2" = 1'-0"


NOT USED

S601

NOT USED

S601


REV	DATE	BY	REVISIONS
0	11/19/2019	AP	ISSUE FOR BIDDING AND PERMIT
1		PCP	
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			



TYP. HSS COL - HSS BEAM CONNECTION

1
S701


SCALE: 1 1/2" = 1'-0"



SIDE MOUNTED EXTERIOR PIPE RAILING

2
S701


SCALE: 6" = 1'-0"



TYP. BEAM TO CMU WALL CONNECTION

3
S701



SCALE: 1 1/2" = 1'-0"



PARTIAL ROOF FRAMING PLAN

4
S701


SCALE: 1/8" = 1'-0"



REMOVABLE GUARDRAIL AT MEZZANINE

5
S701


SCALE: 3" = 1'-0"



HSS 8X4 CONNECTION DETAIL

6
S701

SCALE: 3" = 1'-0"



C12X20.7 CONNECTION DETAIL

7
S701

SCALE: 3" = 1'-0"

ENGINEER/ARCHITECT
SEAL/SIGNATURE

your trusted advisor
engineers
architects
consultants
planners

REV	DATE	BY	REVISIONS
0	1/12/2019	AMND	ISSUE FOR BIDDING AND PERMIT

DATE	DRAWN BY	CHECKED BY	APPROVED BY	F.B. NO.
10/17/2019	AP	PCP		

SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD SHARONVILLE, OH 45241


TYPICAL STEEL DETAILS

SCALE:	As indicated
HORIZ:	
VERT:	
CONTRACT NO:	
	170636
SHEET	
	S701


11/19/2019 10:04:52 AM




DRAWING ABBREVIATIONS				DRAWING REFERENCE		DRAWING SYMBOLS	
<div><div>AB</div><div>ANCHOR BOLT</div></div> <div><div>ABV</div><div>ABOVE</div></div> <div><div>AC</div><div>ACOUSTICAL / AIR CONDITIONING</div></div> <div><div>ACT</div><div>ACOUSTICAL CEILING TILE</div></div> <div><div>AD</div><div>AREA DRAIN</div></div> <div><div>ADA</div><div>AMERICANS WITH DISABILITIES ACT</div></div> <div><div>ADDL</div><div>ADDITIONAL</div></div> <div><div>ADJ</div><div>ADJUSTABLE</div></div> <div><div>ADJT</div><div>ADJACENT</div></div> <div><div>A/E</div><div>ARCHITECT/ENGINEER</div></div> <div><div>AFF</div><div>ABOVE FINISHED FLOOR</div></div> <div><div>AFG</div><div>ABOVE FINISHED GRADE</div></div> <div><div>AFS</div><div>ABOVE FINISHED SLAB</div></div> <div><div>AGG</div><div>AGGREGATE</div></div> <div><div>AHU</div><div>AIR HANDLING UNIT</div></div> <div><div>AIB</div><div>AIR INFILTRATION BARRIER</div></div> <div><div>ALT</div><div>ALTERNATE</div></div> <div><div>ALUM</div><div>ALUMINUM</div></div> <div><div>ANOD</div><div>ANODIZE</div></div> <div><div>APPROX</div><div>APPROXIMATE</div></div> <div><div>ARCH</div><div>ARCHITECT</div></div> <div><div>AUX</div><div>AUXILIARY</div></div> <div><div>A/V</div><div>AUDIO / VISUAL</div></div> <div><div>AVG</div><div>AVERAGE</div></div> <div><div>B/</div><div>BOTTOM OF</div></div> <div><div>B/B</div><div>BACK TO BACK</div></div> <div><div>B/F</div><div>BOTTOM OF FOOTING</div></div> <div><div>BD</div><div>BOARD</div></div> <div><div>BDRY</div><div>BOUNDARY</div></div> <div><div>BHMA</div><div>BUILDER'S HARDWARE</div></div> <div><div></div><div>MANUFACTURER'S ASSOCIATION</div></div> <div><div>BLDG</div><div>BUILDING</div></div> <div><div>BLKG</div><div>BLOCKING</div></div> <div><div>BOS</div><div>BOTTOM OF STEEL</div></div> <div><div>BOT</div><div>BOTTOM</div></div> <div><div>BP</div><div>BASE PLATE</div></div> <div><div>BRG</div><div>BEARING</div></div> <div><div>BRK</div><div>BRICK</div></div> <div><div>BRKT</div><div>BRACKET</div></div> <div><div>BSMT</div><div>BASEMENT</div></div> <div><div>BTWN</div><div>BETWEEN</div></div> <div><div>BUR</div><div>BUILT-UP ROOFING</div></div> <div><div>BW</div><div>BOTH WAYS</div></div> <div><div>CAB</div><div>CABINET</div></div> <div><div>CB</div><div>CATCH BASIN</div></div> <div><div>CCTV</div><div>CLOSED CIRCUIT TV</div></div> <div><div>CD</div><div>CONSTRUCTION DOCUMENTS</div></div> <div><div>CDR</div><div>CARD READER</div></div> <div><div>CEM</div><div>CEMENT</div></div> <div><div>CER</div><div>CERAMIC</div></div> <div><div>CF</div><div>CONTRACTOR FURNISHED</div></div> <div><div>CF/CI</div><div>CONTRACTOR FURNISHED / CONTRACTOR INSTALLED</div></div> <div><div>CFMF</div><div>COLD-FORMED METAL FRAMING</div></div> <div><div>CG</div><div>CORNER GUARD</div></div> <div><div>CIP</div><div>CAST-IN-PLACE</div></div> <div><div>CJ</div><div>CONTROL JOINT</div></div> <div><div>CL</div><div>CENTER LINE</div></div> <div><div>CLG</div><div>CEILING</div></div> <div><div>CLG HT</div><div>CEILING HEIGHT</div></div> <div><div>CLO</div><div>CLOSET</div></div> <div><div>CLR</div><div>COLOR, CLEARANCE</div></div> <div><div>CLRM</div><div>CLASSROOM</div></div> <div><div>CMU</div><div>CONCRETE MASONRY UNIT</div></div> <div><div>CO</div><div>CLEANOUT</div></div> <div><div>COL</div><div>COLUMN</div></div> <div><div>COMB</div><div>COMBINATION</div></div> <div><div>COMM</div><div>COMMUNICATION</div></div> <div><div>CONC</div><div>CONCRETE</div></div> <div><div>CONF</div><div>CONFERENCE</div></div> <div><div>CONST</div><div>CONSTRUCTION</div></div> <div><div>CONT</div><div>CONTINUOUS</div></div> <div><div>CONTR</div><div>CONTRACTOR</div></div> <div><div>COORD</div><div>COORDINATE</div></div> <div><div>CORR</div><div>CORRIDOR, CORRUGATED</div></div> <div><div>CPT</div><div>CARPET</div></div> <div><div>CSWK</div><div>CASEWORK</div></div> <div><div>CT</div><div>CERAMIC TILE</div></div> <div><div>CTR</div><div>CENTER</div></div> <div><div>CU FT</div><div>CUBIC FEET</div></div> <div><div>D</div><div>DEPTH</div></div> <div><div>DBL</div><div>DOUBLE</div></div> <div><div>DEMO</div><div>DEMOLITION</div></div> <div><div>DEPT</div><div>DEPARTMENT</div></div> <div><div>DET</div><div>DETAIL</div></div> <div><div>DF</div><div>DRINKING FOUNTAIN</div></div> <div><div>DIA</div><div>DIAMETER</div></div> <div><div>DIAG</div><div>DIAGONAL DIAGRAM</div></div> <div><div>DIM</div><div>DIMENSION</div></div> <div><div>DIR</div><div>DIRECTION</div></div> <div><div>DIST</div><div>DISTANCE</div></div> <div><div>DL</div><div>DEAD LOAD</div></div> <div><div>DN</div><div>DOWN</div></div> <div><div>DOC</div><div>DOCUMENT</div></div> <div><div>DR</div><div>DOOR</div></div> <div><div>DS</div><div>DOWNSPOUT</div></div> <div><div>DWG</div><div>DRAWING</div></div> <div><div>EA</div><div>EACH</div></div> <div><div>EF</div><div>EACH FACE</div></div> <div><div>EIFS</div><div>EXTERIOR INSULATION AND FINISH SYSTEM</div></div> <div><div>EB</div><div>EXPANSION BOLT</div></div> <div><div>EJ</div><div>EXPANSION JOINT</div></div> <div><div>ES</div><div>EACH SIDE</div></div> <div><div>EL</div><div>ELEVATION</div></div> <div><div>ELEC</div><div>ELECTRIC</div></div> <div><div>ELEV</div><div>ELEVATOR</div></div> <div><div>EMER</div><div>EMERGENCY</div></div> <div><div>EPS</div><div>EXPANDED POLYSTYRENE BOARD (INSULATION)</div></div> <div><div>EQ</div><div>EQUAL</div></div> <div><div>EWC</div><div>ELECTRIC WATER COOLER</div></div> <div><div>EXP</div><div>EXPOSED</div></div> <div><div>EXT</div><div>EXTERIOR, EXTINGUISHER</div></div> <div><div>F/</div><div>FACE OF</div></div> <div><div>F/C</div><div>FACE OF CONCRETE</div></div> <div><div>F/F</div><div>FACE TO FACE, FLOOR TO FLOOR</div></div> <div><div>F/M</div><div>FACE OF MASONRY</div></div> <div><div>F/S</div><div>FACE OF STUDS</div></div> <div><div>FA</div><div>FIRE ALARM</div></div> <div><div>FD</div><div>FLOOR DRAIN</div></div> <div><div>FDN</div><div>FOUNDATION</div></div> <div><div>FE</div><div>FIRE EXTINGUISHER</div></div> <div><div>FEC</div><div>FIRE EXTINGUISHER CABINET</div></div> <div><div>FF</div><div>FINISH FLOOR</div></div> <div><div>FF&E</div><div>FIXTURE, FURNISHING & EQUIPMENT</div></div> <div><div>FHC</div><div>FIRE HOSE CABINET</div></div> <div><div>FHR</div><div>FIRE HOSE RACK</div></div> <div><div>FIN</div><div>FINISH</div></div> <div><div>FLR</div><div>FLOOR</div></div> <div><div>FM</div><div>FACTORY MUTUAL</div></div> <div><div>FP</div><div>FIRE PROOFING</div></div> <div><div>FR</div><div>FRAME</div></div> <div><div>FTG</div><div>FOOTING</div></div> <div><div>FUR</div><div>FURRING</div></div> <div><div>FUT</div><div>FUTURE</div></div> <div><div>FVC</div><div>FIRE VALVE CABINET</div></div> <div><div>GA</div><div>GAUGE</div></div> <div><div>GAL</div><div>GALLON</div></div> <div><div>GALV</div><div>GALVANIZED</div></div> <div><div>GB</div><div>GRAB BAR</div></div> <div><div>GC</div><div>GENERAL CONTRACTOR</div></div> <div><div>GEN</div><div>GENERAL, GENERATOR</div></div> <div><div>GL</div><div>GLASS</div></div> <div><div>GR</div><div>GRADE</div></div> <div><div>GR BM</div><div>GRADE BEAM</div></div> <div><div>GRD</div><div>GROUND</div></div> <div><div>GUT</div><div>GUTTER</div></div> <div><div>GYP BD</div><div>GYPSON BOARD</div></div> <div><div>H</div><div>HIGH</div></div> <div><div>HB</div><div>HOSE BIBB</div></div> <div><div>HC</div><div>HANDICAPPED</div></div> <div><div>HD</div><div>HEAVY DUTY</div></div> <div><div>HDR</div><div>HEADER</div></div> <div><div>HDW</div><div>HARDWARE</div></div> <div><div>HM</div><div>HOLLOW METAL</div></div> <div><div>HORIZ</div><div>HORIZONTAL</div></div> <div><div>HP</div><div>HIGH POINT</div></div> <div><div>HT</div><div>HEIGHT</div></div> <div><div>HTR</div><div>HEATER</div></div> <div><div>HVAC</div><div>HEATING, VENTILATING, & AIR CONDITIONING</div></div> <div><div>HWD</div><div>HARDWOOD</div></div> <div><div>IBC</div><div>INTERNATIONAL BUILDING CODE</div></div> <div><div>ID</div><div>INSIDE DIAMETER</div></div> <div><div>ILO</div><div>IN LIEU OF</div></div> <div><div>IN</div><div>INCH</div></div> <div><div>INFO</div><div>INFORMATION</div></div> <div><div>INSUL</div><div>INSULATION</div></div> <div><div>INT</div><div>INTERIOR</div></div> <div><div>INV</div><div>INVERT</div></div> <div><div>J</div><div>JOIST</div></div> <div><div>JAN</div><div>JANITOR</div></div> <div><div>JB</div><div>JUNCTION BOX</div></div> <div><div>JT</div><div>JOINT</div></div> <div><div>KD</div><div>KNOCK DOWN</div></div> <div><div>KIP</div><div>KILO-POUND</div></div> <div><div>KIT</div><div>KITCHEN</div></div> <div><div>KO</div><div>KNOCKOUT</div></div> <div><div>KPL</div><div>KICKPLATE</div></div> <div><div>LAM</div><div>LAMINATE</div></div> <div><div>LAV</div><div>LAVATORY</div></div> <div><div>LBR</div><div>LUMBER</div></div> <div><div>LB</div><div>POUND</div></div> <div><div>LF</div><div>LINEAR FEET (FOOT)</div></div> <div><div>LH</div><div>LEFT HAND</div></div> <div><div>LIN</div><div>LINEAR</div></div> <div><div>LKR</div><div>LOCKER</div></div> <div><div>LL</div><div>LIVE LOAD</div></div> <div><div>LLH</div><div>LONG LEG HORIZONTAL</div></div> <div><div>LLV</div><div>LONG LEG VERTICAL</div></div> <div><div>LLV</div><div>LONG LEG VERTICAL</div></div> <div><div>LOC</div><div>LOCATION</div></div> <div><div>LP</div><div>LOW POINT</div></div> <div><div>LT</div><div>LIGHT</div></div> <div><div>LTWT</div><div>LIGHT WEIGHT</div></div> <div><div>LVR</div><div>LOUVER</div></div> <div><div>MAINT</div><div>MAINTENANCE</div></div> <div><div>MAS</div><div>MASONRY</div></div> <div><div>MATL</div><div>MATERIAL</div></div> <div><div>MAX</div><div>MAXIMUM</div></div> <div><div>MECH</div><div>MECHANICAL</div></div> <div><div>MEMB</div><div>MEMBRANE</div></div> <div><div>MEZZ</div><div>MEZZANINE</div></div> <div><div>MFR</div><div>MANUFACTURER</div></div> <div><div>MIN</div><div>MINIMUM, MINUTE</div></div> <div><div>MISC</div><div>MISCELLANEOUS</div></div> <div><div>MM</div><div>MILLIMETER</div></div> <div><div>MO</div><div>MASONRY OPENING</div></div> <div><div>MOD</div><div>MODULAR, MODIFY</div></div> <div><div>MOV</div><div>MOVABLE</div></div> <div><div>MTD</div><div>MOUNTED</div></div> <div><div>MTL</div><div>METAL</div></div> <div><div>MULL</div><div>MULLION</div></div> <div><div>NA</div><div>NOT APPLICABLE</div></div> <div><div>NFPA</div><div>NATIONAL FIRE PROTECTION ASSOCIATION</div></div> <div><div>NIC</div><div>NOT IN CONTRACT</div></div> <div><div>NO</div><div>NUMBER</div></div> <div><div>NOM</div><div>NOMINAL</div></div> <div><div>NRG</div><div>NOISE REDUCTION COEFFICIENT</div></div> <div><div>NTS</div><div>NOT TO SCALE</div></div> <div><div>OA</div><div>OVERALL</div></div> <div><div>OC</div><div>ON CENTER</div></div> <div><div>OD</div><div>OUTSIDE DIAMETER</div></div> <div><div>OF</div><div>OUTSIDE FACE</div></div> <div><div>OFD</div><div>OVERFLOW DRAIN</div></div> <div><div>OFCI</div><div>OWNER FURNISHED CONTRACTOR INSTALLED</div></div> <div><div>OFOI</div><div>OWNER FURNISHED OWNER INSTALLED</div></div> <div><div>OPH</div><div>OPPOSITE HAND</div></div> <div><div>OPNG</div><div>OPENING</div></div> <div><div>OPP</div><div>OPPOSITE</div></div> <div><div>OWSJ</div><div>OPEN WEB STEEL JOIST</div></div> <div><div>OPR</div><div>OPERABLE</div></div> <div><div>ORD</div><div>OVERFLOW ROOF DRAIN</div></div> <div><div>ORIG</div><div>ORIGINAL</div></div> <div><div>OZ</div><div>OUNCE</div></div> <div><div>PA</div><div>PUBLIC ADDRESS</div></div> <div><div>PAR</div><div>PARAPET</div></div> <div><div>PAT</div><div>PATTERN</div></div> <div><div>PB</div><div>PULL BOX</div></div> <div><div>PBD</div><div>PARTICLEBOARD</div></div> <div><div>PCF</div><div>POUNDS PER CUBIC FOOT</div></div> <div><div>PCT</div><div>PERCENT</div></div> <div><div>PERF</div><div>PERFORATED</div></div> <div><div>PERIM</div><div>PERIMETER</div></div> <div><div>PH</div><div>PHASE</div></div> <div><div>PL</div><div>PROPERTY LINE</div></div> <div><div>PLAM</div><div>PLASTIC LAMINATE</div></div> <div><div>PLAS</div><div>PLASTER, PLASTIC</div></div> <div><div>PLBG</div><div>PLUMBING</div></div> <div><div>PLG</div><div>PILING</div></div> <div><div>PLYWD</div><div>PLYWOOD</div></div> <div><div>PNL</div><div>PANEL</div></div> <div><div>PR</div><div>PAIR</div></div> <div><div>PRCST</div><div>PRECAST</div></div> <div><div>PRKG</div><div>PARKING</div></div> <div><div>PROP</div><div>PROPERTY, PROPOSED</div></div> <div><div>PSF</div><div>POUNDS PER SQUARE FOOT</div></div> <div><div>PSI</div><div>POUNDS PER SQUARE INCH</div></div> <div><div>PT</div><div>PAINT, POINT, PRESSURE TREATED</div></div> <div><div>PTN</div><div>PARTITION</div></div> <div><div>PWR</div><div>POWER</div></div> <div><div>QT</div><div>QUARRY TILE</div></div> <div><div>QTY</div><div>QUANTITY</div></div> <div><div>R</div><div>RADIUS, RISER</div></div> <div><div>RB</div><div>RESILIENT BASE</div></div> <div><div>RBM</div><div>REINFORCED BRICK MASONRY</div></div> <div><div>RBR</div><div>RUBBER</div></div> <div><div>RC</div><div>REINFORCED CONCRETE</div></div> <div><div>RCP</div><div>REFLECTED CEILING PLAN</div></div> <div><div>RD</div><div>ROOF DRAIN</div></div> <div><div>RGD INS</div><div>RIGID INSULATION, SOLID</div></div> <div><div>REC</div><div>RECESSED</div></div> <div><div>REF</div><div>REFERENCE</div></div> <div><div>REM</div><div>REMOVABLE</div></div> <div><div>REP</div><div>REPAIR</div></div> <div><div>REQ</div><div>REQUIRE</div></div> <div><div>REQD</div><div>REQUIRED</div></div> <div><div>RESIL</div><div>RESILIENT</div></div> <div><div>REV</div><div>REVISED, REVISION</div></div> <div><div>RFG</div><div>ROOFING</div></div> <div><div>RH</div><div>RIGHT HAND</div></div> <div><div>RHR</div><div>RIGHT HAND REVERSE</div></div> <div><div>RL</div><div>ROOF LEADER</div></div> <div><div>RLG</div><div>RAILING</div></div> <div><div>RM</div><div>ROOM</div></div> <div><div>RND</div><div>ROUND</div></div> <div><div>RO</div><div>ROUGH OPENING</div></div> <div><div>RVL</div><div>REVEAL</div></div> <div><div>SAN</div><div>SANITARY</div></div> <div><div>SB</div><div>SPLASH BLOCK</div></div> <div><div>SCHED</div><div>SCHEDULE</div></div> <div><div>SD</div><div>SMOKE DETECTOR</div></div> <div><div>SF</div><div>SQUARE FOOT (FEET)</div></div> <div><div>SGL</div><div>SINGLE</div></div> <div><div>SH</div><div>SHOWER</div></div> <div><div>SHT</div><div>SHEET</div></div> <div><div>SHTHG</div><div>SHEATHING</div></div> <div><div>SHV</div><div>SHELVING</div></div> <div><div>SIM</div><div>SIMILAR</div></div> <div><div>SJ</div><div>SCORED JOINT</div></div> <div><div>SK</div><div>SINK</div></div> <div><div>SLV</div><div>SLEEVE</div></div> <div><div>SM</div><div>SHEET METAL</div></div> <div><div>SPEC</div><div>SPECIFICATION</div></div> <div><div>SQ</div><div>SQUARE</div></div> <div><div>SQ IN</div><div>SQUARE INCH</div></div> <div><div>SQ YD</div><div>SQUARE YARD</div></div> <div><div>SST</div><div>STAINLESS STEEL</div></div> <div><div>ST</div><div>STAIRS</div></div> <div><div>STC</div><div>SOUND TRANSMISSION CLASS</div></div> <div><div>STD</div><div>STANDARD</div></div> <div><div>STL</div><div>STEEL</div></div> <div><div>STOR</div><div>STORAGE</div></div> <div><div>STR</div><div>STRUCTURAL</div></div> <div><div>SUB FL</div><div>SUBFLOOR</div></div> <div><div>SUPP</div><div>SUPPLEMENTAL</div></div> <div><div>SW</div><div>SIDEWALK, SHORT WAY</div></div> <div><div>SYM</div><div>SYMMETRICAL</div></div> <div><div>SYS</div><div>SYSTEM</div></div> <div><div>T</div><div>TREAD</div></div> <div><div>T&B</div><div>TOP & BOTTOM</div></div> <div><div>T&G</div><div>TONGUE & GROOVE</div></div> <div><div>T/</div><div>TOP OF</div></div> <div><div>T/BM</div><div>TOP OF BEAM</div></div> <div><div>T/C</div><div>TOP OF CONCRETE, TOP OF CURB</div></div> <div><div>T/COL</div><div>TOP OF COLUMN</div></div> <div><div>T/FTG</div><div>TOP OF FOOTING</div></div> <div><div>T/J</div><div>TOP OF JOIST</div></div> <div><div>T/S</div><div>TOP OF STEEL</div></div> <div><div>TB</div><div>TEST BORING</div></div> <div><div>TD</div><div>TRENCH DRAIN</div></div> <div><div>TEL</div><div>TELEPHONE</div></div> <div><div>TEMP</div><div>TEMPORARY</div></div> <div><div>TER</div><div>TERRAZZO</div></div> <div><div>THK</div><div>THICK</div></div> <div><div>TKBD</div><div>TACKBOARD</div></div> <div><div>TOPO</div><div>TOPOGRAPHY</div></div> <div><div>TV</div><div>TELEVISION</div></div> <div><div>TYP</div><div>TYPICAL</div></div> <div><div>UC</div><div>UNDERCUT</div></div> <div><div>UG</div><div>UNDERGROUND</div></div> <div><div>UH</div><div>UNIT HEATER</div></div> <div><div>UL</div><div>UNDERWRITERS LABORATORY</div></div> <div><div>UNF</div><div>UNFINISHED</div></div> <div><div>UNO</div><div>UNLESS NOTED OTHERWISE</div></div> <div><div>USGS</div><div>UNITED STATES GEOLOGICAL SURVEY</div></div> <div><div>VAR</div><div>VARIES</div></div> <div><div>VCT</div><div>VINYL COMPOSITION TILE</div></div> <div><div>VERT</div><div>VERTICAL</div></div> <div><div>VIF</div><div>VERIFY IN FIELD</div></div> <div><div>VTR</div><div>VENT THRU ROOF</div></div> <div><div>VWC</div><div>VINYL WALL COVERING</div></div> <div><div>W</div><div>WIDE, WIDTH</div></div> <div><div>W/</div><div>WITH</div></div> <div><div>W/O</div><div>WITHOUT</div></div> <div><div>WC</div><div>WATER CLOSET</div></div> <div><div>WD</div><div>WOOD</div></div> <div><div>WF</div><div>WIDE FLANGE</div></div> <div><div>WH</div><div>WALL HYDRANT, WATER HEATER</div></div> <div><div>WL</div><div>WIND LOAD</div></div> <div><div>WP</div><div>WATERPROOFING, WORK POINT</div></div> <div><div>WSCT</div><div>WAINSCOT</div></div> <div><div>WT</div><div>WEIGHT</div></div> <div><div>WWF</div><div>WELDED WIRE FABRIC</div></div> <div><div>YD</div><div>YARD DRAIN</div></div>	<div><div>01 / 1G110</div><div>NUMBER OF PLAN, DETAIL, ETC. ON SHEET</div><div>BUILDING NUMBER</div><div>SERIES NUMBER</div><div>SHEET NUMBER WITHIN SERIES</div><div>DISCIPLINE: G - GENERAL C - CIVIL S - STRUCTURAL A - ARCHITECTURAL I - INTERIOR M - MECHANICAL P - PLUMBING E - ELECTRICAL</div></div>	<div><div>ROOM NAME</div><div>101</div><div>ROOM NAME / NUMBER</div></div> <div><div>101</div><div>DOOR NUMBER</div></div> <div><div>1</div><div>WINDOW TYPE</div></div> <div><div>11</div><div>INTERIOR PARTITIONS</div></div> <div><div>#</div><div>KEYNOTE TAG</div></div> <div><div>3C 3C 3C</div><div>INTERIOR ELEVATION TAG</div></div> <div><div>11</div><div>COLUMN CENTERLINE</div></div> <div><div>11</div><div>FACE OF STEEL</div></div> <div><div></div><div>REVISION CLOUD</div></div> <div><div>1</div><div>REVISION NUMBER</div></div> <div><div>X'-XX"</div><div>CEILING HEIGHT AFF</div></div> <div><div></div><div>SPOT ELEVATION</div></div> <div><div>LEVEL EL:</div><div>LEVEL LINE</div></div> <div><div>1 A101</div><div>SIM</div><div>INDICATES SECTION LETTER OR DETAIL NUMBER</div><div>INDICATES DRAWING SHEET IN WHICH SECTION/DETAIL IS SHOWN</div></div> <div><div>1 A101</div><div>SIM</div><div>INDICATES CALLOUT AREA</div></div> <div><div>1 A101</div><div>INDICATES ELEVATION NUMBER</div><div>INDICATES DRAWING SHEET IN WHICH ELEVATION IS SHOWN</div></div> <div><div>CJ</div><div>CONTROL JOINT</div></div> <div><div>N</div><div>NORTH ARROW</div></div>					
<div><div>SHARONVILLE FIRE STATION 87 RENOVATION</div><div>CITY OF SHARONVILLE</div><div>11210 READING RD SHARONVILLE, OH 45241</div><div>ABBREVIATIONS AND SYMBOLS</div></div>				<div><div>BY</div><div>MAND</div><div>DATE</div><div>11/20/2019</div><div>REVISIONS</div><div>ISSUE FOR BIDDING AND PERMIT</div><div>DATE</div><div>11/20/2019</div><div>REV</div><div>0</div><div>DATE</div><div>11/20/2019</div><div>DRAWN BY:</div><div>DWUR</div><div>CHECKED BY:</div><div>MAND</div><div>APPROVED BY:</div><div>PO</div><div>DATE</div><div>11/20/2019</div><div>SCALE:</div><div>1/8" = 1'-0"</div><div>HORZ:</div><div>VERT:</div><div>CONTRACT NO:</div><div>170636</div><div>SHEET</div><div>A001</div></div>			



1
A002
FIRST FLOOR
LIFE SAFETY PLAN
1/8" = 1'-0"



2
A002
SECOND FLOOR
LIFE SAFETY PLAN
1/8" = 1'-0"



LIFE SAFETY LEGEND

- 1 HOUR FIRE BARRIER
- 2 HOUR FIRE BARRIER
- EXIT SYMBOL
- XX / YY = ACTUAL / CAPACITY
- FIRE EXTINGUISHER CABINET
- EXTINGUISHER TYPES: 2A, K
- EXIT SIGN; SEE LIGHTING DWGS.
- DF = DRINKING FOUNTAIN
- WIDTH
- WIDTH PER OCCUPANT PER NFPA 101 T 7.3.3.1
- MAXIMUM OCCUPANT CAPACITY
- ACTUAL OCCUPANT LOAD
- DOOR WIDTH

TABLE 3412.7 SUMMARY SHEET - BUILDING CODE			
Existing occupancy: 1st S-2, B 2nd B, R-1	Proposed occupancy: 1st S-2, B, R-1, 2nd B, S-1 (Accession)	Number of stories: 2	Height in feet: 26'
Year building was constructed: 1970	Area per floor: 1st: 5713 2nd: 3015	Corridor wall rating: 1 Hr.	
Type of construction: III B	Completely suppressed: Yes (No)	Type: Required door closers: (Yes) No	
Percentage of open perimeter increase: 17%	Compartmentation: (Yes)	Fire-resistance rating of vertical opening enclosures: 0 Hr.	
	Type of HVAC system: A/C & Furnace	Type and location: Type: Dead ends: Yes (No)	
	Automatic fire detection: Yes No	Elevator controls: Yes (No)	
	Fire alarm system: (Yes) No	Mixed occupancies: (Yes) No	
	Smoke control: (Yes) No	Patient ability for self-preservation: 0	
	Adequate exit routes: (Yes) No	Patient concentration: 0	
	Maximum exit access travel distance: 115	Attendant-to-patient ratio: 0	
	Means of egress emergency lighting: (Yes) No		
	Standpipes: Yes (No)		
	Incidental use: Yes (No)		
	Smoke compartmentation less than 22,500 sq. ft. (2092 m2): Yes (No)		
SAFETY PARAMETERS	FIRE SAFETY (FS)	MEANS OF EGRESS (ME)	GENERAL SAFETY (GS)
3412.6.1 Building Height	20	20	20
3412.6.2 Building Area	14	14	14
3412.6.3 Compartmentation	14	14	14
3412.6.4 Tenant and Dwelling Unit Separations	14	14	14
3412.6.5 Corridor Walls	14	14	14
3412.6.6 Vertical Openings	14	14	14
3412.6.7 HVAC Systems	14	14	14
3412.6.8 Automatic Fire Detection	14	14	14
3412.6.9 Fire Alarm Systems	14	14	14
3412.6.10 Smoke Control	***	0	0
3412.6.11 Means of Egress Capacity	***	2	2
3412.6.12 Dead Ends	***	2	2
3412.6.13 Maximum Exit Access Travel Distance	***	8	8
3412.6.14 Elevator Control	***	-2	-2
3412.6.15 Means of Egress Emergency Lighting	***	4	4
3412.6.16 Mixed Occupancies	***	***	0
3412.6.17 Automatic Sprinklers	***	-3 +2 = -1.5	-3
3412.6.18 Standpipes	***	0	0
3412.6.19 Incidental Use	***	0	0
3412.6.20 Smoke compartmentation	***	0	0
3412.6.21.1 Patient ability for self-preservation	****	0	0
3412.6.21.2 Patient concentration	****	0	0
3412.6.21.3 Attendant-to-patient Ratio	****	0	0
Building score - total value	57	67.5	66

Unsanitary Score 24 34 34

CODE COMPLIANCE SUMMARY

PROJECT DESCRIPTION:
EXISTING TWO-STORY FIRE STATION TO BE RENOVATED WITH THE CURRENT BUILDING USE AND FOOTPRINT TO REMAIN AS-IS. PROJECT SCOPE INCLUDES SELECTIVE DEMOLITION OF EXISTING INTERIOR NON-LOAD BEARING PARTITION WALLS, REPLACEMENT OF ALL EXTERIOR WINDOW AND DOOR UNITS, DEMOLITION INCLUDES REMOVAL OF CHANGED AND OBSOLETE INTERIOR AND EXTERIOR MECHANICAL, ELECTRICAL AND PLUMBING EQUIPMENT. NEW INTERIOR BUILDING SPACES ARE PLANNED, NEW INTERIOR WALLS, DOORS, WINDOWS, EXTERIOR SIDING, ROOF AND SITE ELEMENTS ARE ALSO PLANNED. IMPROVED BUILDING CIRCULATION AND MEANS OF EGRESS WILL BE ADA COMPLIANT.

EXISTING CONDITIONS INCLUDE:
THE EXISTING FIRE STATION, IS 8,728 TOTAL GSF, TYPE III-B CONSTRUCTION, NON-SEPARATED, NON-SPRINKLED MIXED-USE AND CLASSIFIED AS PRIMARY "B" OCCUPANCY WITH BUSINESS OFFICE, TRANSIENT RESIDENTIAL, ACCESSORY ASSEMBLY AND VEHICLE STORAGE (NOT USED FOR REPAIR) USES. THE BUILDING HAS A FIRE-SEPARATION DISTANCE OF GREATER THAN 30' PERIMETER OPEN SPACE ON ALL FOUR SIDES TO ADJACENT STRUCTURES. THE EXTERIOR ENVELOPE WALLS ARE PRECAST CONCRETE AND MULTI-WYTHE MASONRY CONSTRUCTION DESIGNED TO BE NON-COMBUSTIBLE, APPROXIMATELY 1'-4" THICK. THE EXISTING FLOOR/CEILING ASSEMBLY IS 8" CAST-IN-PLACE CONCRETE AND HAS AT LEAST A 2 HOUR FIRE RATING. THE EXISTING BUILDING ENTRY DOES NOT MEET ADAAG REQUIREMENTS FOR AN ACCESSIBLE ROUTE; THE UTILITY AND MECHANICAL ROOMS ROOM HAVE NOT BEEN UPGRADED AND BASED ON INTENDED USE BY ABLE-BODIED PERSONNEL ONLY. THE BUILDING HAS AN EXISTING FIRE ALARM SYSTEM WITH CALL CENTER NOTIFICATION AND AT LEAST ONE STAFF MEMBER IS ON-CALL AND AVAILABLE 24 HOURS/DAY. THE BUILDING ALSO HAS AN EXTERIOR STAIR SERVING SECOND FLOOR LEVEL FROM EXTERIOR DOOR EXITING TO A PUBLIC WAY.

NEW CONDITIONS INCLUDE:
NEW EXTERIOR METAL PANEL BUILDING SKIN, NEW INSULATED WINDOWS AND DOORS, NEW INSULATED EXTERIOR WALL FURRING, NEW ROOF INSULATION AND DECKING, A REDUCTION OF THE NUMBER OF APPARATUS BAYS FROM 4 TO 2, INFILLING WITH NEW EQUIPMENT STORAGE AND SERVICES. NEW FIRST FLOOR BUNKROOMS WILL BE ADA COMPLIANT AND HAVE TWO MEANS OF EGRESS WITH OPERABLE EGRESS WINDOWS AND ONE HOUR FIRE SEPARATION PARTITIONS BETWEEN EACH ROOM AND WITH THE CORRIDOR.

APPLICABLE BUILDING CODES
OHIO BUILDING CODE CHAPTER 34 - EXISTING BUILDINGS AND STRUCTURES
OHIO BUILDING CODE 2017 WITH AUGUST 2018 AMENDMENTS AND 02-08-2019 ERRATA
OHIO PLUMBING CODE 2017 WITH AUGUST 2018 AMENDMENTS
OHIO MECHANICAL CODE 2017 WITH AUGUST 2018 AMENDMENTS
NATIONAL ELECTRIC CODE 2017 - NFPA 70
OHIO FIRE CODE 2011
OHIO ENERGY CODE 2017 (INCLUDING ASHRAE 90.1 2010)
ICC ANSI A117.1-2009 (INCLUDING OHIO AMENDMENTS ADA STANDARDS FOR ACCESSIBLE DESIGN 2010)

BASIC BUILDING DATA
USE GROUP CLASSIFICATION:
302.3 ASSEMBLY GROUP B (PRIMARY), S-1 & R-1 (SECONDARY)

CONSTRUCTION TYPE:
602.2 IIIB (UNPROTECTED); EXTERIOR WALLS NON-COMBUSTIBLE CONSTRUCTION, INTERIOR BUILDING ELEMENTS ANY MATERIAL)

BUILDING AREA:
AREA ALLOWABLE AREA PER OBC 506.2 = 19,000 SF
ACTUAL AREA OF FIRST FLOOR = 5,713 SF (GROSS)
ACTUAL AREA OF SECOND FLOOR = 3,015 SF (GROSS)
HEIGHT ALLOWABLE HEIGHT = 3 STORIES
ACTUAL BUILDING HEIGHT = 2 STORIES (PARTIAL) / 26' HIGH

506.2.1 SINGLE-OCCUPANCY, MIXED-USE PARTIAL TWO STORY BUILDING, NON-SPRINKLED

FIRE RATING REQUIREMENTS (TABLE 601/602):
PRIMARY STRUCTURAL FRAME 0 HR
BEARING WALLS (EXTERIOR) 2 HR
BEARING WALLS (INTERIOR) 0 HR
NONBEARING WALLS (INTERIOR OR EXTERIOR > 10' TO PROP LINE) 0 HR
FLOOR CONSTRUCTION 0 HR
ROOF CONSTRUCTION 0 HR

INTERIOR FINISHES (TABLE 803.11)
A CLASS "A" FLAME SPREAD INDEX (0-25) WALLS AND CEILINGS, INTERIOR EXIT PASSAGEWAYS, CORRIDORS, EXIT ACCESS RAMPS.
C CLASS "C" FLAME SPREAD INDEX (26-75) ROOMS AND ENCLOSED SPACES
B CLASS "B" FLAME SPREAD INDEX (76-200) LOBBIES, INTERIOR EXIT PASSAGEWAYS, CORRIDORS, EXIT ACCESS RAMPS AND SPACES OPEN TO THEM.

FLOORS: NOT LESS THAN CLASS II, AND SHALL COMPLY WITH DOC FF-1 "PILL TEST".

FIRE PROTECTION REQUIREMENTS
903 GROUP B - AUTOMATIC SPRINKLER SYSTEM NOT REQUIRED / NOT PROVIDED
904.12 COMMERCIAL COOKING SYSTEM REQUIRED / PROVIDED (ANSUL) PER UL 300
906 PORTABLE FIRE EXTINGUISHERS REQUIRED / PROVIDED PER INTERNATIONAL FIRE CODE, 2011 OHIO FIRE CODE AND NFPA 10.
907.2.2 GROUP B - MANUAL FIRE ALARM SYSTEM NOT REQUIRED / PROVIDED
907.2.11 SINGLE AND MULTIPLE-STATION SMOKE ALARMS REQUIRED / PROVIDED

MEANS OF EGRESS REQUIREMENTS (Chapter 10)
TBL1006.2.1 GROUP B > 49 OCC. OR > 100' MAX COMMON PATH OF TRAVEL W/O SPRINKLER
1006.2 ROOMS, AREAS, OR SPACES WITH OCCUPANCY GREATER THAN 49 AND LESS THAN 500 SHALL HAVE TWO EXITS OR EXIT ACCESS DOORWAYS.
1010.1.2.1 MORE
DOORS SHALL SWING IN THE DIRECTION OF EGRESS WHERE SERVING AN OCCUPANT LOAD OF 50 OR MORE
1010.1.1 DOOR WIDTH: .15" PER PERS., MIN. 32" CLEAR TO STOPS.
TBL. 1017.2 MAXIMUM EXIT ACCESS TRAVEL DISTANCE FOR "B" USE GROUPS: 200'-0".
1020.4 DEAD END CORRIDORS SHALL NOT EXCEED 20'-0".

OCCUPANCY CALCS. (TABLE 1004.1.2)

OCCUPANCY CALCS. (TABLE 1004.1.2)	OCCUPANT LOAD BY USE	AREA	OCCUPANTS
TOILET ROOMS	528 SF / OCC. GROSS	528 SF	13 OCC.
ACCESSORY STORAGE/MECHANICAL	300 SF / OCC. GROSS	1319 SF	5 OCC.
APPARATUS BAY (PARKING GARAGE)	200 SF / OCC. GROSS	1561 SF	8 OCC.
BUSINESS AREAS (1ST FLR. OFF./LAUND)	100 SF / OCC. GROSS	414 SF	5 OCC.
FITNESS	50 SF / OCC. GROSS	655 SF	14 OCC.
KITCHEN	200 SF / OCC. GROSS	500 SF	3 OCC.
EDUCATIONAL CLASSROOM (DAYROOM)	20 SF / OCC. GROSS	380 SF	19 OCC.
DECK	15 SF / OCC. GROSS	170 SF	12 OCC.
BUNK ROOMS	120 SF / OCC. GROSS	656 SF	9 OCC.

CALCULATED OCCUPANCY FOR ENTIRE BUILDING (B): TOTAL 88 OCC.

EXITING CALCS. (TBL. 1006.3.1)

EXITING CALCS. (TBL. 1006.3.1)	AREA	OCCUPANCY	EXITS REQ'D	EXITS PROVIDED
TOILET ROOMS	528 SF	11 OCC.	1	1
ACCESSORY STORAGE/MECHANICAL	1319 SF	5 OCC.	1	1
APPARATUS BAY (PARKING GARAGE)	1561 SF	8 OCC.	1	1
BUSINESS AREAS (1ST FLR. OFF./LAUND)	414 SF	5 OCC.	1	2
FITNESS	655 SF	14 OCC.	1	1
KITCHEN	500 SF	3 OCC.	1	2
EDUCATIONAL CLASSROOM (DAYROOM)	380 SF	19 OCC.	1	2
DECK	170 SF	12 OCC.	1	1
BUNK ROOMS	656 SF	9 OCC.	1	1

(BUILDING ENTRY DOORS REMAIN OPEN AT ALL TIMES)

ACCESSIBILITY
THIS BUILDING AND FACILITY HAS NEW ACCESSIBILITY FEATURES IN ACCORDANCE WITH IBC CHAPTER 11 ACCESSIBILITY AND ICC A117.1.

PLUMBING FIXTURE REQUIREMENTS (TBL. 2902.1)
RESTROOM REQUIREMENTS FOR OVERALL BUILDING BASED ON CODE ALLOWABLE OCCUPANCY = 88 OCC./2 = 44 MALE AND 44 FEMALE:

WATER CLOSETS:
MALE: 1/125 1 REQ'D / 3 PROVIDED
FEMALE: 1/65 1 REQ'D / 2 PROVIDED

LAVATORIES:
MALE: 1/200 1 REQ'D / 3 PROVIDED
FEMALE: 1/200 1 REQUIRED / 2 PROVIDED

DRINKING FOUNTAINS:
1/500 OCC. 1 REQUIRED / 1 PROVIDED

SERVICE SINK: 1 REQUIRED / 2 PROVIDED

your trusted advisor
engineers
architects
consultants
planners

DATE:	11/20/2019	BY:	MAND
DRAWN BY:	DWJR	CHECKED BY:	MAND
APPROVED BY:		F.B. NO.	
SHARONVILLE FIRE STATION 87 RENOVATION			
CITY OF SHARONVILLE			
11210 READING RD SHARONVILLE, OH 45241			
LIFE SAFETY PLANS			
SCALE:	As indicated		
HORIZ:			
VERT:			
CONTRACT NO:	170636		
SHEET	A002		


- A. TACTILE CHARACTERS ON SIGNS SHALL BE LOCATED 48 INCHES MINIMUM ABOVE THE FINISH FLOOR OR GROUND SURFACE, MEASURED FROM THE BASELINE OF THE LOWEST TACTILE CHARACTER AND 60 INCHES MAXIMUM ABOVE THE FINISH FLOOR OR GROUND SURFACE MEASURED FROM THE BASELINE OF THE HIGHEST TACTILE CHARACTER.
- B. WHERE A TACTILE SIGN IS PROVIDED AT A DOOR, THE SIGN SHALL BE LOCATED ALONGSIDE THE DOOR AT THE LATCH SIDE.
- C. WHERE A TACTILE SIGN IS PROVIDED AT DOUBLE DOORS WITH ONE ACTIVE LEAF, THE SIGN SHALL BE LOCATED ON THE INACTIVE LEAF.
- D. WHERE A TACTILE SIGN IS PROVIDED AT DOUBLE DOORS WITH TWO ACTIVE LEAFS, THE SIGN SHALL BE LOCATED TO THE RIGHT OF THE RIGHT HAND DOOR.
- E. WHERE THERE IS NO WALL SPACE AT THE LATCH SIDE OF THE DOOR OR THE RIGHT SIDE OF THE DOUBLE DOORS, SIGN SHALL BE LOCATED AT THE NEAREST ADJACENT WALL.
- F. SIGNS CONTAINING TACTILE CHARACTERS SHALL BE LOCATED SO THAT A CLEAR FLOOR SPACE OF 18" MIN. BY 18" MIN. CENTERED ON THE TACTILE CHARACTERS IS OBTAINED BEYOND THE ARC OF ANY DOOR SWING BETWEEN THE CLOSED POSITION AND 45 DEGREE OPEN POSITION.
- G. SIGN WITH TACTILE CHARACTERS SHALL BE PERMITTED ON THE PUSH SIDE OF DOORS WITH CLOSERS AND WITHOUT HOLD-OPEN DEVICES.



SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD SHARONVILLE, OH 45241

SIGNAGE

SCALE:	As indicated
HORIZ:	
VERT:	
CONTRACT NO:	
	170636
SHEET	
	A003



2
A004
FIRST FLOOR SLAB DEMOLITION PLAN
1/8" = 1'-0"

ADD ALTERNATES

REFER TO SPECIFICATIONS FOR MORE INFORMATION


- #1 MASONRY MONUMENT SIGN: 8" DOUBLE WYTHE CMU CANTILEVERED WALL FOR MONUMENT SIGNAGE. (4.5)
- #2 REMOVE AND REPLACE CONCRETE PAVEMENT (WEST): NEW EXTERIOR PAVING. (32.2)
- #3 REMOVE AND REPLACE CONCRETE PAVEMENT (NORTH): NEW EXTERIOR PAVING. (32.4)

GENERAL SITE NOTES


- A. EACH CONTRACTOR SHALL VERIFY EXISTING CONDITIONS AS INDICATED ON THE DRAWINGS AND SHALL REPORT ANY DISCREPANCIES TO THE ARCHITECT.
- B. EACH CONTRACTOR SHALL COORDINATE THE LOCATION OF HIS COMPONENTS AND EQUIPMENT SO AS NOT TO INTERFERE WITH OTHER INSTALLATIONS.
- C. COORDINATE ALL SITE WORK WITH CIVIL ENGINEERING DRAWINGS. REFER TO CIVIL ENGINEERING DRAWINGS FOR SITE GEOMETRICS AND SITE WORK RESPONSIBILITIES.
- D. THIS DRAWING IS FOR COORDINATION AND REFERENCE ONLY. REFER TO SUBCONTRACTOR DISCIPLINE SPECIFIC DRAWINGS FOR ACTUAL DIMENSIONS, SIZES, ETC.
- E. ALL WORK SHALL CONFORM TO ALL GOVERNING CODES AND O.S.H.A. REQUIREMENTS.
- F. FIELD VERIFY ALL DIMENSIONS.
- G. FOR AREAS OF WORK, CONTRACTOR SHALL FAMILIARIZE HIMSELF WITH ALL EXISTING CONDITIONS PRIOR TO SUBMITTING A BID AND COVER ALL WORK TO BE PERFORMED AS REQUIRED FOR A COMPLETE JOB.
- H. WHERE REQUIRED, CONCRETE WALKS, EXISTING PAVEMENT, ETC. SHALL BE NEATLY SAW CUT AND PATCHED TO BLEND IN WITH ADJACENT SURFACES.
- I. VERIFY LOCATION OF UNDER GROUND UTILITIES, PLUMBING, ELECTRICAL, ETC. PRIOR TO ANY CUTTING, CORING, EXCAVATING, ETC. ALL UTILITY COMPANIES SHALL BE CONTACTED BY THE CONTRACTOR AND THEIR FACILITIES SHALL BE LOCATED PRIOR TO WORK IN ANY EASEMENT, RIGHT-OF-WAY, OR SUSPECTED UTILITY LOCATION.

KEYNOTES

- 3.15 NEW 5' WIDE SIDEWALK TO DRIVEWAY.
- 4.5 ADD ALTERNATE #1: 8" DOUBLE WYTHE CMU CANTILEVERED MURAL WALL FOR MONUMENT SIGNAGE. 6" DIA. BOLLARD, PAINTED.
- 5.24 EXISTING EXTERIOR PAVING TO REMAIN.
- 32.1 ADD ALTERNATE #2: NEW EXTERIOR PAVING.
- 32.2 NEW GENERATOR ENCLOSURE AND PAD. PROVIDE GRAVEL FRONT. REFER TO ELECTRICAL DRAWINGS AND SPECIFICATIONS FOR MORE INFORMATION.
- 32.3 ADD ALTERNATE #3: NEW EXTERIOR PAVING.
- 32.4 NEW MAIN ENTRY SIGNAGE. BY OTHERS.
- 32.10 SAWCUT AND REMOVE STRUCTURAL FLOOR SLAB THIS AREA. REFER TO STRUCTURAL FLOOR PLANS FOR ADDITIONAL INFORMATION.
- D3.3 EXISTING EXTERIOR CONCRETE TO BE REMOVED. TERMINATE AT EXISTING SIDEWALK. PROVIDE 4" OF TOPSOIL AND RE-SEED AS REQUIRED.
- D32.1 EXISTING TREE TO BE REMOVED. GRIND STUMP. REMOVE TOP ROOTS AND RESEED AS REQUIRED.
- D32.4 ADD-ALTERNATE #3: EXISTING EXTERIOR CONCRETE TO BE REMOVED. TERMINATE AT EXISTING SIDEWALK. PROVIDE 4" OF TOPSOIL AND RE-SEED AS REQUIRED.
- D32.6 ADD-ALTERNATE #2: EXISTING EXTERIOR CONCRETE TO BE REMOVED. TERMINATE AT EXISTING SIDEWALK. PROVIDE 4" OF TOPSOIL AND RE-SEED AS REQUIRED.
- D32.7



1
A004
ARCHITECTURAL SITE PLAN
3/32" = 1'-0"



your trusted advisor

consultants

engineers

architects

planners

REV	DATE	BY	REVISIONS
0	11/20/2019	MAND	ISSUE FOR BIDDING AND PERMIT
1	11/20/2019	DWUR	
2		MAND	
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			
13			
14			
15			
16			
17			
18			
19			
20			
21			
22			
23			
24			
25			
26			
27			
28			
29			
30			
31			
32			
33			
34			
35			
36			
37			
38			
39			
40			
41			
42			
43			
44			
45			
46			
47			
48			
49			
50			
51			
52			
53			
54			
55			
56			
57			
58			
59			
60			
61			
62			
63			
64			
65			
66			
67			
68			
69			
70			
71			
72			
73			
74			
75			
76			
77			
78			
79			
80			
81			
82			
83			
84			
85			
86			
87			
88			
89			
90			
91			
92			
93			
94			
95			
96			
97			
98			
99			
100			


SHARONVILLE FIRE STATION 87 RENOVATION

CITY OF SHARONVILLE


11210 READING RD SHARONVILLE, OH 45241

ARCHITECTURAL SITE AND SLAB DEMO PLANS


SCALE:	As indicated
HORZ:	
VERT:	
CONTRACT NO:	170636
SHEET	A004



1
A101
1/8" = 1'-0"



2
A101
1/8" = 1'-0"



3
A101
3/4" = 1'-0"

GENERAL DEMOLITION NOTES


- VERIFY EXISTING CONDITIONS IN FIELD AND NOTIFY ARCHITECT OF ANY DISCREPANCIES.
- WHERE REMOVING PORTIONS OF MASONRY OR CONCRETE, USE A SAW TO CUT CLEAN, SHARP LINES. REMOVE MASONRY AT NEAREST EXISTING MORTAR JOINT(S).
- WHERE ADJACENT OR INTERSECTING CONSTRUCTION IS TO REMAIN, TRIM, GRIND, SCRAPE, OR SAND FACES OF DEMOLISHED ITEMS FLUSH WITH ADJACENT SURFACES TO REMAIN.
- WHERE CREATING AN OPENING FOR A DOOR OR WINDOW, ONLY REMOVE AS MUCH OF THE EXISTING CONSTRUCTION AS REQUIRED. COORDINATE EXACT LOCATION WITH PROPOSED PLANS.
- WHERE REMOVING MASONRY TO CREATE AN OPENING THAT WILL BE EXPOSED TO VIEW, REMOVE ADDITIONAL MASONRY REQUIRED TO "TOOTH-IN" JAMB PIECES TO MATCH EXISTING BOND PATTERN. MAKE PROVISIONS FOR LINTELS, INCLUDING MIN 8" BEARING AT EACH END. COORDINATE WITH STRUCTURAL DRAWINGS.
- CONTRACTOR SHALL BE RESPONSIBLE FOR TEMPORARY SHORING AND BRACING.
- COORDINATE WORK BETWEEN TRADES AND OTHER DISCIPLINES. ADDITIONAL ITEMS OF WORK MAY APPEAR ELSEWHERE IN THE CONSTRUCTION DOCUMENTS.
- REMOVE ALL EXISTING INTERIOR WALLS, DOORS, WINDOWS AND CASEWORK. REFER TO MEP DRAWINGS FOR DEMOLITION OF MECHANICAL, ELECTRICAL AND PLUMBING.
- EXISTING OFFICE EQUIPMENT AND FILING TO BE REMOVED BY OWNER PRIOR TO DEMOLITION.

KEYNOTES

- D2.1 EXISTING WALL CONSTRUCTION TO REMAIN.
- D3.3 SAWCUT AND REMOVE STRUCTURAL FLOOR SLAB THIS AREA. REFER TO STRUCTURAL FLOOR PLANS FOR ADDITIONAL INFORMATION.
- D3.4 REMOVE EXISTING GYPSUM BOARD WALLS, TYP.
- D3.5 DEMOLISH EXISTING CMU WALLS, TYP.
- D4.3 EXISTING CONCRETE SLAB TO REMAIN.
- D4.4 SAWCUT AND REMOVE EXISTING CMU WALLS THIS CLOSET. 4" CONCRETE CURB TO REMAIN.
- D5.1 REMOVE EXISTING STAIR, RAILING AND STRUCTURE.
- D5.3 REMOVE EXISTING METAL FASCIA AND BLOCKING TO MEMBRANE AND COPING.
- D5.4 REMOVE FLOOR FRAMING ABOVE, RAILING AND STEEL TUBE SUPPORT. CMU WALL TO REMAIN.
- D5.5 REMOVE METAL FRAMING AT BASE OF WINDOW.
- D5.6 REMOVE LADDER UP TO ROOF HATCH. SALVAGE FOR REUSE.
- D7.1 REMOVE EXISTING ROOF MEMBRANE. INSULATION TO REMAIN. PATCH AS REQUIRED AT VOIDS AND TERMINATION.
- D8.1 REMOVE EXISTING DOOR ASSEMBLY.
- D8.2 REMOVE EXISTING WINDOW AND METAL FRAMING BELOW, TYP.
- D8.3 REMOVE EXISTING OVERHEAD DOOR, FRAMING AND OPERATORS. UNBOLT EXISTING WHEEL GUARDS AT DOORS TO BE TERMINATED.
- D8.4 SAWCUT AND REMOVE EXISTING WALL CONSTRUCTION FOR NEW OPENING. REFER TO A201 FOR HEIGHT, ALIGNMENT WITH ADJACENT OPENINGS AND HEAD GROOVE.
- D8.6 PATCH MASONRY ABOVE TO INFILL WHERE EXISTING EXHAUST FAN WAS REMOVED WITH METAL STUD FRAMING.
- D8.7 REMOVE EXISTING OVERHEAD DOOR, FRAMING AND OPERATORS. UNBOLT EXISTING WHEEL GUARDS AT DOORS TO BE SALVAGED AND REUSED.
- D8.8 REMOVE EXISTING STOREFRONT SYSTEM.
- D9.3 REMOVE EXISTING CEILING GRID AND LIGHTING IN APPARATUS BAY.
- D9.4 REMOVE EXISTING FLOORING. SMOOTH TO PREPARE FOR POLISHED CONCRETE.
- D9.5 REMOVE EXISTING CEILING GRID AND LIGHTING, TYPICAL THIS FLOOR.
- D10.1 REMOVE EXISTING PLAQUE AND RETURN TO OWNER.
- D10.2 REMOVE EXISTING LETTERS AND SALVAGE FOR REUSE.
- D12.2 REMOVE EXISTING TROPHY CASE AND SALVAGE. RETURN TO OWNER.
- D12.3 REMOVE EXISTING NOTICE CASE. SALVAGE.
- D22.1 EXISTING OIL SEPARATOR, PREPARE FOR FINAL CLEANING, CAP AND BACKFILL WITH PEAGRAVEL AS REQUIRED.
- D22.2 REMOVE EXISTING TRENCH DRAIN GRATE. INFILL WITH FLOWABLE FILL.
- D26.1 REMOVE EXISTING LIGHTING IN SOFFIT. TERMINATE WIRING AND PREPARE FOR NEW LIGHTING.
- D26.2 REMOVE EXISTING LIGHT ABOVE. CAP AND PREPARE FOR NEW LIGHT ASSEMBLY.
- D26.3 REMOVE AND TERMINATE EXISTING CALL BOX. REMOVE CONDUIT AND PATCH HOLES AS REQUIRED.
- D26.4 REMOVE EXISTING UTILITY LINE THIS AREA. REFER TO MEP DRAWINGS FOR MORE INFORMATION.
- D32.3 REMOVE EXISTING FLAG POLE ASSEMBLY THIS SIDE. PATCH MASONRY AS REQUIRED.
- D33.1 REMOVE EXISTING GAS FIRED UNIT HEATERS. CAP.

your trusted advisor engineers architects planners consultants		BY MAND	DATE 1/16/2019	REV 0	ISSUE FOR BIDDING AND PERMIT	REVISIONS	DATE 1/16/2019	DRAWN BY DWJR	CHECKED BY MAND	APPROVED BY F.B. NO.	PG.
SHARONVILLE FIRE STATION 87 RENOVATION CITY OF SHARONVILLE 11210 READING RD SHARONVILLE, OH 45241 DEMOLITION PLANS AND SECTIONS											
SCALE: As indicated HORIZ: VERT: CONTRACT NO: 170636 SHEET A101											

11/19/2019 12:52:21 PM



1 FIRST FLOOR PLAN
A102 1/4" = 1'-0"

KEYNOTES

- 0.1 LINE OF NEW OPENING ABOVE.
- 2.1 EXISTING CONSTRUCTION TO REMAIN.
- 3.1 CMU WALL WITH STUCCO FINISH TO MATCH EXTERIOR FACE FLUSH WITH ADJACENT. ARCHITECT TO VERIFY TYPICAL MATCHING TEXTURE PRIOR TO PLACEMENT.
- 3.3 EXISTING CONCRETE STAIR. PRESSURE WASH AND SEAL TREADS AND RISERS.
- 3.5 NEW CONCRETE RAMP UP TO EXISTING STOOP. SAWCUT AND REMOVE EXISTING DRIVE TO INSTALL.
- 3.8 NEW CONCRETE RAMP UP TO EXISTING SLAB.
- 3.9 TOOTH IN PROPOSED MASONRY TO MATCH EXISTING.
- 3.12 NEW 4" CONCRETE SLAB.
- 3.13 NEW CONCRETE INFILL. SLOPE RAMP TO EXISTING.
- 3.14 NEW 5 3/8" CONCRETE FLOOR SLAB INFILL.
- 3.15 NEW 5" WIDE SIDEWALK TO DRIVEWAY.
- 4.16 8" CMU WALL. REFER TO STRUCTURAL DRAWINGS FOR MORE INFORMATION.
- 4.19 12" CMU.
- 5.2 HSS STEEL COLUMN. PAINTED (P1). REFER TO STRUCTURAL DRAWINGS FOR SIZES AND LOCATIONS.
- 5.9 COLD FORMED METAL FRAMED CANOPY WITH CORRUGATED METAL SIDING.
- 5.24 6" DIA. BOLLARD. PAINTED.
- 5.35 4" HIGH PERFORATED METAL SCREEN (RED).
- 8.1 NEW ALUMINUM FRAMED INSULATED GLASS WINDOW. SEE A601 FOR MORE INFORMATION.
- 9.10 FROSTED FILM INSIDE GLASS TO 7'-2" AFF.
- 9.11 ALIGN WALLS THIS SIDE.
- 10.1 SEMI-RECESSED FIRE EXTINGUISHER CABINET.
- 10.6 OWNER FURNISHED, OWNER INSTALLED.
- 11.3 WASHER. REFER TO PLUMBING DRAWINGS.
- 11.4 DRYER. REFER TO PLUMBING DRAWINGS.
- 12.1 PROVIDE AND INSTALL 98% BLACKOUT WINDOW SHADES AT WINDOW.
- 12.3 18"x18" LOCKABLE PLASTIC LAMINATE PASS-THRU LOCKERS. REFER TO 13/14/A404 FOR DIMENSIONS AND DETAILS.
- 22.1 FLOOR DRAIN. REFER TO PLUMBING DRAWINGS.
- 22.2 MOP BASIN. PROVIDE WALL GUARDS AND MOP HANGER BRACKET ABOVE. REFER TO PLUMBING DRAWINGS.
- 22.3 FREE STANDING UTILITY SINK. REFER TO PLUMBING DRAWINGS.
- 22.4 EXISTING TRENCH DRAIN. REFER TO PLUMBING DRAWINGS.
- 22.5 UTILITY SINK. REFER TO PLUMBING DRAWINGS.
- 22.6 EMERGENCY EYE WASH. REFER TO PLUMBING DRAWINGS.
- 26.2 CARD SWIPE READER.
- 32.7 KEEP COVERS CLEAR FOR BELOW GRADE ENCASEMENT WITH UNDERGROUND OIL/SILT SEPARATOR.
- 32.9 BACKFILL WITH BIG STONE.

GENERAL NOTES

- A. FINISH FLOOR ELEVATION OF 100'-0" IS EQUAL TO USGS ELEVATION OF 598.78'.
- B. VERIFY EXISTING CONDITIONS IN FIELD AND NOTIFY ARCHITECT OF ANY DISCREPANCIES.
- C. EXTERIOR DIMENSIONS SHOWN ARE TO OUTSIDE FACE OF FOUNDATION WALL OR ROUGH OPENINGS. TYPICAL UNLESS NOTED OTHERWISE.
- D. INTERIOR DIMENSIONS SHOWN ARE TO FACE OF PROPOSED STUDS, CMU, OR CONCRETE CONSTRUCTION, UNLESS NOTED OTHERWISE.
- E. ALL DOORS INSTALLED IN GYPSUM BOARD PARTITIONS TO BE LOCATED 0'-4" FROM EDGE OF JAMB OF DOOR TO ADJACENT WALL. ALL DOORS INSTALLED IN MASONRY PARTITIONS TO BE LOCATED 0'-8" FROM EDGE OF JAMB OF DOOR TO ADJACENT WALL, UNLESS NOTED OTHERWISE.
- F. PROVIDE BULLNOSE CMU AT EXPOSED DOOR JAMBS.
- G. VERIFY SIZE OF PRE-FABRICATED ITEMS SUCH AS FIRE EXTINGUISHER CABINETS, CABINET HEATERS, AND RESTROOM ACCESSORIES PRIOR TO INSTALLING ADJACENT FRAMING.
- H. PROVIDE BLOCKING OR METAL STRAPS IN WALLS AS REQUIRED FOR ATTACHMENT OF SURFACE MOUNTED ITEMS SUCH AS RESTROOM ACCESSORIES, CASEWORK, AND FIRE EXTINGUISHERS.
- I. PROVIDE SEALANT AT JOINTS BETWEEN ALL DISSIMILAR MATERIALS.
- J. PROVIDE GYPSUM BOARD CONTROL JOINTS PER THE SPECIFICATIONS, BUT NOT TO EXCEED 30'-0" ALONG CONTINUOUS INTERIOR PARTITIONS.
- K. PAINT ALL EXPOSED, UNFINISHED EXTERIOR STEEL (DOORS, FRAMES, LINTELS, BOLLARDS, ETC.).
- L. COORDINATE WORK BETWEEN TRADES AND OTHER DISCIPLINES. ADDITIONAL ITEMS OF WORK MAY APPEAR ELSEWHERE IN THE CONSTRUCTION DOCUMENTS.
- M. SEE DEMOLITION DRAWINGS FOR EXTENT OF CONCRETE WALKS AND APRONS.
- N. PROVIDE MASONRY CONTROL JOINT (C.J.) AT EACH OPENING OF INTERIOR WALLS.
- O. REFER TO A0A01 FOR ABBREVIATIONS AND SYMBOLS.
- P. ALL WALLS TO BE PAINTED P-1 UNLESS NOTED OTHERWISE.
- Q. ALL FITNESS EQUIPMENT TO BE PROVIDED AND INSTALLED BY OWNER.

your trusted advisor
engineers
architects
consultants
planners

BY	DATE	REV	REVISIONS	DATE	BY	DATE	REV	REVISIONS
MAND	1/12/2019	0	ISSUE FOR BIDDING AND PERMIT	11/20/2019	DWJR	1/12/2019	1	ISSUE FOR BIDDING AND PERMIT
					CHECKED			
					APPROVED BY:			
					F.B. NO.			

SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD SHARONVILLE, OH 45241

FIRST FLOOR PLAN

SCALE: As indicated
HORZ:
VERT:
CONTRACT NO: 170636
SHEET A102

KEYNOTES

- 3.2 NEW OPENING IN SLAB.
5.6 42" GUARDRAIL WITH INTERMEDIATES NO GREATER THAN 4" CLEAR. PAINTED.
5.12 36" HANDRAIL.
5.23 SALVAGED LADDER TO ROOF HATCH.
7.1 NEW TPO ROOF MEMBRANE. ADD 2" NEW POLYISO INSULATION ON TOP OF EXISTING.
8.1 NEW ALUMINUM FRAMED INSULATED GLASS WINDOW. SEE A601 FOR MORE INFORMATION.
8.3 NEW AIR INTAKE AND VENTILATION LOUVER. FINISH TO MATCH ADJACENT WINDOWS. MATCH WINDOW TYPE 'C'.
9.10 FROSTED FILM INSIDE GLASS TO 7'-2" AFF.
10.6 OWNER FURNISHED, OWNER INSTALLED.
10.7 FULL HEIGHT MIRROR. REFER TO SHEET A405 FOR MORE INFORMATION.
22.5 UTILITY SINK. REFER TO PLUMBING DRAWINGS.
22.7 COFFEE MAKER. BY OWNER.

your trusted advisor

consultants

engineers
architects
planners

DATE: 11/20/2019

DRAWN BY: DWJR

CHECKED BY: MAND

APPROVED BY: F.B. NO.

REVISIONS

ISSUE FOR BIDDING AND PERMIT

REV 0

DATE: 11/20/2019

DRAWN BY: DWJR

CHECKED BY: MAND

APPROVED BY: F.B. NO.

SHARONVILLE FIRE STATION 87 RENOVATION

CITY OF SHARONVILLE

11210 READING RD SHARONVILLE, OH 45241

SECOND FLOOR PLAN

SCALE: 1/4" = 1'-0"

HORZ:


VERT:

CONTRACT NO: 170636

SHEET A103

1 SECOND FLOOR PLAN

1/4" = 1'-0"



5 A602

1" / 1'-0" SLOPE

11 A302

BAY ROOF

1" / 1'-0" SLOPE

3 A201

1 A201

3 A303

5.6

1 A403

1/4" / 1'-0" SLOPE

4 A303

KITCHEN 201

JANITOR'S CLOSET 128

MECHANICAL 208

STAIR 207

DAYROOM 202

RESTROOM 203

RESTROOM 204

CORRIDOR 200

FITNESS 206

2 A301

1 A301

4 A201


1 A303

2 A303


1 A201

1 A103



11/19/2019 12:52:25 PM




3 **STAIR SECTION**
A104 3/8" = 1'-0"




1 **ENLARGED MEZZANINE PLAN**
A104 1/4" = 1'-0"



4 **ENLARGED PLAN AT FIRST FLOOR**
A104 3/8" = 1'-0"



5 **STAIR DETAIL**
A104 1 1/2" = 1'-0"




2 **APPARATUS BAY ELEVATION**
A104 1/2" = 1'-0"

KEYNOTES


- 2.1 EXISTING CONSTRUCTION TO REMAIN.
- 5.1 42" GUARDRAIL WITH INTERMEDIATES NO GREATER THAN 36" APART. PAINTED YELLOW. MOUNT TO FACE OF WALL. REFER TO STRUCTURAL DRAWINGS.
- 5.7 METAL STAIRS.
- 5.12 36" HANDRAIL.
- 5.15 FIXED WALL MOUNTED LADDER WITH HANDRAIL AND REMOVABLE SAFETY GUARD. PAINT YELLOW.
- 5.18 STEEL ANGLE. WELD TO STRINGER AND EXPANSION BOLT TO CONCRETE SLAB.
- 5.19 1/8" STEEL RISER CLOSURE.
- 5.20 1/4" END PLATE.
- 5.34 RUBBER STAIR TREAD.
- 9.1 2x2' SUSPENDED ACOUSTIC CEILING WITH AXIOM PERIMETER TRIM. REFER TO SHEET A105 FOR CEILING HEIGHTS.
- 9.14 WRAP EXPOSED EDGE OF SLAB WITH STEEL DECORATIVE CHECKER PLATE. FASTENERS @ 24" O.C. MITER CORNERS AND FILE NEATLY.
- 10.1 SEMI-RECESSED FIRE EXTINGUISHER CABINET.
- 26.2 CARD SWIPE READER.

REV	DATE	BY	REVISIONS
0	11/20/2019	MAND	ISSUE FOR BIDDING AND PERMIT
1	11/20/2019	DWJR	DRAWN BY:
2		MAND	CHECKED BY:
3		MAND	APPROVED BY:
4			F.B. NO.


SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD SHARONVILLE, OH 45241
MEZZANINE FLOOR PLAN AND STAIR DETAILS
SCALE: As indicated
HORIZ:
VERT:
CONTRACT NO:
170636
SHEET
A104




11/19/2019 12:52:28 PM




1 **FIRST FLOOR REFLECTED CEILING PLAN**
A105 1/8" = 1'-0"




2 **SECOND FLOOR REFLECTED CEILING PLAN**
A105 1/8" = 1'-0"




6 **CEILING DETAIL**
A105 1 1/2" = 1'-0"



7 **BULKHEAD, TYP.**
A105 3/4" = 1'-0"



3 **MEZZANINE REFLECTED CEILING PLAN**
A105 1/8" = 1'-0"



8 **ROOM LID @ ELECTRICAL ROOM**
A105 3/4" = 1'-0"

GENERAL NOTES

- A. UNLESS NOTED OTHERWISE, ACOUSTICAL TILE CEILING GRIDS TO BE CENTERED IN ROOM.
B. ACCESS PANEL LOCATIONS TO BE DETERMINED IN FIELD PER ACTUAL VALVE LOCATIONS AND MEP DRAWINGS.

LEGEND

SEE MECHANICAL, ELECTRICAL, AND FIRE PROTECTION DRAWINGS FOR ADDITIONAL INFORMATION.

- 2'-0" x 2'-0" ACOUSTICAL CEILING TILE.
- GYPSUM BOARD CEILING, SOFFIT, OR BULKHEAD.
- RECESSED TROFFER OR DOWNLIGHT (CAN LIGHT).
- PENDANT FIXTURE.
- EXIT SIGN.
- SUPPLY AIR DIFFUSER.
- RETURN AIR DIFFUSER OR EXHAUST FAN.

KEYNOTES

- 2.2 EXISTING ROOF HATCH BEYOND. PAINT WITH CEILING.
4.7 8" CMU.
4.17 CONTINUOUS BOND BEAM. GROUT SOLID. SEE STRUCTURAL DRAWINGS FOR REINFORCEMENT.
5.2 HSS STEEL COLUMN, PAINTED (P1). REFER TO STRUCTURAL DRAWINGS FOR SIZES AND LOCATIONS.
5.17 3-5/8" METAL STUD.
6.4 5/8" PLYWOOD SHEATHING.
6.5 1X6 WOOD FASCIA BOARD. PAINT P4.
8.2 NEW PREMANUFACTURED TANDEM INSULATED SKYLIGHT ASSEMBLY.
9.1 2x2' SUSPENDED ACOUSTIC CEILING WITH AXIOM PERIMETER TRIM. REFER TO SHEET A105 FOR CEILING HEIGHTS.
9.2 OPEN TO STRUCTURE ABOVE. PAINT EXISTING EXPOSED STRUCTURE, WIRING, PIPING AND DUCTWORK DRYFALL BLACK, TYP.
9.8 2x2' SUSPENDED ACOUSTIC CEILING SYSTEM. REFER TO A105 FOR CEILING HEIGHTS.

SHARONVILLE FIRE STATION 87 RENOVATION

CITY OF SHARONVILLE

11210 READING RD SHARONVILLE, OH 45241

REFLECTED CEILING PLANS

SCALE: As indicated
HORZ:
VERT:
CONTRACT NO:
170636
SHEET
A105

DATE	11/20/2019	DRAWN BY	DMUR	CHECKED BY	MAND	APPROVED BY	F.B. NO.
REV	0	ISSUE FOR BIDDING AND PERMIT					
REVISIONS							
BY	MAND						

DATE

REVISIONS

REV

DATE

DRAWN BY

CHECKED BY

APPROVED BY

F.B. NO.

SCALE: As indicated
HORZ:
VERT:
CONTRACT NO:
170636
SHEET
A105

DATE

REVISIONS

REV

DATE


DRAWN BY

CHECKED BY


APPROVED BY

F.B. NO.

11/19/2019 12:52:32 PM




1 **ROOF PLAN**
A106 3/16" = 1'-0"



5 **MONUMENTAL MURAL WALL ELEVATION**
A106 1/4" = 1'-0"

4 **PRECAST CAP DETAIL**
A106 3" = 1'-0"

3 **WALL SECTION**
A106 1/2" = 1'-0"



2 **ENLARGED MURAL WALL PLAN**
A106 1/2" = 1'-0"

- KEYNOTES**
- 2.1 EXISTING CONSTRUCTION TO REMAIN.
 - 3.10 PRECAST CONCRETE SILL CAP WITH DRIP EDGE. ROCKCAST PROFILE SL100.
 - 4.5 ADD ALTERNATE #1: 8" DOUBLE WYTHE CMU CANTILEVERED MURAL WALL FOR MONUMENT SIGNAGE.
 - 4.8 8" REINFORCED CMU.
 - 4.9 12" DOUBLE WYTHE CMU WALL.
 - 4.10 MODULAR BLOCK RETAINING WALL WITH CAP.
 - 4.11 CONCRETE FOOTING. REFER TO STRUCTURAL DRAWINGS.
 - 4.15 GROUT SOLID. PROVIDE GROUT WASH, TYP.
 - 5.5 METAL PANEL CANOPY, WITH DELEGATED DESIGN BASED ON LOAD PARAMETERS INDICATED ON SHEET S001. REFER TO LEGEND FOR COLORS.
 - 5.8 ALUMINUM LETTERS.
 - 7.1 NEW TPO ROOF MEMBRANE. ADD 2" NEW POLYISO INSULATION ON TOP OF EXISTING.
 - 7.15 SHEET WATER PROOFING.
 - 8.2 NEW PREMANUFACTURED TANDEM INSULATED SKYLIGHT ASSEMBLY.
 - 9.15 PRIME FOR ARTIST MURAL. ARTWORK BY MURALIST.
 - 11.1 MECHANICAL EQUIPMENT. REFER TO MEP DRAWINGS.
 - 26.1 LIGHT FIXTURE. REFER TO ELECTRICAL DRAWINGS.
 - 32.5 VERIFY LANDSCAPING WITH ARCHITECT PRIOR TO INSTALLATION THIS AREA.
 - 32.11 20' FLAGPOLE AND BASE. REFER TO 1/S101 FOR MORE INFORMATION.
 - D5.2 REMOVE EXISTING EQUIPMENT ENCLOSURE.
 - D11.1 REMOVE EXISTING ROOFTOP EQUIPMENT.

your trusted advisor
consultants
engineers
architects
planners


DATE	BY	REVISIONS	REV	DATE	BY	REVISIONS	REV
11/20/2019	MAND	ISSUE FOR BIDDING AND PERMIT	0				

DATE	DRAWN BY	CHECKED BY	APPROVED BY	F.B. NO.
11/20/2019	DWJR	MAND		

SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD SHARONVILLE, OH 45241

ROOF PLAN AND MURAL WALL DETAILS


SCALE:	As indicated
HORZ:	
VERT:	
CONTRACT NO:	170636
SHEET	A106




7 **SIGNAGE DISPLAY 1**
A201 1/2" = 1'-0"




6 **SIGNAGE DISPLAY 2**
A201 1/2" = 1'-0"




5 **SIGNAGE DISPLAY 3**
A201 1/2" = 1'-0"




3 **NORTH ELEVATION**
A201 1/8" = 1'-0"



4 **EAST ELEVATION**
A201 1/8" = 1'-0"




1 **SOUTH ELEVATION**
A201 1/8" = 1'-0"



2 **WEST ELEVATION**
A201 1/8" = 1'-0"

METAL WALL PANEL COLOR LEGEND



KEYNOTES

- 2.1 EXISTING CONSTRUCTION TO REMAIN.
- 3.1 CMU WALL WITH STUCCO FINISH TO MATCH EXTERIOR FACE FLUSH WITH ADJACENT. ARCHITECT TO VERIFY TYPICAL MATCHING TEXTURE PRIOR TO PLACEMENT.
- 3.3 EXISTING CONCRETE STAIR. PRESSURE WASH AND SEAL TREADS AND RISERS.
- 4.1 INFILL WITH 12" CMU. ALIGNED TO ADJACENT INTERIOR WALLS.
- 4.4 PRESSURE WASH AND SEAL EXISTING EXPOSED CONCRETE.
- 5.2 HSS STEEL COLUMN. PAINTED (P1). REFER TO STRUCTURAL DRAWINGS FOR SIZES AND LOCATIONS.
- 5.3 SINGLE SKIN METAL VERTICAL WALL PANELS. REFER TO LEGEND FOR COLORS.
- 5.5 METAL PANEL CANOPY, WITH DELEGATED DESIGN BASED ON LOAD PARAMETERS INDICATED ON SHEET S001. REFER TO LEGEND FOR COLORS.
- 5.9 COLD FORMED METAL FRAMED CANOPY WITH CORRUGATED METAL SIDING.
- 5.21 PATCH BEYOND WITH METAL STUDS AS REQUIRED.
- 5.24 6" DIA. BOLLARD. PAINTED.
- 5.35 4" HIGH PERFORATED METAL SCREEN (RED).
- 8.2 NEW PREMANUFACTURED TANDEM INSULATED SKYLIGHT ASSEMBLY.
- 8.3 NEW AIR INTAKE AND VENTILATION LOUVER. FINISH TO MATCH ADJACENT WINDOWS. MATCH WINDOW TYPE 'C'.
- 8.4 STOREFRONT SYSTEM WITH TEMPERED GLASS.
- 8.5 STOREFRONT SYSTEM WITH SPANDREL GLASS.
- 8.8 NEW AIR INTAKE AND VENTILATION LOUVER. REFER TO MECHANICAL DRAWINGS FOR MORE INFORMATION.
- 10.3 MEMORIAL LETTERS SALVAGED FROM EXISTING BUILDING.
- 10.4 ALUMINUM LETTERING.
- 10.5 DO NOT DISTURB GOVERNMENT USGS FIELD EQUIPMENT. CONTACT TOM HARRIS AT 1 (816) 805-7194 OR THARRIS@USGS.GOV FOR REMOVAL PRIOR TO DEMOLITION.
- 11.7 DRYER EXHAUST VENT.
- 26.1 LIGHT FIXTURE. REFER TO ELECTRICAL DRAWINGS.
- 26.2 CARD SWIPE READER.
- D10.1 REMOVE EXISTING PLAQUE AND RETURN TO OWNER.
- D32.5 REMOVE EXISTING FLAGPOLE ASSEMBLY. PATCH MASONRY WITH GROUT. SOLID.

your trusted advisor
engineers
architects
planners

DATE	BY	REVISIONS	ISSUE FOR BIDDING AND PERMIT
11/20/2019	MAND		

DATE	DRAWN BY	CHECKED BY	APPROVED BY	P.G.
11/20/2019	DWJR			


SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD SHARONVILLE, OH 45241

BUILDING ELEVATIONS


SCALE:	As indicated
HORZ:	
VERT:	
CONTRACT NO:	
	170636
SHEET	
	A201

KEYNOTES

- 2.1 EXISTING CONSTRUCTION TO REMAIN.
3.0 EXISTING CONCRETE SLAB.
3.4 NEW CONCRETE SLAB. REFER TO STRUCTURAL DRAWINGS.
3.9 TOOTH IN PROPOSED MASONRY TO MATCH EXISTING.
3.11 4" METAL DECK WITH 2" CONCRETE.
5.3 SINGLE SKIN METAL VERTICAL WALL PANELS. REFER TO LEGEND FOR COLORS.
5.7 METAL STAIRS.
5.12 3/8" HANDRAIL.
7.1 NEW TPO ROOF MEMBRANE. ADD 2" NEW POLYISO INSULATION ON TOP OF EXISTING.
8.2 NEW PREMANUFACTURED TANDEM INSULATED SKYLIGHT ASSEMBLY.
9.1 2x2" SUSPENDED ACOUSTIC CEILING WITH AXIOM PERIMETER TRIM. REFER TO SHEET A105 FOR CEILING HEIGHTS.
10.1 SEMI-RECESSED FIRE EXTINGUISHER CABINET.
12.3 18"x18" LOCKABLE PLASTIC LAMINATE PASS-THRU LOCKERS. REFER TO 13/14/A404 FOR DIMENSIONS AND DETAILS.



2 BUILDING SECTION
A301 1/4" = 1'-0"



1 BUILDING SECTION
A301 1/4" = 1'-0"

your trusted advisor

engineers
architects
planners

T







consultants

DATE:	11/20/2019	DRAWN BY:	DWJR	CHECKED BY:	MAND	APPROVED BY:		F.B. NO.	
REV	0	ISSUE FOR BIDDING AND PERMIT							
DATE	11/20/2019	MAND							
BY	MAND								


SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD SHARONVILLE, OH 45241

BUILDING SECTIONS


SCALE:	1/4" = 1'-0"
HORIZ:	
VERT:	
CONTRACT NO:	170636
SHEET	A301




11/19/2019 12:52:47 PM




1 WALL SECTION
A303 3/4" = 1'-0"



2 WALL SECTION
A303 3/4" = 1'-0"



3 WALL SECTION
A303 3/4" = 1'-0"



4 WALL SECTION
A303 3/4" = 1'-0"

- KEYNOTES**
- 2.1 EXISTING CONSTRUCTION TO REMAIN.
 - 3.5 NEW CONCRETE RAMP UP TO EXISTING STOOP. SAWCUT AND REMOVE EXISTING DRIVE TO INSTALL.
 - 4.7 8" CMU.
 - 5.2 HSS STEEL COLUMN, PAINTED (P1). REFER TO STRUCTURAL DRAWINGS FOR SIZES AND LOCATIONS.
 - 5.3 SINGLE SKIN METAL VERTICAL WALL PANELS. REFER TO LEGEND FOR COLORS.
 - 5.6 42" GUARDRAIL WITH INTERMEDIATES NO GREATER THAN 4" CLEAR. PAINTED.
 - 5.8 ALUMINUM LETTERS.
 - 5.11 7/8" HAT CHANNEL. GALVANIZED.
 - 5.13 GALVANIZED METAL DECK.
 - 5.16 PREFINISHED METAL COPING.
 - 6.2 CONTINUOUS PRESSURE TREATED WOOD BLOCKING.
 - 7.1 NEW TPO ROOF MEMBRANE. ADD 2" NEW POLYISO INSULATION ON TOP OF EXISTING.
 - 7.2 R-15 BATT INSULATION.
 - 7.3 METAL FLASHING.
 - 7.9 3" INSULATED METAL SOFFIT PANEL.
 - 9.1 2x2' SUSPENDED ACOUSTIC CEILING WITH AXIOM PERIMETER TRIM. REFER TO SHEET A105 FOR CEILING HEIGHTS.
 - 9.4 5/8" TYPE X GYPSUM WALL BOARD.
 - 9.8 2x2' SUSPENDED ACOUSTIC CEILING SYSTEM. REFER TO A105 FOR CEILING HEIGHTS.
 - 9.9 GYPSUM WALL BOARD AND METAL STUD CEILING. REFER TO 8/A105.
 - 26.1 LIGHT FIXTURE. REFER TO ELECTRICAL DRAWINGS.

SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD SHARONVILLE, OH 45241

WALL SECTIONS

SCALE: 3/4" = 1'-0"

HORIZ: _____

VERT: _____

CONTRACT NO: 170636

SHEET A303

DATE: 11/20/2019

DRAWN BY: DWJR

CHECKED BY: MAND

APPROVED BY: _____

F.B. NO. _____

PG. _____

REVISIONS


REV	DATE	DESCRIPTION
0	11/20/2019	ISSUE FOR BIDDING AND PERMIT

BY: MAND


DATE: 11/20/2019

your trusted advisor
engineers
architects
consultants
planners


11/19/2019 12:52:51 PM




10
A401
ENLARGED RESTROOM PLAN
1/2" = 1'-0"




11
A401
INTERIOR RESTROOM ELEVATION
1/2" = 1'-0"




12
A401
INTERIOR RESTROOM ELEVATION
1/2" = 1'-0"



13
A401
INTERIOR RESTROOM ELEVATION
1/2" = 1'-0"




14
A401
INTERIOR RESTROOM ELEVATION
1/2" = 1'-0"




15
A401
TYP. WATER CLOSET LAYOUT
1/2" = 1'-0"


KEYNOTES
7.19 4" CURB.
9.10 FROSTED FILM INSIDE GLASS TO 7'-2" AFF.




5
A401
INTERIOR RESTROOM ELEVATION
1/2" = 1'-0"




6
A401
INTERIOR RESTROOM ELEVATION
1/2" = 1'-0"




7
A401
INTERIOR RESTROOM ELEVATION
1/2" = 1'-0"




8
A401
INTERIOR RESTROOM ELEVATION
1/2" = 1'-0"




9
A401
INTERIOR RESTROOM ELEVATION
1/2" = 1'-0"




1
A401
FIRST FLOOR ENLARGED RESTROOM PLAN
1/2" = 1'-0"



2
A401
INTERIOR RESTROOM ELEVATION
1/2" = 1'-0"



3
A401
INTERIOR RESTROOM ELEVATION
1/2" = 1'-0"







4
A401
INTERIOR RESTROOM ELEVATION
1/2" = 1'-0"

SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD SHARONVILLE, OH 45241
ENLARGED RESTROOM PLANS AND DETAILS

SCALE: 1/2" = 1'-0"
HORIZ:
VERT:
CONTRACT NO: 170636
SHEET A401

REV	DATE	BY	REVISIONS
0	11/20/2019	MAND	ISSUE FOR BIDDING AND PERMIT
1		DWJR	
2		MAND	
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			
13			
14			
15			
16			
17			
18			
19			
20			
21			
22			
23			
24			
25			
26			
27			
28			
29			
30			
31			
32			
33			
34			
35			
36			
37			
38			
39			
40			
41			
42			
43			
44			
45			
46			
47			
48			
49			
50			
51			
52			
53			
54			
55			
56			
57			
58			
59			
60			
61			
62			
63			
64			
65			
66			
67			
68			
69			
70			
71			
72			
73			
74			
75			
76			
77			
78			
79			
80			
81			
82			
83			
84			
85			
86			
87			
88			
89			
90			
91			
92			
93			
94			
95			
96			
97			
98			
99			
100			









your trusted advisor
consultants
engineers
architects
planners



KEYNOTES


7.19 4" CURB.

9.10 FROSTED FILM INSIDE GLASS TO 7'-2" AFF.



ACCESSORIES SCHEDULE		
<p>ALL FIXTURES TO BE HANDICAPPED ACCESSIBLE (HC) SHALL BE INSTALLED AT HEIGHTS AND LOCATIONS THAT ARE ACCESSIBLE PER ADA GUIDELINES. ALL OTHER ACCESSORIES SHALL BE INSTALLED AT HEIGHTS RECOMMENDED BY MFR.</p> <p>SEE PLANS FOR QUANTITY AND LOCATION OF ACCESSORIES, AND SEE SPECIFICATIONS FOR ADDITIONAL DESCRIPTIONS. PROVIDE BLOCKING FOR SURFACE MOUNTED ACCESSORIES (GRAB BARS, DISPENSERS, ETC...) AS REQUIRED</p>		
ABBREV.	ITEM	MFG. NO. / DESCRIPTION (BASIS OF DESIGN)
BE	BENCH (3'-6" LONG)	HARDWOOD BENCH WITH STEEL PEDESTALS.
CH	CLOTHES/TOWEL HOOK	BOBRICK MODEL B-6827.
CUR	SHOWER CURTAIN	BOBRICK MODEL 204-3.
EWC	ELECTRIC WATER COOLER WITH BOTTLE FILLING STATION (HC ACCESSIBLE AS INDICATED)	SEE PLUMBING DRAWINGS.
FD	FLOOR DRAIN	SEE PLUMBING DRAWINGS.
GB1	GRAB BAR 36"	BOBRICK MODEL B-6806 SERIES.
GB2	GRAB BAR 42"	BOBRICK MODEL B-6806 SERIES.
GB3	GRAB BAR 24" (VERTICAL)	BOBRICK MODEL B-6806 SERIES.
GB4	SHOWER GRAB BAR	BOBRICK MODEL B-6861.
LAV1	LAVATORY (STANDARD HC ACCESSIBLE HT.)	SEE PLUMBING DRAWINGS.
LAV2	LAVATORY (STANDARD HC ACCESSIBLE HT.)	SEE PLUMBING DRAWINGS.
L1	LOCKER	.
MB	MOP BASIN	SEE PLUMBING DRAWINGS.
MR	MIRROR 24" x 36"	BOBRICK MODEL B-290 2436.
PTD	SURFACE-MOUNTED PAPER TOWEL DISPENSER	BOBRICK MODEL B-4262.
SCH	SHOWER CURTAIN HOOKS	BOBRICK MODEL 204-1.
SCR	SHOWER CURTAIN ROD	BOBRICK MODEL B-6107.
SH	SHELF	BOBRICK MODEL B-295.
TTD	TOILET TISSUE DISPENSER	BOBRICK MODEL B-4288.
WC / HC WC	WATER CLOSET / STANDARD HC ACCESSIBLE HT. WATER CLOSET	SEE PLUMBING DRAWINGS.
WR	WASTE RECEPTACLE	BOBRICK MODEL B-277.

11/19/2019 12:52:57 PM



KEYNOTES

- 2.1 EXISTING CONSTRUCTION TO REMAIN.
- 8.6 4" FAN EXHAUST BOTH ENDS.
- 8.7 3 5/8" METAL STUD FRAMING AROUND OPENING.
- 9.1 2x2" SUSPENDED ACOUSTIC CEILING WITH AXIOM PERIMETER TRIM. REFER TO SHEET A105 FOR CEILING HEIGHTS.
- 10.6 OWNER FURNISHED, OWNER INSTALLED.
- 10.8 OWNER FURNISHED, CONTRACTOR INSTALLED.
- 11.6 COMMERCIAL RANGE HOOD.
- 12.3 18"x18" LOCKABLE PLASTIC LAMINATE PASS-THRU LOCKERS. REFER TO 13/14/A404 FOR DIMENSIONS AND DETAILS.
- 12.4 LOCKABLE, FULL HEIGHT PLASTIC LAMINATE PANTRY.
- 22.7 COFFEE MAKER, BY OWNER.

your trusted advisor

engineers
architects
consultants
planners

T

consultants

REV	DATE	BY	REVISIONS
0	11/20/2019	MAND	ISSUE FOR BIDDING AND PERMIT
1	11/20/2019	DWJR	DATE: 11/20/2019
2	11/20/2019	MAND	DRAWN BY: DWJR
3	11/20/2019	MAND	CHECKED BY: MAND
4	11/20/2019	MAND	APPROVED BY: MAND
5	11/20/2019	MAND	PG. NO.

SHARONVILLE FIRE STATION 87 RENOVATION

CITY OF SHARONVILLE

11210 READING RD SHARONVILLE, OH 45241

INTERIOR ELEVATIONS AND TYPICAL DETAILS

SCALE: As indicated

HORZ: 1" = 1'-0"


VERT: 1" = 1'-0"

CONTRACT NO: 170636


SHEET A403

KEYNOTES


- 2.1 EXISTING CONSTRUCTION TO REMAIN.
4.1 INFILL WITH 12" CMU, ALIGNED TO ADJACENT INTERIOR WALLS.
9.7 4" RUBBER COVE BASE.
12.3 18"x18" LOCKABLE PLASTIC LAMINATE PASS-THRU LOCKERS. REFER TO 13/14/A404 FOR DIMENSIONS AND DETAILS.
12.5 FULL-HEIGHT MIRROR.




8 **105 - SOUTH**
A404 1/2" = 1'-0"




9 **106 - SOUTH**
A404 1/2" = 1'-0"




10 **109 - NORTH**
A404 1/2" = 1'-0"




11 **110 - NORTH**
A404 1/2" = 1'-0"




12 **111 - NORTH**
A404 1/2" = 1'-0"




5 **206 - NORTH**
A404 1/2" = 1'-0"




6 **117 EAST**
A404 1/2" = 1'-0"




7 **118 SOUTH**
A404 1/2" = 1'-0"




1 **120 - NORTH**
A404 1/2" = 1'-0"



2 **120 - EAST**
A404 1/2" = 1'-0"



3 **120 - SOUTH**
A404 1/2" = 1'-0"





4 **120 - WEST**
A404 1/2" = 1'-0"






ROOM FINISH SCHEDULE											
ABBREVIATIONS					REMARKS						
ACT CPT CONC CT EXP.	ACOUSTICAL CEILING TILE CARPET SEALED CONCRETE CERAMIC TILE EXPOSED	P-CONC P-GB P-MAS RB	POLISHED CONCRETE PAINTED GYPSUM BOARD PAINTED MASONRY RUBBER BASE	1. SEE A402/A403 FOR LOCATION OF CERAMIC WALL TILE.							
ROOM NO.	ROOM NAME	BASE	FLOOR	WALLS					CEILINGS		REMARKS
				NORTH	EAST	SOUTH	WEST	ALL	MAT.	HEIGHT	
100	VESTIBULE	RB	P-CONC	P-GB	P-MAS	P-GB	P-GB		ACT-1	9' - 0"	
101	CORRIDOR	RB	P-CONC	-	-	-	-	P-GB	EXP.	-	
102	CORRIDOR	RB	P-CONC	-	-	-	-	P-GB	ACT-2	9' - 0"	
103	LT OFFICE	RB	CPT	P-GB	P-MAS	P-GB	P-MAS		ACT-1	9' - 0"	
104	LT BUNK	RB	CPT	P-GB	P-GB	P-GB	P-MAS		ACT-2	9' - 0"	
105	FF BUNK	RB	CPT	-	-	-	-	P-GB	ACT-2	9' - 0"	
106	RESTROOM	RB	P-CONC	-	-	-	-	P-GB / CT	ACT-1	9' - 0"	1.
107	RESTROOM	RB	P-CONC	-	-	-	-	P-GB / CT	ACT-1	9' - 0"	1.
108	FF BUNK	RB	CPT	-	-	-	-	P-GB	ACT-2	9' - 0"	
109	MECHANICAL CLOSET	-	CONC	-	-	-	-	P-GB	EXP.	-	
110	FF BUNK	RB	CPT	-	-	-	-	P-GB	ACT-2	9' - 0"	
111	FF BUNK	RB	CPT	-	-	-	-	P-GB	ACT-2	9' - 0"	
112	LAUNDRY	RB	P-CONC	-	-	-	-	P-GB	ACT-2	9' - 0"	
113	JANITOR'S CLOSET	RB	CONC	-	-	-	-	P-GB	EXP.	9' - 0"	
114	FF OFFICE	RB	CPT	-	-	-	-	P-GB	ACT-1	9' - 0"	
115	SERVER	RB	CONC	-	-	-	-	P-GB	EXP.	-	
116	CORRIDOR	RB	CONC	P-GB	P-GB / P-MAS	P-GB	P-GB		ACT-3	9' - 0"	
117	TOOLS/STORAGE	RB	CONC	P-GB	P-MAS	P-MAS	P-GB		EXP.	9' - 0"	
118	SCBA	RB	CONC	P-GB	P-GB	P-MAS	P-GB		EXP.	9' - 0"	
119	DECON	RB	CONC	P-GB	P-GB	P-MAS	P-MAS		EXP.	9' - 0"	
120	TURNOUT GEAR	RB	CONC	P-GB	P-GB	P-GB	P-MAS		EXP.	9' - 0"	
121	STORAGE	RB	CONC	-	-	-	-	P-GB	EXP.	9' - 0"	
122	EMS SUPPLY	RB	CONC	-	-	-	-	P-GB	ACT-3	9' - 0"	
123	RESTROOM	RB	CONC	-	-	-	-	P-GB	ACT-3	9' - 0"	
124	ELECTRICAL	-	CONC	-	-	-	-	E-MAS	ACT-3	9' - 0"	
125	APPARATUS BAY	-	CONC	P-MAS	P-MAS	P-GB / P-MAS	P-MAS		EXP.	-	
126	CLOSET	-	CONC	-	-	-	-	E-MAS	EXP.	-	
127	HOSE STORAGE	-	CONC	P-MAS	P-MAS	-	-		EXP.	-	
128	JANITOR'S CLOSET	RB	CONC	-	-	-	-	P-GB	EXP.	-	
129	STAIR	-	CONC	-	P-GB	P-GB	P-GB		EXP.	-	
130	MEZZANINE	-	CONC	-	P-MAS	P-GB	P-GB		EXP.	-	
200	CORRIDOR	RB	P-CONC	-	-	-	-	P-GB	ACT-1 / EXP.	10' - 6"	
201	KITCHEN	RB	P-CONC	P-GB	-	P-GB	P-GB		ACT-1 / EXP.	10' - 6"	
202	DAYROOM	RB	CONC / CPT	P-GB	P-GB	-	-		ACT-1 / EXP.	10' - 6"	
203	RESTROOM	RB	P-CONC	-	-	-	-	P-GB / CT	ACT-1	10' - 6"	1.
204	RESTROOM	RB	P-CONC	-	-	-	-	P-GB / CT	ACT-1	10' - 6"	1.
206	FITNESS	RB	RAF	-	-	-	-	P-GB	ACT-2	10' - 6"	
207	STAIR	-	P-CONC	-	P-GB	P-GB	P-GB		ACT-1 / EXP.	10' - 6"	
208	MECHANICAL	-	CONC	-	-	-	-	P-GB	EXP.	10' - 6"	

MATERIAL SPECIFICATION											
ABBR.		ITEM				ABBR.		ITEM			
WALLS						CEILINGS					
P1	PAINT	MANUF.	SHERWIN WILLIAMS			ACT1	ACOUSTIC CEILING TILE	MANUF.	ARMSTRONG CEILING SOLUTIONS		
	COLOR:	ICICLE			TYPE:		SHASTA				
	ITEM #:	SW6238			COLOR:		WHITE				
					ITEM #:		-				
P2	PAINT	MANUF.	SHERWIN WILLIAMS			ACT2	ACOUSTIC CEILING TILE	MANUF.	ARMSTRONG CEILING SOLUTIONS		
	COLOR:	EARL GREY			TYPE:		ULTIMA				
	ITEM #:	SW7660			COLOR:		WHITE				
					ITEM #:		1902				
P3	PAINT	MANUF.	SHERWIN WILLIAMS			ACT3	ACOUSTIC CEILING TILE	MANUF.	ARMSTRONG CEILING SOLUTIONS		
	COLOR:	CYBERSPACE			TYPE:		KITCHEN ZONE				
	ITEM #:	SW7076			COLOR:		WHITE				
					ITEM #:		673				
P4	PAINT	MANUF.	SHERWIN WILLIAMS			GWB	GYPSUM WALL BOARD	MANUF.	-		
	COLOR:	RED BAY			COLOR:		-				
	ITEM #:	SW6321			ITEM #:		-				
WP1	VERTICAL METAL WALL PANEL	MANUF.	METLSPAN			SS1	POLISHED CONCRETE	MANUF.	-		
	COLOR:	BRITE RED			COLOR:		-				
	ITEM #:	434R843			ITEM #:		-				
WP2	VERTICAL METAL WALL PANEL	MANUF.	METLSPAN			SS2	SOLID SURFACE	MANUF.	FORMICA		
	COLOR:	SNOW WHITE			COLOR:		WHITE SPEX				
	ITEM #:	431R539			ITEM #:		931				
T1	CERAMIC TILE	MANUF.	DALTILE			PL1	PLASTIC LAMINATE	MANUF.	ARBORITE		
	COLOR:	11% - BLACK D311 89% - BISCUIT D317			COLOR:		CHARCOAL				
	ITEM #:	2x1 D00021WIND			ITEM #:		S434CA				
T2	PORCELAIN TILE	MANUF.	DALTILE			PL2	PLASTIC LAMINATE	MANUF.	ARBORITE		
	COLOR:	11% - RED D017 89% - PEPPER WHITE D037			COLOR:		BERGUNDY				
	ITEM #:	2x1 D00021WIND			ITEM #:		S419CA				
FLOORS						PL3	PLASTIC LAMINATE	MANUF.	ARBORITE		
SC	SEALED CONCRETE	MANUF.	-				COLOR:	DARK SUGAR CANE			
	COLOR:	-			ITEM #:		W-434 RM				
	ITEM #:	-									
CPT	CARPET TILE	MANUF.	MILLIKEN			RB	4" RUBBER COVE BASE	MANUF.	JOHNSONITE TARKETT		
	COLOR:	CHROMA W/ SMOLDER			COLOR:		TG4 - BLACK MAGIC				
	ITEM #:	CUR109-119			ITEM #:		4" DURACOVE				
RAF	RUBBERIZED ATHLETIC FLOORING	MANUF.	THOR PERFORMANCE PRODUCTS								
	COLOR:	REGUPOL AKTIV - THUNDER GREY									
	ITEM #:	AP95102									

PARTITION HEADS



WALL TYPES



FLOORING TRANSITION DETAIL


2
A501 6" = 1'-0"





SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD SHARONVILLE, OH 45241
ROOM FINISH SCHEDULE AND WALL TYPES

SCALE: As indicated
HORIZ:
VERT:
CONTRACT NO: 170636
SHEET A501

DATE: 11/20/2019
DRAWN BY: DWJR
CHECKED BY: MAND
APPROVED BY:
F.B. NO.
REV 0
ISSUE FOR BIDDING AND PERMIT
REVISIONS
DATE 11/20/2019
BY MAND
MAND

your trusted advisor
engineers
architects
planners
consultants





- 2.1 EXISTING CONSTRUCTION TO REMAIN.
- 3.1 CMU WALL WITH STUCCO FINISH TO MATCH EXTERIOR FACE FLUSH WITH ADJACENT. ARCHITECT TO VERIFY TYPICAL MATCHING TEXTURE PRIOR TO PLACEMENT.
- 3.8 NEW CONCRETE RAMP UP TO EXISTING SLAB.
- 3.13 NEW CONCRETE INFILL. SLOPE RAMP TO EXISTING.
- 4.19 12" CMU.
- 5.2 5/8" STEEL COLUMN, PAINTED (P1). REFER TO STRUCTURAL DRAWINGS FOR SIZE AND LOCATIONS.
- 5.3 SINGLE SKIN METAL VERTICAL WALL PANELS. REFER TO LEGEND FOR COLORS.
- 5.5 METAL PANEL CANOPY, WITH DELEGATED DESIGN BASED ON LOAD PARAMETERS INDICATED ON SHEET S001. REFER TO LEGEND FOR COLORS.
- 5.10 3 5/8" METAL STUDS.
- 5.11 7/8" HAT CHANNEL, GALVANIZED.
- 5.14 ADHESIVE ANCHORS DESIGNED BY CANOPY DESIGNER. GROUT SOLID CMU CORES AT ANCHORS. UNLESS OTHERWISE NOTED, ADHESIVE ANCHORS SHALL HAVE SCREEN TUBES FOR INSTALLATION IN BRICK AND/OR HOLLOW CMU. ANCHORAGE TO ONLY THE FACE BRICK IS UNACCEPTABLE.
- 5.22 BLACK BREAK METAL.
- 5.24 6" DIA. BOLLARD, PAINTED.
- 5.25 METAL WALL PANEL SYSTEM TRIM.
- 5.30 SINGLE SKIN FLAT METAL PANEL, WHITE.
- 5.31 8" METAL STUDS @ 24" O.C., TYP.
- 5.32 SCHEDULED FASTENERS. SEE STRUCTURAL GENERAL NOTES.
- 5.33 FASTENERS.
- 6.6 2x4 CONTINUOUS PRESSURE TREATED WOOD BLOCKING.
- 7.1 NEW TPO ROOF MEMBRANE. ADD 2" NEW POLYISO INSULATION ON TOP OF EXIST.
- 7.2 R-15 BATT INSULATION.
- 7.3 METAL FLASHING.
- 7.5 SEALANT.
- 7.9 3" INSULATED METAL SOFFIT PANEL.
- 7.18 4" METAL BACK FLASHING.
- 8.2 NEW PREMANUFACTURED TANDEM INSULATED SKYLIGHT ASSEMBLY.
- 9.4 5/8" TYPE X GYPSUM WALL BOARD.
- 11.6 COMMERCIAL RANGE HOOD.

SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD SHARONVILLE, OH 45241





























DETAILS

SCALE:	As indicated
HORIZ:	
VERT:	
CONTRACT NO:	
	170636
SHEET	
	A602

ESSENTIAL FACILITY SEISMIC REQUIREMENTS

SEISMIC BRACING FOR ALL NON-STRUCTURAL COMPONENTS INCLUDING BUT NOT LIMITED TO EQUIPMENT, PIPING, CONDUIT AND DUCTWORK IS REQUIRED FOR THIS PROJECT. THE DESIGN AND INSTALLATION OF THE SEISMIC RESTRAINT DEVICES IS DELEGATED TO THE CONTRACTOR. REFER TO SEISMIC CONTROLS SPECIFICATION FOR DELEGATED DESIGN SUBMITTAL REQUIREMENTS.

PLUMBING LEGEND


SYMBOL	DESCRIPTION
PLUMBING ACCESSORIES	
	UNION
	PIPE CAP
	STRAINER
	PRESSURE GAUGE
	THERMOMETER
	FCO - FLOOR CLEANOUT, GCO - GRADE CLEANOUT
	CO - CLEANOUT, WCO - WALL CLEANOUT
	FLOOR DRAIN, AREA DRAIN
	TRENCH DRAIN
	ROOF DRAIN (PRIMARY), OVERFLOW DRAIN (SECONDARY)
	EXPANSION TANK
PIPE VALVES	
	SHUT-OFF VALVE
	CHECK VALVE
	BALANCING VALVE
	PRESSURE REGULATOR VALVE
	GAS PRESSURE REGULATOR
	PRESSURE AND TEMPERATURE RELIEF VALVE
	BACKFLOW PREVENTER
	DOUBLE CHECK VALVE BACKFLOW PREVENTER
	FROST PROOF WALL HYDRANT (EXTERIOR)
	HOSE BIBB (INTERIOR)
	TRAP PRIMER VALVE
PLUMBING SYMBOLS	
	PIPE UP
	PIPE DOWN
	PIPE TEE DOWN
	PIPE TEE UP
	CONNECT TO EXISTING (FIELD VERIFY EXISTING UTILITY SERVICE TYPE, PRIOR TO MAKING CONNECTION)
	VENT THROUGH ROOF

STANDARD PLUMBING ABBREVIATIONS


AAVE	ARCHITECT / ENGINEER	INST	INSTALLED
AD	AIR ADMITTANCE VALVE	KW	KILOWATT
AD	AREA DRAIN	KWH	KILOWATT HOUR
AFB	ABOVE FINISHED FLOOR	LPG	LIQUID PROPANE GAS
AFB	ABOVE FINISHED GRADE	LV	LAVATORY
ANSI	AMERICAN NATIONAL	MAU	MAKE-UP AIR UNIT
STANDARDS	INSTITUTE	MAX	MAXIMUM
APPROX	APPROXIMATE	MBH	1000 BTUH
ASPE	AMERICAN SOCIETY OF	MH	MANHOLE
PLUMBING	ENGINEERS	MIN	MINIMUM
AV	ACID VENT	MOCOP	MAXIMUM OVERCURRENT
AW	ACID WASTE		PROTECTION
BAS	BUILDING AUTOMATION SYSTEM	MS	MOP SINK
BFP	BACKFLOW PREVENTER	MV	MIXING VALVE
BT	BATHTUB	N	NITROGEN
BTU	BRITISH THERMAL UNIT	NC	NATURALLY CLOSED
BTUH	BRITISH THERMAL UNIT PER	NG	NATURAL GAS
HOUR		NIC	NOT IN CONTRACT
BWV	BACK WATER VALVE	NO	NITROUS OXIDE
CA	COMPRESSED AIR	NOM	NOMINAL
CF	CATCH BASIN	NT	NOT TO SCALE
CFH	CUBIC FEET PER HOUR	O	OXYGEN
CFM	CUBIC FEET PER MINUTE	OCF	OVER CURRENT PROTECTION
CI	CAST IRON	OD	OVERFLOW DRAIN
CO	CLEAN OUT	OI	OLEO INTERCEPTOR
CONC	CARBON DIOXIDE	PC	PRESSING CONTRACTOR
COMP	COMPRESSOR UNIT	PPM	PARTS PER MILLION
CP	CIRCULATION PUMP	PRV	PRESSURE REGULATING VALVE
CPVC	CHLORINATED POLYVINYL	PSI	POUNDS PER SQUARE INCH
	CHLORIDE	PSIA	POUNDS PER SQUARE INCH - ABSOLUTE
CW	COLD WATER (POTABLE)		POUNDS PER SQUARE INCH -
DF	DRAINING FOUNTAIN	PSIG	
DI	DEIONIZED WATER	GAGE	
DIA	DIAMETER	PVC	POLYVINYL CHLORIDE
DN	DOWN	RD	ROOF DRAIN
DS	DROPSPOUT	RH	REFUSE HYDRANT
EC	ELECTRICAL CONTRACTOR	RS	REVERSE OSMOSIS
ET	EXPANSION TANK	RPZ	REDUCED PRESSURE ZONE
EW	ELECTRIC WATER COOLER		
EW	ELECTRIC WATER HEATER	RTU	ROOF TOP UNIT
EX	EXISTING	S	SANITARY
	FAHRENHEIT	SI	SOLIDS INTERCEPTOR
FCO	FLOOR CLEAN OUT	SK	SINK
FD	FLOOR DRAIN	SOFT	SOFT WATER
FLE	FINISHED FLOOR ELEVATION	SPEC	SPECIFICATION
FLA	FULL LOAD AMPERES	SQ FT	SQUARE FOOT (FEET)
FS	FLOOR SINK	SS	STAINLESS STEEL
FT	FEET	ST	STORM PIPING
FW	FILTERED WATER	TD	TRENCH DRAIN
G	GAS	TDH	TOTAL DYNAMIC HEAD
GCO	GRADE CLEAN OUT	TEMP	TEMPERATURE
GWH	GRADE WIRE WATER HEATER	TM	TEMPERATURE MIXING VALVE
GI	GREASE INTERCEPTOR	TP	TRAP PRIMER
GPD	GALLONS PER DAY	UH	UNIT HEATER
GPH	GALLONS PER HOUR	UN	UNION
GPM	GALLONS PER MINUTE	UR	URINAL
GS	GAS PRESSURE REGULATOR	VACUM	VACUUM
GW	GREASE WASTE	VFD	VARIABLE FREQUENCY DRIVE
H&CW	HOT & COLD WATER	VP	VACUUM PUMP
HC	HOSE BIBB	VTR	VENT THRU ROOF
HB	HVAC CONTRACTOR	WAGD	WASTE ANESTHESIA GAS
HDRAIN	HOT DRAIN	WB	WASHER BOX
HDPE	HIGH DENSITY POLYETHYLENE	WC	WATER CLOSET
HP	HORSEPOWER	WCO	WALL CLEAN OUT
HT	HOT TAP	WH	WALL HYDRANT
HW	HOT WATER	WF	WATER FILTER
HW	HOT WATER RETURN	YH	YARD HYDRANT
IE	INVERT ELEVATION		
IN WC	INCH WATER COLUMN		

PLUMBING UTILITY CONTACT INFO

DOMESTIC WATER	
UTILITY COMPANY	GREATER CINCINNATI WATER WORKS
PHONE NUMBER	513-591-7700
SANITARY SEWER	
UTILITY COMPANY	METROPOLITAN SEWER DISTRICT OF GREATER CINCINNATI
PHONE NUMBER	513-557-3594
NATURAL GAS	
UTILITY COMPANY	DUKE ENERGY
UTILITY CONTACT	BRANDON PONDER
PHONE NUMBER	513-287-1464
EMAIL ADDRESS	BRANDON.PONDER@DUKE-ENERGY.COM
METER FURNISHED BY	DUKE ENERGY
METER INSTALLED BY	DUKE ENERGY
AVAILABLE PRESSURE AT MAIN	HIGH PRESSURE
REQUIRED BUILDING PRESSURE	2 PSI
HEALTH DEPARTMENT	
HEALTH DEPARTMENT	CITY OF CINCINNATI HEALTH DEPARTMENT
PHONE NUMBER	513-564-1751



1
P-101
FIRST FLOOR PLUMBING DEMOLITION PLAN
1/8" = 1'-0"



3
P-101
SECOND FLOOR PLUMBING DEMOLITION PLAN
1/8" = 1'-0"

PLUMBING GENERAL DEMO NOTES

- A. DEMOLISH ALL PLUMBING FIXTURES, EQUIPMENT AND ASSOCIATED PIPING UNLESS OTHERWISE NOTED.
B. DEMOLISH ALL ABOVE GROUND HOT WATER AND COLD WATER PIPING BACK TO WATER SERVICE ENTRANCE AND CAP.
C. DEMOLISH ALL GAS PIPING BACK TO GAS METER. EXISTING GAS METER TO REMAIN. COORDINATE REPLACING THE REGULATOR BEFORE THE GAS METER WITH DUKE ENERGY TO INCREASE THE PRESSURE AFTER THE METER TO 2 PSI. COORDINATE POSSIBLE RELOCATION AND RESETTNG OF METER FOR BUILDING ENVELOPE INSTALLATION.
D. DEMOLISH ALL VENT PIPING AND VENTS THROUGH THE ROOF.
E. DEMOLISH ALL ABOVE GROUND SANITARY PIPING TO UNDERGROUND. CAP BELOW NEW WORK FINISHED FLOOR ELEVATION AND ABANDON. FILL ABANDONED PIPING WITH FLOWABLE FILL. NO DEAD LEGS OVER 2'-0" ALLOWED.
F. DEMOLISH ALL ROOF DRAINS. ABOVE GROUND STORM PIPING IN APP BAY AREA TO REMAIN. TEMPORARILY CAP PIPING BELOW ROOF IN THESE AREAS TO BE RECONNECTED TO NEW ROOF DRAINS IN NEW WORK PHASE. ABOVE GROUND STORM PIPING FROM THE UPPER ROOF BE DEMOLISHED TO UNDERGROUND. CAP UNDERGROUND STORM PIPING BELOW NEW WORK FINISHED FLOOR ELEVATION AND ABANDON. FILL ABANDONED PIPING WITH FLOWABLE FILL. NO DEAD LEGS OVER 2'-0" ALLOWED.

PLUMBING LEGEND

SYMBOL	DESCRIPTION
PLAN-VIEW LINE TYPES	
	WORK SHOWN FADED INDICATES EXISTING WORK TO REMAIN OR NEW WORK BY OTHERS AS APPLICABLE
	WORK SHOWN BOLD-DASHED INDICATES SELECTIVE DEMOLITION WORK
	WORK SHOWN BOLD-CONTINUOUS INDICATES NEW WORK
PIPING LINE TYPES	
	SANITARY WASTE PIPING
	OIL WASTE PIPING
	STORM PIPING (PRIMARY)
	DOMESTIC COLD WATER PIPING

5
P-101
ROOF PLUMBING DEMOLITION PLAN
1/8" = 1'-0"

KLH ENGINEERS
MECHANICAL/ELECTRICAL ENGINEERS
WWW.KLHENGERS.COM
1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8050
859-442-8058 FAX
LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK



your trusted advisor
consultants
engineers
architects
planners

REV	DATE	BY	REVISIONS
0	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT

SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241
PLUMBING DEMOLITION PLAN

SCALE:	1/8" = 1'-0"
HORZ:	
VERT:	
CONTRACT NO:	170636
SHEET	P-101

11/14/2019 10:19:13 AM

PLUMBING GENERAL NEW WORK NOTES

- WHERE ABANDONED UNDERGROUND PIPING INTERFERES WITH NEW WORK, DEMOLISH ABANDONED PIPING AND CAP AS NECESSARY.
- PROVIDE PIPE INSULATION JACKETING TO PROTECT ALL INSULATED PIPES IN APPARATUS BAY.

Plumbing Pipe Type Legend

Mark	Color	System Name	Pipe Material
C1.1	Blue	C1 - Domestic Cold Water	1 - Copper - Type L - ASTM B88
H1.1	Red	H1 - Domestic Hot Water	1 - Copper - Type L - ASTM B88
G1.7	Yellow	G1 - Natural Gas	7 - Black Steel - ASTM A53/A53M
HR1.1	Magenta	HR1 - Hot Water Return	1 - Copper - Type L - ASTM B88
A1.7	Brown	A1 - Compressed Air	7 - Black Steel - ASTM A53/A53M




MECHANICAL/ELECTRICAL ENGINEERS
WWW.KLHENGRS.COM

1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8050
859-442-8058 FAX

LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK



your trusted advisor
engineers
architects
consultants
planners



REV	DATE	BY	REVISIONS
0	11/20/2019	AMS	ISSUE FOR BIDDING AND PERMIT
1		DJT	
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			
13			
14			
15			
16			
17			
18			
19			
20			
21			
22			
23			
24			
25			
26			
27			
28			
29			
30			
31			
32			
33			
34			
35			
36			
37			
38			
39			
40			
41			
42			
43			
44			
45			
46			
47			
48			
49			
50			
51			
52			
53			
54			
55			
56			
57			
58			
59			
60			
61			
62			
63			
64			
65			
66			
67			
68			
69			
70			
71			
72			
73			
74			
75			
76			
77			
78			
79			
80			
81			
82			
83			
84			
85			
86			
87			
88			
89			
90			
91			
92			
93			
94			
95			
96			
97			
98			
99			
100			

SHARONVILLE FIRE STATION 87 RENOVATION

CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241

PLUMBING WATER & GAS - FIRST FLOOR

SCALE: As Indicated

HORIZ: VERT:


CONTRACT NO:

170636

SHEET


P-102

KLH JOB#: 21459.00



1 PLUMBING WATER & GAS - FIRST FLOOR

P-102 1/4" = 1'-0"



PLUMBING GENERAL NEW WORK NOTES

- A. WHERE ABANDONED UNDERGROUND PIPING INTERFERES WITH NEW WORK, DEMOLISH ABANDONED PIPING AND CAP AS NECESSARY.
B. PROVIDE PIPE INSULATION JACKETING TO PROTECT ALL INSULATED PIPES IN APPARATUS BAY.

Plumbing Pipe Type Legend

Mark	Color	System Name	Pipe Material
C1.1	Blue	C1 - Domestic Cold Water	1 - Copper - Type L - ASTM B88
H1.1	Red	H1 - Domestic Hot Water	1 - Copper - Type L - ASTM B88
G1.7	Yellow	G1 - Natural Gas	7 - Black Steel - ASTM A53/A53M
HR1.1	Magenta	HR1 - Hot Water Return	1 - Copper - Type L - ASTM B88
A1.7	Brown	A1 - Compressed Air	7 - Black Steel - ASTM A53/A53M
V6.6	Dark Brown	V6 - Intake Air Flue Vent	6 - PVC - Schedule 40 - ASTM D1785
V7.6	Light Brown	V7 - Exhaust Air Flue Vent	6 - PVC - Schedule 40 - ASTM D1785


KLH ENGINEERS
MECHANICAL/ELECTRICAL ENGINEERS
WWW.KLHENGERS.COM
1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8050
859-442-8058 FAX
LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK



REV	DATE	BY	REVISIONS
0	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT









SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241
PLUMBING WATER & GAS - SECOND FLOOR



SCALE: 1/4" = 1'-0"
HORIZ:
VERT:
CONTRACT NO: 170636
SHEET P-103



1 PLUMBING WATER & GAS - SECOND FLOOR
P-103 1/4" = 1'-0"


- A. WHERE ABANDONED UNDERGROUND PIPING INTERFERES WITH NEW WORK, DEMOLISH ABANDONED PIPING AND CAP AS NECESSARY.
- B. PROVIDE PIPE INSULATION JACKETING TO PROTECT ALL INSULATED PIPES IN APPARATUS BAY.

Plumbing Pipe Type Legend			
Mark	Color	System Name	Pipe Material
S3.6		S3 - Oil Waste	6 - PVC - Schedule 40 - ASTM D1785
S1.6		S1 - Sanitary	6 - PVC - Schedule 40 - ASTM D1785
V1.4		V1 - Vent	4 - Cast Iron - Hubless - ASTM A888
S1.4		S1 - Sanitary	4 - Cast Iron - Hubless - ASTM A888
S11.4		S11 - Storm	4 - Cast Iron - Hubless - ASTM A888
S11.6		S11 - Storm	6 - PVC - Schedule 40 - ASTM D1785
V3.6		V3 - Oil Vent	6 - PVC - Schedule 40 - ASTM D1785
V3.4		V3 - Oil Vent	4 - Cast Iron - Hubless - ASTM A888

[illegible]

SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241
PLUMBING SANITARY PLAN - FIRST FLOOR

SCALE:	1/4" = 1'-0"
HORIZ:	
VERT:	
CONTRACT NO:	
170636	
SHEET	
P-105	



PLUMBING GENERAL NEW WORK NOTES

- A. WHERE ABANDONED UNDERGROUND PIPING INTERFERES WITH NEW WORK, DEMOLISH ABANDONED PIPING AND CAP AS NECESSARY.
B. PROVIDE PIPE INSULATION JACKETING TO PROTECT ALL INSULATED PIPES IN APPARATUS BAY.

Plumbing Pipe Type Legend			
Mark	Color	System Name	Pipe Material
S1.6	Green	S1 - Sanitary	6 - PVC - Schedule 40 - ASTM D1785
S1.4	Green	S1 - Sanitary	4 - Cast Iron - Hubless - ASTM A888
V1.4	Yellow	V1 - Vent	4 - Cast Iron - Hubless - ASTM A888
S11.4	Pink	S11 - Storm	4 - Cast Iron - Hubless - ASTM A888
V3.4	Brown	V3 - Oil Vent	4 - Cast Iron - Hubless - ASTM A888
S12.4	Pink	S12 - Storm Overflow	4 - Cast Iron - Hubless - ASTM A888



MECHANICAL/ELECTRICAL ENGINEERS
WWW.KLHENGERS.COM

1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8050
859-442-8058 FAX


LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK



REV	DATE	REVISIONS	BY
0	11/20/2019	ISSUE FOR BIDDING AND PERMIT	CAM

SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241
PLUMBING SANITARY PLAN - SECOND FLOOR

SCALE:	1/4" = 1'-0"
HORZ:	
VERT:	
CONTRACT NO:	
170636	
SHEET	
P-106	



1
P-106
PLUMBING SANITARY PLAN - SECOND FLOOR
1/4" = 1'-0"



1538 ALEXANDRIA PIKE, SUITE 1
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8050
859-442-8058 FAX

engineers
architects
planners

MARK	DESCRIPTION	MANUFACTURER	MODEL	TRAP PRIMER	TRAP SIZE (in)	SAN SIZE (in)	VENT SIZE (in)
FD1	FLOOR DRAIN	ZURN	2415B	YES	SEE DRAWINGS	SEE DRAWINGS	SEE DRAWINGS
OD1	OVERFLOW DRAIN	ZURN	Z100-W2	NO	4	---	---
RD1	ROOF DRAIN	ZURN	Z100	NO	4	---	---
TD1	DRAIN TROUGH	I-H-M COMPANY	DRAIN TROUGH	NO	---	3	---

Equipment shall be braced and labeled by the equipment manufacturer to withstand the minimum scheduled available fault current value for listed equipment.

MARK	DESCRIPTION	MANUFACTURER	MODEL	WATTS	VOLTS	PHASE	FLA	AVAILABLE FAULT CURRENT	CW SIZE (IN)	SAN SIZE (IN)	VENT SIZE (IN)	TRAP SIZE (IN)	INT TRAP
EW1	DOMESTIC ELECTRIC WATER COOLER	ELKAY	LZ5TL8WSLK	370	120	1	5.0		1/2	1-1/2	1-1/2	---	NO

ABBREVIATIONS	CONTRACTOR TYPE	MOTOR CONTROL TYPE	CONTROL TYPE
DC LOCAL DISCONNECT	EC ELECTRICAL CONTRACTOR	CS COMBINATION STARTER	TC TIMECLOCK
MC MOTOR CONTROL (POWER)	EX EXISTING	MCC MOTOR CONTROL STARTER	CTP CONTROL POWER TRANSFORMER
SD FIRE SMOKE DETECTOR	MG FIRE PROTECTION CONTRACTOR	MS MAGNETIC STARTER OR CONTACT	BA BUILDING AUTOMATION SYSTEM
NC CONTROLS	GC GENERAL CONTRACTOR	MS MANUAL STARTER	LPT LOW VOLTAGE CONTROLS
TS TOGGLE SWITCH	HC HVAC CONTRACTOR	VFD VARIABLE FREQUENCY DRIVE	LINE LINE VOLTAGE CONTROLS
CB H.A.C.C. CIRCUIT BREAKER AT SOURCE PANELBOARD	MSR MECHANICAL STARTER	MSR MANUAL STARTER WITH CONTACT RELAY	RLN REVERSE ACTING LINE VOLTAGE THERMOSTAT
FUSE FUSE AT LOCAL DISCONNECT (VERIFY FILING RATING)	PC PLUMBING CONTRACTOR	OV OVERCURRENT PROTECTION	MAN MANUAL
FLA OPERATING FULL LOAD AMPS	OR OWNER OR OTHERS		LINE FIRE ALARM
MOA MINIMUM CIRCUIT AMPACITY			CA CARBON MONOXIDE SENSOR
CP CORD AND PLUG CONNECTION			INT INTEGRAL TO EQUIPMENT

EQUIPMENT MARK	DESCRIPTION	VOLTS (V)	PHASE	EMERGENCY	BHP (HP)	HP (HP)	HTG KW (KW)	WATTS (W)	FLA (A)	MCA (A)	OCF (A)	DC TYPE	DC FURN	DC INST	DC WIRE	MC TYPE	MC FURN	MC INST	MC WIRE	CN TYPE	CN FURN	CN INST	CN WIRE	AVAILABLE FAULT CURRENT (A)
AC1	AIR COMPRESSOR	208	1										EC	EC	EC	MG	MFR	MFR	MFR	INT	MFR	MFR	MFR	4141
EW1C1	DOMESTIC ELECTRIC WATER COOLER	120	1				370		5.0			CP	EC	EC	EC	MG	MFR	MFR	MFR	INT	MFR	MFR	MFR	
GD1	GARBAGE DISPOSAL	120	1						9.5			CP	EC	EC	EC	MG	MFR	MFR	MFR	MAN	EC	EC	EC	2697
GW1H	DOMESTIC GAS-FIRED TANK-TYPE WATER HEATER	120	1						5.0				EC	EC	EC	---	---	---	---	INT	MFR	MFR	MFR	5590
RCF1	HOT WATER RECIRCULATING PUMP	120	1			1/12	85		1.3				EC	EC	EC	MG	MFR	MFR	MFR	LINE	PC	PC	PC	5903

MARK	DESCRIPTION	LOCATION	MANUFACTURER	MODEL	VALVE/FAUCET MFG#	VALVE/FAUCET MODEL	CW SIZE (in)	HW SIZE (in)	SAN SIZE (in)	VENT SIZE (in)	TRAP SIZE (in)	INT TRAP	ACCESSORIES
BFP1	BACKFLOW PREVENTER	CLOSET 208	WATTS	LF009	---	---	2	---	---	---	---	---	---
BFP2	BACKFLOW PREVENTER	MECHANICAL 206	WATTS	LF007	---	---	2	---	---	---	---	---	---
BFP3	BACKFLOW PREVENTER	DECON 119	WATTS	LF007	---	---	1	---	---	---	---	---	---
BFP4	BACKFLOW PREVENTER	---	WATTS	---	---	---	---	1	---	---	---	---	---
DW1	DISHWASHER	KITCHEN 201	PROVIDED BY OTHERS	PROVIDED BY OTHERS	---	---	---	---	---	---	---	---	---
ESEW1	EMERGENCY SHOWER EYEWASH STATION	DECON 119	BRADLEY	S19314FW	---	---	---	1/2	---	---	---	---	DISHWASHER SUPPLY AND DRAIN TO TIE INTO ADJACENT KITCHEN SINK.
ET1	EXPANSION TANK	MECHANICAL 206	AMTROL	ST-12	---	---	3/4	---	---	---	---	---	PROVIDE WITH TM2V. BARRIER FREE, ADA COMPLIANT.
EW1	DOMESTIC ELECTRIC WATER COOLER	---	ELKAY	LZSLT8WSLK	---	---	1/2	---	1-1/2	1-1/2	---	NO	---
FILL LINE	FDC APPARATUS BAY FILL LINE	APPARATUS BAY	---	---	---	---	2	---	---	---	---	---	FDC CONNECTION PER FIRE CHIEF SPECIFICATION. PROVIDE FED FROM ASSE 1015 DOUBLE CHECK VALVE LINE IN MECHANICAL ROOM.
HB1	HOSE BIBB	SEE ARCH PLANS	WOODFORD	MODEL B24	---	---	3/4	---	---	---	---	---	---
HB2	HOSE BIBB	DECON	WOODFORD	MODEL 24	---	---	3/4	---	---	---	---	---	PROVIDE INLINE ASSE 1015 DOUBLE CHECK VALVE AND PRESSURE REGULATING VALVE SET PER EXTRACTOR REQUIREMENTS.
HB3	HOSE BIBB	APPARATUS BAY	WOODFORD	MODEL 24	---	---	3/4	---	---	---	---	---	PROVIDE NIDEL MODEL 37HD1 ON OUTLET.
HB4	HOSE BIBB	TOOLS/STORAGE	WOODFORD	MODEL 24	---	---	3/4	---	---	---	---	---	---
HR-CA	COMPRESSED AIR HOSE REEL	APPARATUS BAY 125	REELCRAFT	82100 OLP-HTH	---	---	---	---	---	---	---	---	---
HR-W	WATER HOSE REEL	APPARATUS BAY 125	REELCRAFT	83050 OLP-HTH	---	---	1/2	---	---	---	---	---	---
L1	LAVATORY	RESTROOMS	KOHLER	K-261	---	---	1/2	1/2	1-1/2	1-1/2	---	NO	ADA COMPLIANT. ASSE 1070. CARRIER.
M1	MOP SINK	DECON SHOWER	FAUCET ONLY	FAUCET ONLY	CHICAGO FAUCETS	---	3/4	3/4	---	---	---	---	INSTALL IN DECON SHOWER ON WALL. ARCHITECT TO CONFIRM LOCATION AND MOUNTING HEIGHT.
MS1	OIL/SAND SEPARATOR	EXTERIOR	E.C. BABBERT, INC.	O-4	---	---	---	---	4	3	---	---	---
SB1	SUPPLY BOX	KITCHEN 201	GUY GRAY	MIB1	---	---	1/2	---	---	---	---	---	PROVIDE ACCESSIBLE ASSE 1022 BACKFLOW PROTECTION.
SH1	SHOWER	RESTROOMS	SEE ARCH PLANS	SEE ARCH PLANS	BRADLEY	WS-1X-HB	1/2	1/2	2	1-1/2	2	NO	ADA COMPLIANT.
SK1	KITCHEN SINK	KITCHEN 201	ELKAY	LRAD312265	KOHLER	K-596	1/2	1/2	1-1/2	1-1/2	1-1/2	NO	ADA COMPLIANT. ASSE 1070. FINISH AS SELECTED BY ARCHITECT.
SK2	LAUNDRY SINK	LAUNDRY 112	FIAT	SF-1-F	ZURN	Z831B4-XL	1/2	1/2	1-1/2	1-1/2	1-1/2	NO	---
SK3	DECON SINK	DECON 119	ADVANCED TABCO	---	---	---	1/2	1/2	1-1/2	1-1/2	1-1/2	NO	24" X CUSTOM LENGTH (SEE PLANS) DOUBLE BOWL SINK. STAND ALONE, SLOPED DRAIN BOARD, T&S BRASS B-0502-SL FOOT PEDALS.
SV1	SOLENOID VALVE	---	ASCO	22 SERIES 820	---	---	---	---	---	---	---	---	---
TMV1	THERMOSTATIC MIXING VALVE	---	LEONARD	---	---	---	1/2	1/2	---	---	---	---	---
TMV2	THERMOSTATIC MIXING VALVE	DECON 119	BRADLEY	S19-2150	---	---	3/4	3/4	---	---	---	---	---
TP1	TRAP PRIMER	---	PPP	P2-500	---	---	1/2	---	---	---	---	---	---
WB1	WASHER BOX	---	GUY GRAY	T200	---	---	1/2	1/2	1-1/2	1-1/2	1-1/2	NO	PROVIDE WOOD STUD CONNECTION REQUIRED FOR SURFACE MOUNT TO BLOCK WALL.
WC1	FLUSH VALVE WATER CLOSET	RESTROOMS	KOHLER	K-4325	---	---	2	1	---	---	---	YES	ADA COMPLIANT. PROVIDE WITH SPECIFIED CARRIER.
WC2	WATER CLOSET CARRIER	RESTROOMS	WATTS	ISCA-151	---	---	---	---	4	2	---	---	---
WC2	WATER CLOSET CARRIER	RESTROOMS	WATTS	ISCA-151-D	---	---	---	---	4	2	---	---	---
WH1	WALL HYDRANT	EXTERIOR	WOODFORD	MODEL 65	---	---	3/4	---	---	---	---	---	---

Total Equivalent Length of Pipe (Feet):		185	(pressure Drop inches W.C.):	56	Delivery Pressure After Meter & PRV (inches W.C.):	28	Gas Type	NATURAL GAS
MARK	HVACTYPE	DESCRIPTION			GAS HTG IN (CFH)	MIN GAS PRESSURE (IN WC)	MAX GAS PRESSURE (IN WC)	
FCU-01	23 92 19.00.00	FANCOIL UNIT			40	4.5	13.6	
FCU-02	23 92 19.00.00	FANCOIL UNIT			38	4.5	13.6	
FCU-03	23 92 19.00.00	FANCOIL UNIT			80	4.5	13.6	
FCU-04	23 92 19.00.00	FANCOIL UNIT			40	4.5	13.6	
GAS GRILL		GAS GRILL			60			
GENERATOR		GENERATOR			1389	7	11	
GFUH-01	23 55 33.00.00	GAS FIRED UNIT HEATER			105	5	14	
GW1H	22 34 00.00.00	DOMESTIC GAS-FIRED TANK-TYPE WATER HEATER			199	3.5	14	
RANGE					203			
TOTAL GAS LOAD:					2142			

Equipment shall be braced and labeled by the equipment manufacturer to withstand the minimum scheduled available fault current value for listed equipment

MARK	DESCRIPTION	LOCATION	MANUFACTURER	MODEL	STORAGE (GAL)	FUEL	GAS HTG IN (MBH)	VOLTS	PHASE	FLA	AVAILABLE FAULT CURRENT	ACCESSORIES
AC1	AIR COMPRESSOR	MEZZ	CHAMPION	VRS-8	80	ELECTRIC	0	208	1		4141	16.5 CFM @ 175 PSIG
GD1	GARBAGE DISPOSAL	KITCHEN 201	INSINKERATOR	BADGER SXP		ELECTRIC	0	120	1	9.5	2697	3/4 HP

Equipment shall be braced and labeled by the equipment manufacturer to withstand the minimum scheduled available fault current value for listed equipment.

MARK	DESCRIPTION	LOCATION	MANUFACTURER	MODEL	VOLTS	PHASE	WEIGHT (lbs)	FLOW (gpm)	HEAD (ft)	WATTS	RPM	FLA (amps)	AVAILABLE FAULT CURRENT	ACCESSORIES
RCP1	HOT WATER RECIRCULATING PUMP	MECHANICAL 206	BELL & GOSSETT	ECOCIRC XL 20-35	120	1	20	1	12	85	0	1.3	5593	

Equipment shall be braced and labeled by the equipment manufacturer to withstand the minimum scheduled available fault current value for listed equipment

MARK	DESCRIPTION	LOCATION	MANUFACTURER	MODEL	EWI (DEG F)	LWT (DEG F)	GAS HTG IN (MDH)	STORAGE (GAL)	FUEL	MIN GAS PRESSURE (IN WC)	MAX GAS PRESSURE (IN WC)	VOLTS	PHASE	WEIGHT	FLA	ACCESS	AVAILABLE LATEST CURRENT
GW1H	DOMESTIC GAS-FIRED TANK-TYPE WATER HEATER	MECHANICAL 206	AO SMITH	BT4-128A	52	140	199	120	NATURAL GAS	3.5	14	120	1	523			5.0 6900

KLH JOB#: 21459.00

11/14/2019 10:20:14 AM

DOMESTIC WATER PRESSURE ANALYSIS REPORT			
Water Supply Fixture Units	95	WSFU	
Additional Non-WSFU Flow	0	gpm	
Total Peak demand	66	gpm	
PRESSURE LOSS ANALYSIS			
Flow test data was recorded for this project. Please contact engineer of record if further information is required.			
Design Flushing Type	Flush Valve		
Recorded Static Pressure	75	psi	
Recorded Residual Pressure	75	psi	
Pressure Losses in Piping	1	psi	
Pressure Losses in Equipment	17	psi	
Pressure Losses in Elevation	5	psi	
Static Pressure at Controlling Fixture	58	psi	
Residual Pressure at Controlling Fixture	52	psi	
Pressure at the controlling fixture meets the design requirements.			
PRESSURE AT CONTROLLING FIXTURE			
Design Controlling Fixture Pressure	35	psi	
Pump Required	NO		
Pressure Boost Required	---	psi	

Plumbing Pipe Type Legend			
Mark	Color	System Name	Pipe Material
C1.1	Blue	C1 - Domestic Cold Water	1 - Copper - Type L - ASTM B88
H1.1	Red	H1 - Domestic Hot Water	1 - Copper - Type L - ASTM B88
HR1.1	Magenta	HR1 - Hot Water Return	1 - Copper - Type L - ASTM B88
V6.6	Brown	V6 - Intake Air Flue Vent	6 - PVC - Schedule 40 - ASTM D1785
V7.6	Dark Brown	V7 - Exhaust Air Flue Vent	6 - PVC - Schedule 40 - ASTM D1785
G1	Yellow	G1 - Natural Gas	7 - Black Steel - ASTM A53/A53M




MECHANICAL/ELECTRICAL ENGINEERS
WWW.KLHENGERS.COM

1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8050
859-442-8058 FAX

LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK



your trusted advisor
engineers
architects
consultants
planners



REV	DATE	BY	REVISIONS
0	11/20/2019	AMS	ISSUE FOR BIDDING AND PERMIT
1	11/20/2019	DJT	
2			
3			
4			
5			
6			
7			
8			
9			
10			


SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241

PLUMBING - WATER & GAS ISOMETRIC

SCALE:
HORIZ:
VERT:


CONTRACT NO:
170636







SHEET
P-901



1
P-901
PLUMBING - DOMESTIC WATER ISOMETRIC

2
P-901
PLUMBING - GAS ISOMETRIC



Plumbing Pipe Type Legend			
Mark	Color	System Name	Pipe Material
S3.6		S3 - Oil Waste	6 - PVC - Schedule 40 - ASTM D1785
S1.6		S1 - Sanitary	6 - PVC - Schedule 40 - ASTM D1785
V1.4		V1 - Vent	4 - Cast Iron - Hubless - ASTM A888
S1.4		S1 - Sanitary	4 - Cast Iron - Hubless - ASTM A888
V3.6		V3 - Oil Vent	6 - PVC - Schedule 40 - ASTM D1785
V3.4		V3 - Oil Vent	4 - Cast Iron - Hubless - ASTM A888


[illegible]

SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241


PLUMBING - SANITARY & VENT ISOMETRIC

SCALE: _____
HORIZ: _____
VERT: _____
CONTRACT NO: _____
170636
SHEET
P-902

11/14/2019 10:16:51 AM



3 FIRST FLOOR ZONE MAP
M-001 1/8" = 1'-0"



2 SECOND FLOOR ZONE MAP
M-001 1/8" = 1'-0"


ESSENTIAL FACILITY SEISMIC REQUIREMENTS

SEISMIC BRACING FOR ALL NON-STRUCTURAL COMPONENTS INCLUDING BUT NOT LIMITED TO EQUIPMENT, PIPING, CONDUIT AND DUCTWORK IS REQUIRED FOR THIS PROJECT. THE DESIGN AND INSTALLATION OF THE SEISMIC RESTRAINT DEVICES IS DELEGATED TO THE CONTRACTOR. REFER TO SEISMIC CONTROLS SPECIFICATION FOR DELEGATED DESIGN SUBMITTAL REQUIREMENTS.

KLH ENGINEERS
MECHANICAL/ELECTRICAL ENGINEERS
WWW.KLHENGRS.COM
1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8050
859-442-8058 FAX
LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK



your trusted advisor
engineers
architects
consultants
planners



MECHANICAL LEGEND

SYMBOL	DESCRIPTION
PLAN-VIEW LINE TYPES	
WORK SHOWN BOLD-CONTINUOUS INDICATES NEW WORK	
PIPING LINE TYPES	
RL	REFRIGERANT LIQUID
RS	REFRIGERANT SUCTION
CD	CONDENSATE DRAIN

MECHANICAL MISCELLANEOUS

PS	ANSUL PULL STATION
ECR	ENVIRONMENTAL CONTROL PANEL
UC 0'-1"	1" DOOR UNDERCUT

MECHANICAL STATS & SENSORS

T	LOW VOLTAGE THERMOSTAT
L	LINE VOLTAGE THERMOSTAT
CONC	COMBINATION CARBON MONOXIDE AND NITROGEN DIOXIDE SENSOR

MECHANICAL DUCTWORK ACCESSORIES

Round Elbow with Turning Vanes	DUCT WITH MANUAL VOLUME DAMPER
Elbow with Turning Vanes	MOTOR OPERATED DAMPER - LINE VOLTAGE
Motor Operated Damper - Low Voltage	DUCT MOUNTED SMOKE DETECTOR (HARD WIRE INTERLOCK TO FAN MOTOR BY E.C.) FURNISHED BY E.C., INSTALLED BY M.C.
FD 1.5 HR	FIRE DAMPER - 1.5 HR

MECHANICAL AIR DEVICES

SR	SUPPLY REGISTER
RR	RETURN REGISTER
ER	EXHAUST REGISTER
SG	SUPPLY GRILLE
RG	RETURN GRILLE
CD	CEILING DIFFUSER
CD-10"Ø	2'x2' SQUARE CEILING DIFFUSER WITH 10" NECK

MECHANICAL DUCTWORK

Supply Duct with Elbow Turned Up	Supply Duct with Elbow Turned Down
Return Duct with Elbow Turned Up	Return Duct with Elbow Turned Down
Exhaust Duct with Elbow Turned Up	Exhaust Duct with Elbow Turned Down
24x12 SA	24x12 RA
24x12 EA	24x12 OA
1" LINED DUCTWORK	FLEXIBLE DUCTWORK CONNECTION
BRANCH TAKEOFF	REDUCER, CONCENTRIC
REDUCER, NONCONCENTRIC	DUCT FLEX CONNECTOR

STANDARD HVAC ABBREVIATIONS

AAV	AUTOMATIC AIR VENT	I/O	INPUT/OUTPUT
ACCESS	ACCESSORIES	IAQ	INDOOR AIR QUALITY
AD	ACCESS DOOR	IN HG	INCHES OF MERCURY
AFF	ABOVE FINISHED FLOOR	IN WC	INCH WATER COLUMN
AMP	AMPERE	IN WG	INCH WATER GAUGE
AP	ACCESS PANEL	IPLY	INTERGRADED PART LOAD VALUE
APD	AIR PRESSURE DROP	INST	INSTALLED
ARI	AIR CONDITIONING AND REFRIGERATION INSTITUTE	KW	KILOWATT
ASME	AMERICAN SOCIETY OF MECHANICAL ENGINEERS	KWH	KILOWATT HOUR
BAS	BUILDING AUTOMATION SYSTEM	LAT	LEAVING AIR TEMPERATURE
BHP	BACKDRAFT DAMPER	LB/HR	POUNDS PER HOUR
BTU	BRITISH THERMAL UNIT	LF	LINEAR FOOT (FEET)
BTUH	BRITISH THERMAL UNIT PER HOUR	LPR	LOW PRESSURE RETURN
CFH	CUBIC FEET PER HOUR	LPS	LOW PRESSURE STEAM
CFM	CUBIC FEET PER MINUTE	LWT	LEAVING WATER TEMPERATURE
CHWR	CHILLED WATER RETURN	MAX	MAXIMUM
CHWS	CHILLED WATER SUPPLY	MBH	1000 BTUH
CI	CAST IRON	MCA	MINIMUM BRANCH CIRCUIT AMPACITY
CLG	COOLING	MERV	MINIMUM EFFICIENCY REPORTING VALUE
CO	CARBON MONOXIDE	MIN	MINIMUM
CO2	CARBON DIOXIDE	MOD	MOTOR OPERATED DAMPER
COP	COEFFICIENT OF PERFORMANCE	MPR	MEDIUM PRESSURE RETURN
CV	CONSTANT VOLUME	MPS	(STEAM CONDENSATE) MEDIUM PRESSURE STEAM
CWR	CONDENSER WATER RETURN	MRI	MAGNETIC RESONANCE IMAGING
CWS	CONDENSER WATER SUPPLY	MVD	MANUAL VOLUME DAMPER
DB	DECELS	NA	NOT APPLICABLE
DB	DRY-BULB TEMPERATURE	NC	NOISE CRITERIA
DISC	DISCONNECT	NC	NORMALLY CLOSED
DDC	DIRECT DIGITAL CONTROLS	NO	NORMALLY OPEN
DEG	DEGREE DELTA(CHANGE IN TEMPERATURE)	NTS	NOT TO SCALE
DIA	DIAMETER	OA	OUTSIDE AIR
DIW	DEIONIZED WATER	OCP	OVER CURRENT PROTECTION
DP	DEW POINT TEMPERATURE	PD	PRESSURE DROP
DX	DIRECT EXPANSION	PPM	PARTS PER MILLION
EA	EXHAUST AIR	PRS	PRESSURE REGULATING (VALVE) STATION
EAT	ENTERING AIR TEMPERATURE	PRV	PRESSURE REGULATING VALVE
EER	ENERGY EFFICIENCY RATIO	PSI	POUNDS PER SQUARE INCH
EG	EXHAUST GRILLE	PSIA	POUNDS PER SQUARE INCH - ABSOLUTE
EMERG	EMERGENCY POWER	PSIG	POUNDS PER SQUARE INCH - GAGE
ESP	EXTERNAL STATIC PRESSURE	RA	RETURN AIR
EW	ENTERING WATER TEMPERATURE	RAT	RETURN AIR TEMPERATURE
EX	EXISTING	RH	RELATIVE HUMIDITY
F	FAHRENHEIT	RL	REFRIGERANT LIQUID LINE
F&T	FLOAT AND THERMOSTATIC	RLA	RUN LOAD AMPERE
FA	FREE AREA	RO	REVERSE OSMOSIS
FD	FIRE DAMPER	RPM	REVOLUTIONS PER MINUTE
FLA	FULL LOAD AMPERES	RS	REFRIGERANT SUCTION
FPM	FEET PER MINUTE	SA	SUPPLY AIR
FPS	FEET PER SECOND	SAT	SUPPLY AIR TEMPERATURE
FT	FEET	SC	SHADING COEFFICIENT
FURN	FURNISHED	SCD	SMOKE CONTROL DAMPER
GA	GAUGE	SD	SMOKE DETECTOR
GAL	GALLONS	SENS	SENSIBLE HEAT
GPM	GALLONS PER MINUTE	SP	STATIC PRESSURE
HD	HEAD	TAB	TESTING, ADJUSTING, BALANCE
HOA	HAND/OFF/AUTOMATIC	TDH	TOTAL DYNAMIC HEAD
HP	HORSEPOWER	TDS	TOTAL DISSOLVED SOLIDS
HPR	HIGH PRESSURE RETURN (STEAM CONDENSATE)	TSP	TOTAL STATIC PRESSURE
HSTAT	HUMIDISTAT	TSTAT	THERMOSTAT
HTG	HEATING	UL	UNDERWRITERS LABORATORY
HWR	HEATING HOT WATER RETURN	VAV	VARIABLE AIR VOLUME
HWS	HEATING HOT WATER SUPPLY	VFD	VARIABLE FREQUENCY DRIVE
HZ	HERTZ	WB	WET-BULB (TEMPERATURE)
		WG	WATER GAGE
		WPD	WATER SIDE PRESSURE DROP
		WIRE	WIRED

NEW WORK GENERAL NOTES


- PROVIDE ALL LABOR, MATERIAL, AND EQUIPMENT NECESSARY TO COMPLETELY FURNISH, INSTALL, AND PLACE INTO OPERATION. ALL SYSTEMS SHOWN ON THE DRAWINGS AND DELINEATED IN THE SPECIFICATIONS IN ACCORDANCE WITH ALL STATE AND LOCAL CODES AND ORDINANCES. REPORT ANY KNOWN DISCREPANCIES TO THE ARCHITECT/ENGINEER PRIOR TO INSTALLATION.
- REFER TO ARCHITECTURAL REFLECTED CEILING PLANS FOR EXACT LOCATIONS OF CEILING DIFFUSERS, REGISTERS AND GRILLES.
- DO NOT SCALE DRAWINGS; REFER TO ARCHITECTURAL DRAWINGS FOR DIMENSIONED LOCATIONS OF WALLS, DOORS, WINDOWS, AND CABINETS.
- COORDINATE WORK AND SPACE REQUIREMENTS IN CEILING SPACES WITH OTHER TRADES PRIOR TO INSTALLATION.
- COORDINATE LOCATIONS AND ORIENTATION OF ROOF MOUNTED EQUIPMENT WITH ARCHITECTURAL AND STRUCTURAL DRAWINGS. COORDINATE WALL LOUVERS WITH ARCHITECTURAL ELEVATIONS AND DETAILS.
- PROVIDE VOLUME DAMPERS AT ALL SUPPLY, RETURN, AND EXHAUST DUCT BRANCH TAKE-OFFS.
- PROVIDE TURNING VANES IN ALL 90 DEGREE MITERED ELBOWS. OMIT TURNING VANES IN ACOUSTIC LINED RETURN DUCT ELBOWS.
- PROVIDE FLEXIBLE DUCT ON INLET TO EACH CEILING DIFFUSER. CUT FLEXIBLE DUCTS TO LENGTH NEEDED AND INSTALL WITHOUT KINKS OR SHARP BENDS (BENDS WITH CENTERLINE RADIUS LESS THAN DUCT DIAMETER). SUPPORT FLEXIBLE DUCTS WITH MINIMUM 1" WIDE METAL STRAPS OR SADDLES.
- SIZES OF ACOUSTIC LINED DUCTS ARE NET INSIDE DIMENSION. INCREASE SHEET METAL SIZE ACCORDINGLY.
- RUNOUTS TO CEILING DIFFUSERS ARE THE SAME SIZE AS THE DIFFUSER NECK UNLESS NOTED OTHERWISE.
- INSTALL ALL EQUIPMENT WITH CODE REQUIRED AND MANUFACTURER RECOMMENDED MINIMUM CLEARANCES FOR SERVICE, ACCESS, AND FIRE PROTECTION.
- MAINTAIN A MINIMUM OF 10 FEET BETWEEN ALL OUTSIDE AIR INTAKES AND ALL EXHAUST, VENT, AND FLUE OUTLETS.
- ALL MATERIALS EXPOSED WITHIN PLenums SHALL BE NON-COMBUSTIBLE OR SHALL HAVE A FLAME SPREAD INDEX OF NOT MORE THAN 25 AND A SMOKE-DEVELOPED INDEX OF NOT MORE THAN 50 WHEN TESTED IN ACCORDANCE WITH ASTM E 84.
- ALL FLOOR PENETRATIONS SHALL BE COORDINATED WITH THE CONCRETE RIBS IN THE FLOOR STRUCTURE.
- MECHANICAL CONTROLS CONTRACTOR TO PROVIDE A LINK TO THE CONTROLS SHOP DRAWINGS INCLUDING SEQUENCE OF OPERATIONS ON THE HOME PAGE OF THE FRONT-END GRAPHICS.

SHARONVILLE FIRE STATION 87 RENOVATION

CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241

MECHANICAL COVER SHEET

SCALE:	1/8" = 1'-0"
HORIZ:	
VERT:	
CONTRACT NO:	170636
SHEET	M-001





11/14/2019 10:17:20 AM

KLH

ENGINEERS

MECHANICAL/ELECTRICAL ENGINEERS

WWW.KLHENGERS.COM

1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8050
859-442-8058 FAX

LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK

STATE OF OHIO

KRIS SCHNITGEN

77432

REGISTERED PROFESSIONAL ENGINEER

11/04/19

your trusted advisor

engineers
architects
planners

consultants

your trusted advisor

engineers
architects
planners

consultants

REV	DATE	BY	REVISIONS
0	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
1	11/20/2019	DS	
2	11/20/2019	RAL	
3	11/20/2019	F.B.	
4	11/20/2019	PG	
5	11/20/2019	NO	

SHARONVILLE FIRE STATION 87 RENOVATION

CITY OF SHARONVILLE

11210 READING RD, SHARONVILLE, OH 45241

MECHANICAL DUCTWORK - SECOND FLOOR

SCALE: 1/4" = 1'-0"

HORZ:

VERT:

CONTRACT NO: 170636

SHEET M-103

KLH JOB#: 21459.00

1
M-103
MECHANICAL DUCTWORK - SECOND FLOOR
1/4" = 1'-0"

KLH

ENGINEERS

MECHANICAL/ELECTRICAL ENGINEERS

WWW.KLHENGERS.COM

1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8050
859-442-8058 FAX

LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK

STATE OF OHIO

KRIS SCHNITGEN

77432

REGISTERED PROFESSIONAL ENGINEER

11/04/19

your trusted advisor

consultants

engineers
architects
planners

KLH

ENGINEERS

1

M-104

MECHANICAL DUCTWORK PLAN - ROOF

1/4" = 1'-0"

N

DATE:	11/20/2019	REV:	0	REVISIONS	DATE	BY
DRAWN BY:	DS	ISSUE FOR BIDDING AND PERMIT	11/20/2019	CAM		
CHECKED BY:	RAL					
APPROVED BY:						
F.B. NO.						
P.G.						
SHARONVILLE FIRE STATION 87 RENOVATION						
CITY OF SHARONVILLE						
11210 READING RD, SHARONVILLE, OH 45241						
MECHANICAL DUCTWORK PLAN - ROOF						
SCALE: 1/4" = 1'-0"						
HORIZ:						
VERT:						
CONTRACT NO:						
170636						
SHEET						
M-104						

11/14/2019 10:17:27 AM

KLH JOB#: 21459.00

KLH

ENGINEERS

MECHANICAL/ELECTRICAL ENGINEERS

WWW.KLHENGERS.COM

1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8060
859-442-8058 FAX

LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK



your trusted advisor

engineers
architects
planners

consultants

REV	REVISIONS	DATE	BY
0	ISSUE FOR BIDDING AND PERMIT	11/20/2019	CAM


SHARONVILLE FIRE STATION 87 RENOVATION

CITY OF SHARONVILLE

11210 READING RD, SHARONVILLE, OH 45241

MECHANICAL PIPING - FIRST FLOOR

SCALE:	1/4" = 1'-0"
HORIZ:	
VERT:	
CONTRACT NO:	170636
SHEET	M-105



1

MECHANICAL PIPING - FIRST FLOOR

1/4" = 1'-0"

N

11/14/2019 10:17:34 AM

KLH

ENGINEERS

MECHANICAL/ELECTRICAL ENGINEERS

WWW.KLHENGERS.COM

1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8060
859-442-8058 FAX

LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK



your trusted advisor

consultants

engineers
architects
planners

REV	REVISIONS	DATE	BY
0	ISSUE FOR BIDDING AND PERMIT	11/20/2019	CAM


SHARONVILLE FIRE STATION 87 RENOVATION

CITY OF SHARONVILLE

11210 READING RD, SHARONVILLE, OH 45241

MECHANICAL PIPING - SECOND FLOOR

SCALE:	1/4" = 1'-0"
HORZ:	
VERT:	
CONTRACT NO:	
	170636
SHEET	
	M-106




1

MECHANICAL PIPING - SECOND FLOOR

M-106 1/4" = 1'-0"

11/14/2019 10:17:47 AM




KEYED NOTES:

1. OPENING IN DUCT FOR HEATER, VERIFY OPENING SIZE PER MFG'R REQUIREMENTS.
2. ELECTRIC HEATING ELEMENT W/ AIR FLOW PROVING SWITCH
3. TERMINAL COMPARTMENT
4. MINIMUM 48" FROM ANY DUCT FITTING OR FAN OUTLET

238216.00-01 - PACKAGED ELECTRIC DUCT HEATER

SCALE: NONE




KEYED NOTES:

1. TERMINATE THROUGH ROOF OR WALL W/CAP AND 2" ELASTOMERIC INSULATION WITH 10' CLEAR FROM INTAKES OR BUILDING OPENINGS.
2. BACKDRAFT DAMPER
3. ALTERNATE ROUTE THROUGH SIDE WALL
4. 4" Ø INSULATED SHEETMETAL SMOOTH INTERIOR DUCT WITH JOINTS IN DIRECTION OF AIRFLOW & NO OBSTRUCTION TO AIRFLOW
5. MAXIMUM 25'-0" EQUIVALENT FEET FROM DRYER TO OUTLET TERMINAL
6. METALLIC FLEXIBLE DUCT CONNECTOR MAX. 6'-0" (NOT ALLOWED IN CONCEALED LOCATIONS)
7. PROVIDE CLEANOUT IN EACH VERTICAL RISER
8. SECURE ALONG WALL W/ STRAPS
9. PROVIDE SHEETMETAL RAIN CAP 24" MIN. ABOVE ROOF.
10. CONDUIT HOLE
11. RUBBER GASKET APPLIED TO TOP OF CURB

233500.00-01 - DRYER EXHAUST

SCALE: NONE



KEYED NOTES:


1. PROPELLER ROOF FAN
2. WOOD NAILER
3. ANCHOR ALL FOUR SIDES WITH SCREWS 12" O.C.
4. PREFABRICATED INSULATED CURB
5. MOTOR OPER. DAMPER INTERFACED WITH EXHAUST FAN WIRING/STARTER
6. CONDUIT HOLE
7. ANCHOR TO ROOF DECK AS REQUIRED
8. RUBBER GASKET APPLIED TO TOP OF CURB
9. ROOFING UP UNDER FLASHING, PROVIDE CURB TYPE AND FLASHING PER ROOFING MANUFACTURER'S REQUIREMENTS
10. BIRD SCREEN
11. CENTER TRANSITION TO DUCTWORK FROM DAMPER OR CURB, PROVIDE 3X DIAMETER STRAIGHT RUN MINIMUM.

GENERAL NOTES:

- A. DELETE CANT FOR SINGLE MEMBRANE ROOFS.
- B. TOP OF CURB MUST BE LEVEL. FABRICATE PITCH IN CURB IF NECESSARY
- C. CONTRACTOR HAS THE OPTION TO INCREASE THE HEIGHT OF THE CURB OR ADD BLOCKING TO THE CURB. THE ADDITIONAL HEIGHT REQUIRED SHALL EQUAL THE ROOF ASSEMBLY THICKNESS. THE CURB INTAKE OPENING SHALL BE AT A MINIMUM 12" ABOVE FINISHED ROOF.
- D. LOCATE A MINIMUM OF 10'-0" FROM EDGE OF ROOF, INTAKES, AND ROOF HATCH.

MECHANICAL - DETAILS

SCALE: NONE



KEYED NOTES:

1. DX COOLING COIL
2. CONDITIONED OUTLET AIR
3. AIR FILTER
4. FAN MOTOR
5. 3/4" CONDENSATE DRAIN WITH TRAP
6. REFRIGERANT LINES (NOT TO BE EXPOSED TO OCCUPANT), MAXIMUM PIPING LENGTH EQUAL TO 100FT. MAXIMUM ELEVATION DIFFERENCE EQUAL TO 50 FT. INSULATE SUCTION AND LIQUID LINES.
7. OUTLET LOUVER
8. INLET AIR


SIDE VIEW

FRONT VIEW

3'-0" MINIMUM CLEARANCE FOR SERVICE AND AIR FLOW.

MECHANICAL - DETAILS

SCALE: NONE



KEYED NOTES:


1. ANCHOR UNIT TO CURB
2. PRESSURE TREATED WOOD NAILER
3. VIBRATION ISOLATORS
4. ROOF DECK
5. PREFABRICATED EQUIPMENT SUPPORT
6. SINGLE MEMBRANE ROOFING, FLASH PER MFG'R RECOMMENDATIONS. FLASH UP AND OVER WOOD NAILER.
7. PREFABRICATED DOG HOUSE
8. SEAL AND FLASH OPENING

GENERAL NOTES:

- A. ON PROJECTS WITH BUILT-UP ROOFS, ADD CANT ON EQUIPMENT SUPPORTS AND PREFABRICATE PIPING CHASE
- B. PLACE EQUIPMENT ACROSS BAR JOIST OR ADD ADDITIONAL STRUCTURAL STEEL AS NECESSARY TO CARRY EQUIPMENT WEIGHT
- C. LOCATE A MINIMUM OF 10'-0" FROM EDGE OF ROOF AND ROOF HATCH.

MECHANICAL - DETAILS

SCALE: NONE




KEYED NOTES:

1. VENT CAP
2. CURB AND FLASHING
3. ROOF THIMBLE
4. CLEAN OUT
5. DOUBLE WALL VENT PIPE
6. GALVANIZED HANGER RODS
7. UNIT HEATER

MECHANICAL - DETAILS

SCALE: NONE




KEYED NOTES:

1. CANVAS FLEXIBLE CONNECTION
2. RETURN PLENUM, PROVIDE 1/2" ACOUSTIC LINING
3. 4" CONCRETE PAD
4. RETURN PLENUM UNDER UNIT FOR SUPPLY AIR FLOW GREATER THAN 1800 CFM. PROVIDE SUPPORT ANGLES IN CORNERS OF UNIT
5. COPPER CONDENSATE DRAIN, PIPE TO FLOOR DRAIN
6. UNION
7. GAS COCK (PLUG VALVES)
8. REFRIGERANT LINES, PROVIDE 3/4" ARAMFLEX ON SUCTION LINE
9. VENT-PER MFG'R REQUIREMENTS
10. COMBUSTION INTAKE (IF REQ'D)
11. CONDENSING FURNACE CONDENSATE DRAIN, CPVC PIPING, PIPE TO FLOOR DRAIN
12. GAS FIRED FURNACE
13. EVAPORATOR COIL & INSULATED PLENUM
14. GAS PIPING, BLACK STEEL
15. CAP
16. FILTER AND RACK
17. FUNNEL DRAIN
18. HIGH WATER ALARM IN CONDENSATE DRAIN PAN. WIRE TO BREAK 24 VOLT CONTROL POWER IN THE CASE OF A HIGH WATER EVENT.

MECHANICAL - DETAILS

SCALE: NONE



KEYED NOTES:

1. EXTERIOR WALL MOUNTED LOUVER
2. MOTOR OPER. DAMPER
3. CAULKING
4. ANCHOR TO WALL AT 12" O.C.
5. PROVIDE INSULATED SHEET METAL PLENUM, FULL SIZE OF LOUVER, (MIN 12" DEEP)
6. TRANSITION INSULATED DUCT CONNECTION WITH ANGLED FITTING TO PLENUM FOR UNIFORM AIR FLOW
7. 3/4" PIPING TO FLOOR DRAIN


GENERAL NOTES:

- A. REFER TO ARCHITECTURAL DRAWINGS FOR SIZES AND LOCATIONS.

MECHANICAL - DETAILS


SCALE: NONE

GENERAL NOTES:



MECHANICAL - DETAILS

SCALE: NONE




KEYED NOTES:

1. 20 GAUGE DOUBLE SHEET METAL AIR FOIL FULL DEPTH OF MAIN DUCT UP TO 12" WIDE BRANCHES 18 GAUGE ON WIDER BRANCHES
2. MAIN DUCT
3. GALVANIZED 3/16" ROD
4. VENTLOCK NO. 600-3 DAMPER BLADE, BRACKET & LOCKING BALL JOINT WITH 1/40" GALVANIZED OPERATOR PAD
5. GALVANIZED MAIN DUCT
6. DOUBLE THICKNESS TURNING VANES (TYPICAL)
7. 3" RADIUS MINIMUM

MECHANICAL - DETAILS

SCALE: NONE




GENERAL NOTES:

- A. LOCATE TRAPS SO AS TO BE ACCESSIBLE FOR CLEANING.
- B. CONDENSATE PIPING SHALL GRADUALLY SLOPE DOWN FROM DRAIN TRAP.
- C. CONFIRM TRAP REQUIREMENTS WITH EQUIPMENT MANUFACTURER.
- D. REFER TO SPECIFICATIONS FOR MATERIAL AND INSULATION REQUIREMENTS
- E. PROVIDE UNION UPSTREAM AND DOWNSTREAM OF TRAP.

MECHANICAL - DETAILS

SCALE: NONE



KEYED NOTES:

1. CONNECT TO STRUCTURE (TYPICAL).
2. GALVANIZED THREADED HANGER RODS (TYPICAL), SEE SPECIFICATIONS.
3. UNISTRUT,
4. PLATED NUT & WASHER (TYPICAL),
5. CONTINUOUS INSULATION AS SPECIFIED, (TYPICAL).
6. CHANNEL MOUNTED CLAMPING SYSTEM (TYPICAL).
7. SPACER SIZED TO PREVENT COMPRESSION OF INSULATION.
8. PLATED DOUBLE NUT AND WASHER.

MECHANICAL - DETAILS

SCALE: NONE

KLH ENGINEERS
MECHANICAL/ELECTRICAL ENGINEERS
WWW.KLHENGRS.COM
1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8050
859-442-8058 FAX
LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK


STATE OF OHIO
KRIS SCHNITGEN
77432
REGISTERED PROFESSIONAL ENGINEER
11/04/19

your trusted advisor
engineers
architects
consultants
planners


DATE:	11/20/2019	BY:	CLM
DRAWN BY:	DS	DATE:	11/20/2019
CHECKED BY:	RAL	REVISIONS	
APPROVED BY:		REV	0
F.B.		ISSUE FOR BIDDING AND PERMIT	
P.G.			

SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241
MECHANICAL - DETAILS


SCALE:	1/8" = 1'-0"
HORIZ:	
VERT:	
CONTRACT NO:	170636
SHEET	M-501




1 APPARATUS BAY EXHAUST ISOMETRIC




2 MECHANICAL ROOM PIPING ISOMETRIC



3 MECHANICAL ROOM DUCTWORK ISOMETRIC 1



4 MECHANICAL ROOM DUCTWORK ISOMETRIC 2



5 SLEEPING QUARTERS DUCTWORK ISOMETRIC

Sequence of Operations

Split System Furnace ACU (Gas-Fired/DX, with O.A.)

- Startup
 - The unit shall operate on an occupied/unoccupied cycle.
- Supply Fan
 - The supply fan speed shall be constant and balanced to the required CFM.
 - The supply fan shall run continuously, be two stage and modulate up and down based on a call for heating or cooling.
- Space Temperature Control
 - Provide local wall mounted room temperature thermostat with digital display of room temperature and setpoint (+/- deg. F. adjustable) and override feature.
- Minimum Outside Air Control
 - During occupied mode the minimum outside air damper shall be open. Provide motorized outdoor air damper.
 - During occupied mode, the minimum outside air damper shall be open to the scheduled minimum outdoor air flow and modulate proportionally with the supply fan speed to maintain the scheduled minimum outside airflow. When the supply fan speed is set to high, outside air damper shall be partially closed allowing minimum outside air flow as scheduled. As supply fan speed is set to low, damper shall fully open allowing minimum outside air flow as scheduled. Provide motor operated dampers.
- Economizer Control (FCU-03 only)
 - Provide dual enthalpy economizer control. Economizer control shall be enabled whenever the outside air enthalpy is lower than the return air enthalpy. Enthalpy shall be calculated from sensors which are tied to the same controller for accuracy. During economizer mode, the outside air damper shall modulate to 100% open. The economizer damper shall modulate open on a call for cooling and modulate closed on a call for heating. The return damper shall modulate inversely with the economizer damper.
- Cooling Control
 - Cooling shall be controlled to maintain space temperature setpoint. On a call for cooling the heating shall be off. On a further call for cooling the mechanical cooling shall be staged on. Provide Low Ambient Controls on condensing unit for operation down to -20 degrees F.
 - (FCU-03 Only) Heating shall be controlled to maintain space temperature setpoint. On a call for heating, the mechanical cooling shall be off. On a further call for heating, the economizer mode shall be disabled. On a further call for heating, the supply fan shall be set to low speed. On a further call for heating, the natural gas heat shall stage on. On a further call for heating, the supply fan shall be set to high speed.
- Heating Control
 - Heating shall be controlled to maintain space temperature setpoint. On a call for heating, the mechanical cooling shall be off. On a further call for heating the gas heating shall be staged on.
 - (FCU-03 only) Heating shall be controlled to maintain space temperature setpoint. On a call for heating, the mechanical cooling shall be off. On a further call for heating, the economizer mode shall be disabled. On a further call for heating, the supply fan shall be set to low speed. On a further call for heating, the natural gas heat shall stage on. On a further call for heating, the supply fan shall be set to high speed.
- Smoke Detector
 - When the smoke detector is alarmed, the air handler shall fail safe with manual reset. Electrical contractor shall furnish, HVAC Contractor shall mount & Electrical contractor shall wire a UL listed photoelectric smoke detector per local code authority having jurisdiction.
- Unoccupied Mode
 - During the unoccupied mode of operation, the ACU shall go into night setback mode.
- Night Setback/Shutdown
 - At night setback/shutdown the ACU shall go to fail safe position. Fail safe position is defined by the following: The supply fan is off, the outdoor air intake damper is closed, the heating is off and the mechanical cooling is off. The supply fan shall cycle in conjunction with either the heating or cooling system to maintain a minimum/maximum space temperature depending on the season.

Split System ACU (Electric Heat/DX, with O.A.)

- Startup
 - The unit shall operate on an occupied/unoccupied cycle.
- Supply Fan
 - The supply fan speed shall be constant and balanced to the required CFM.
- Space Temperature Control
 - Provide local wall mounted room temperature thermostat with digital display of room temperature and setpoint (+/- deg. F. adjustable) and override feature.
- Minimum Outside Air Control
 - During occupied mode the minimum outside air damper shall be open. Provide motorized outdoor air damper.
- Cooling Control
 - Cooling shall be controlled to maintain space temperature setpoint. On a call for cooling the SCR electric heater shall be off. On a further call for cooling the mechanical cooling shall be staged on. Provide Low Ambient Controls on condensing unit for operation down to -20 degrees F.
- Heating Control
 - Heating shall be controlled to maintain space temperature setpoint. On a call for heating, the mechanical cooling shall be off. On a further call for heating the SCR electric heating shall be modulate.
- Unoccupied Mode
 - During the unoccupied mode of operation, the ACU shall go into night setback mode.
- Night Setback/Shutdown
 - At night setback/shutdown the ACU shall go to fail safe position. Fail safe position is defined by the following: The supply fan is off, the outdoor air intake damper is closed, the heating is off and the mechanical cooling is off. The supply fan shall cycle in conjunction with either the heating or cooling system to maintain a minimum/maximum space temperature depending on the season.

DUCTLESS SPLIT SYSTEM ACU - DATA CLOSET

- The unit shall operate to maintain space temperature set point. The fan shall cycle in sequence with the heating/cooling coils to maintain space temperature setpoint. On a call for cooling, the evaporator fan shall start and run continuously and mechanical cooling shall stage on. All a call for heating, the evaporator fan and mechanical cooling shall shut down.
- Provide Low Ambient Controls on condensing unit for operation down to -20 degrees F.

CONDENSING UNITS

- All safeties interlocks associated with the condensing unit shall be hard wired. Software interlocks are acceptable as secondary additional safeties.
- Unit shall have self-contained controls by unit manufacturer. Provide Low Ambient Controls on condensing unit for operation down to -20 degrees F.
- On a call for cooling, with all safety devices satisfied, the first stage compressor contactor and condenser fan contactor energize causing the compressor and condenser fan motor to operate (the indoor fan contactor shall be wired to start at the same time as the compressor). A liquid line solenoid valve will open when the first stage compressor starts.
- On a further call for cooling, the second stage compressor contactor and condenser fan contactor energize causing the second stage compressor and condenser fan motor to operate. A liquid line solenoid valve will open when the second stage compressor starts.
- As cooling demand decreases, the second stage compressor contactor and condenser fan contactor de-energize causing the second stage compressor and condenser fan motor to shut down. A corresponding liquid line solenoid valve will close when the second stage compressor is off preventing refrigerant migration back to the compressor during the off cycle.

EXHAUST FANS

- General
 - Provide high limit pressure switch on the suction side of all constant volume fans greater than 3 HP to disable the fan upon exceeding static pressure setpoint. Provide manual reset.
- Toilet Exhaust Fans (Manual)
 - Exhaust fans shall be controlled by local manual switch furnished, installed and wired by electrical contractor. When activated, exhaust fan motor damper shall open and fan shall start.
- Janitor Closet Exhaust Fans (Timeclock)
 - Exhaust fans shall be tied to timeclock, which shall be furnished, installed and wired by electrical contractor. When activated, exhaust fan motor damper shall open and fan shall start.
- Kitchen Hood Exhaust Fan (Type I)
 - The Kitchen Hood exhaust system shall be initiated by a manual switch/8-hour wind-up timer located on the face of the kitchen hood with indicator light. At startup, energize exhaust fan motor.
 - The exhaust fan shall run continuously at constant speed. Provide a current transducer to prove fan operation. At shutdown, the exhaust fan shall stop.
 - Provide all controls and wiring for complete interlock and operation of Kitchen Hood, exhaust fan, and all associated motor dampers.

Apparatus Bay Exhaust Fans

- Multiple space carbon monoxide (CO) and nitrogen dioxide (NO2) sensors located in various spots in the apparatus bay shall control the exhaust system. Provide interface from the vehicle exhaust gas detection control panel so that on alarm of carbon monoxide (>35 ppm, adjustable) or on alarm of high nitrogen dioxide (>2 ppm, adjustable), and the motorized exhaust fan dampers and outside air damper intake shall open and fans shall start. Fan speed shall be set to balance to airflow as noted.
- Provide all controls for complete interlock and operation of Apparatus Bay Gas Detection System, exhaust fan and all associated motor dampers. Provide BACnet interface to be monitored by the BAS.
- Provide a manual over-ride in the apparatus bay to activate the system for a maximum of 30 minutes (adjustable). (SEE MIAMI TWTP 81)
- Option: Provide door switches and interface to exhaust system so that when doors are opened, fans shall start and dampers shall open, and system shall run for [15] min. adj. This shall not disable the carbon monoxide and nitrogen dioxide control or manual override of the system.
- Option: Provide option to interlock exhaust system enable with the building's Location system and the apparatus bay door switches. Apparatus bay exhaust system shall activate and run for 5 minutes upon any door opening conjunction with a tone drop. Exhaust system shall be deactivated if a door is opened and no tone drop is present.
- Provide indicator light adjacent to main control panel to illuminate when the exhaust system is activated.

Electric Wall Heater/ Unit Heater


- Provide integral thermostat with adjustable setpoint. On a call for heating, fan shall start and coil shall activate to maintain room temperature setpoint.

SPECIALTY CONTROLS AND MONITORING

Data Closets

Provide temperature sensor in each data closet that will alarm if temperature rises above setpoint.

KLH ENGINEERS
MECHANICAL/ELECTRICAL ENGINEERS
WWW.KLHENGRS.COM
1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8050
859-442-8058 FAX
LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK



DATE:	11/20/2019	DESIGNED BY:	DS	CHECKED BY:	RAL	APPROVED BY:	PG.	REV	0	ISSUE FOR BIDDING AND PERMIT	REVISIONS	DATE	11/20/2019	BY	CAM
DRAWN BY:															
F.B.															


SHARONVILLE FIRE STATION 87 RENOVATION


CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241

MECHANICAL - DETAILS

SCALE:	
HORZ:	
VERT:	
CONTRACT NO:	
170636	
SHEET	
M-502	

HOOD OPTIONS	
UL 710 LISTED W/ OUT EXHAUST FIRE DAMPER - UL #R25625	
HOOD TOP INSULATED FOR ZERO CLEARANCE TO COMBUSTIBLES	
BACK INTEGRAL AIR SPACE - 3 IN WIDE - ZERO CLEARANCE	
LEFT NON-INTEGRAL AIR SPACE - 1 IN THICK - ZERO CLEARANCE	
RIGHT NON-INTEGRAL AIR SPACE - 1 IN THICK - ZERO CLEARANCE	
6 IN HIGH CEILING ENCLOSURES - FRONT LEFT RIGHT - FIELD INSTALLED	
FACTORY MOUNTED EXHAUST COLLAR(S)	
BACKSPLASH 80.00 IN HIGH 50.00 IN LONG	
LEFT SIDESPLASH 108.00 IN HIGH 18.00 IN LONG	
RIGHT SIDESPLASH 108.00 IN HIGH 18.00 IN LONG	
PERFORMANCE ENHANCING LIP (PEL) TECHNOLOGY	
STANDING SEAM CONSTRUCTION FOR SUPERIOR STRENGTH	





ACCUREX

ACCUREX SOUTH OH KY IN

BRYAN OSBORN

BRYAN.OSBORN@ACCUREX.COM

(513)550-5511


PROJECT

8/29/2019

SHARONVILLE FIRE STATION

MARK

KH-1



UL

LISTED

CONSTRUCTION EQUIPMENT

SHARONVILLE FIRE STATION 87 RENOVATION CITY OF SHARONVILLE 11210 READING RD, SHARONVILLE, OH 45241	MECHANICAL - DETAILS
SCALE: HORZ: VERT:	
CONTRACT NO:	
170636	
SHEET	
M-503	



**KLH
ENGINEERS**

MECHANICAL/ELECTRICAL ENGINEERS

WWW.KLHENGERS.COM


1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075

800-354-9783
859-442-8050
859-442-8058 FAX

LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK



engineers
architects
planners



DATE	11/20/2019	11/20/2019	11/20/2019
DRAWN BY:	DS		
CHECKED BY:	HAL		
APPROVED BY:			
F.g.	PG.		

SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241

MECHANICAL - DETAILS

SCALE:
HORZ:
VERT:
CONTRACT NO:
170636
SHEET
M-504

Direct Drive Upblast Centrifugal Roof Exhaust Fan

MARK INFORMATION		FAN INFORMATION						MOTOR INFORMATION					
QTY	MARK	MODEL	VOLUME (CFM)	TOTAL EXTERNAL SP (IN WG)	FAN RPM	OPERATING POWER (HP)	WEIGHT (LB.)	SIZE (HP)	V/C/P	ENCLOSURE	MOTOR RPM	WINDINGS	NEC FLA*
1	KEF-1	XRUD-099-VG	788	0.962	1,725	0.24	69	0.25	115/60/1	OP	1725	1	5.8


*NEC FLA - Based on tables 150 or 148 of National Electrical Code 2002. Actual motor FLA may vary, for sizing thermal overload, consult factory

KEF-1 : SELECTED OPTIONS AND ACCESSORIES

Sidewall Mounting - Fan Configured for Wall-Mounted Applications
UL/ULC 762 Listed - "Power Ventilators for Rest. Exh. Appliances"
Switch, NEMA-3R, Toggle, Shipped with Unit
Hinged Bracket (PN: 877580)
Hinge Latch (PN: 879145)
High Temp Curb Seal Rated for Continuous Duty at 2000 F (Attached)
Grease Pan Kit - Containment Configured for Wall-Mounted Applications (PN 879136)
Grease Trap (PN:475538)



NOTE: SUGGESTED WALL OPENING WITH ROOF CURB - 19
DUCT DIMENSIONS ARE LARGEST POSSIBLE DUCT TO FIT THROUGH CURB.
CONSULT SYSTEM DESIGN ENGINEER FOR RECOMMENDED DUCT SIZE.
OVERALL HEIGHT MAY BE GREATER DEPENDING ON MOTOR.



SHARONVILLE FIRE STATION

KEF-1

PROJECT
8/29/2019

ACCUREX SOUTH OH KY IN
BRYAN OSBORN
BRYAN.OSBORN@ACCUREX.COM
(513)550-5511

FIRE SYSTEM INFORMATION

MARK	MODEL	LOCATION	FLOW POINTS		SUPPLY LINE	DETECTION	MARK(S) PROTECTED BY FIRE SYSTEM
			HOODS	PCU			
FIRE SUPPRESSION	ANSUL R-102 WET CHEMICAL	REMOTE MOUNTED	6 UTILIZED 11 AVAILABLE		CONTINUOUS	FUSIBLE LINK	KH-1 SECTION 1

FIRE SYSTEM OPTIONS AND ACCESSORIES

FULL INSTALLATION (INCLUDES PRE-PIPED HOOD(S) WITH DETECTION AND FACTORY COORDINATED INSTALL)
CHROME SLEEVES FOR FACTORY PROVIDED APPLIANCES DROPS - INCLUDED
METAL BLOW-OFF CAPS - INCLUDED
STAMPED DRAWINGS - INCLUDED
GAS VALVE - INCLUDED - MECHANICAL SHUTOFF VALVE, 2", (ANSUL) - PART# ANSULMECHSHUTOFFVALVE200
HOOD SUPPRESSION AGENT - INCLUDED - 3 GAL. - [(1) 3.0 TANK(S)]
REMOTE PULL STATION - STANDARD - INSTALLATION AT SINGLE POINT OF EGRESS

ANSUL R102 (WET CHEMICAL) FIRE PROTECTION SYSTEM - MODEL FS5C

CONTROL PANEL

NOT TO SCALE

NOTES:

WET CHEMICAL FIRE PROTECTION SYSTEM TO BE ANSUL R-102, DESIGNED IN COMPLIANCE WITH UL 300 REQUIREMENTS.

- VERIFICATION OF ALL COOKING EQUIPMENT MAKE, MODEL AND LOCATION REQUIRED FOR ALL FIRE PROTECTION SYSTEMS.
- ALL FIRE SYSTEM PIPING IS STANDARDLY TO THE RIGHT END OF THE HOOD UNLESS A WALL IS LOCATED ON THE RIGHT END.
- ANSUL AUTOMAN RELEASE TO BE LOCATED WITHIN 60" OF HOOD.

THE BASIC FIRE SYSTEM WILL INCLUDE THE FOLLOWING:

- GAS SHUT-OFF VALVE, IF REQUIRED, TO BE SUPPLIED BY MANUFACTURER (UP TO 2" DIAMETER AS STANDARD), AND INSTALLED BY A LICENSED PLUMBER.
- MICRO SWITCH TO BE SUPPLIED BY MANUFACTURER FOR CONNECTION TO, BUT NOT LIMITED TO, BUILDING ALARM SYSTEM(S), EXHAUST AND SUPPLY FANS AND ELECTRICAL POWER SHUT DOWN. FIELD WIRING AND CONNECTIONS TO BE PERFORMED BY A LICENSED ELECTRICIAN.

THE BASIC FIRE SYSTEM DOES NOT INCLUDE THE FOLLOWING:

- FULL DUMP TEST OTHER THAN WHAT IS SPECIFIED PER THE INSTALLATION MANUAL, OR TO SATISFY A STATE OR LOCAL CODE. PERMIT AND TESTING FEES ARE NOT INCLUDED UNLESS NOTED UNDER THE EQUIPMENT SCHEDULE FOR THE FIRE SYSTEM.
- MORE THAN TWO TRIPS TO THE JOBSITE OR SPECIAL TRANSPORTATION, OR OVERNIGHT LODGING REQUIREMENTS IN REMOTE AREAS. NORMAL TRAVEL DISTANCE IS FIRST 50 MI. (80.5 KM) FROM OFFICE.
- SPECIAL CLASSES OR ADDITIONAL LABOR FOR ACCESS TO SECURITY SENSITIVE AREAS.
- INSTALLATION OF GAS SHUT-OFF VALVE.
- SPECIAL DRAWINGS REQUIRED TO SATISFY STATE OR LOCAL CODE. PLAN EXAMINATION FEES, PE OR FS APPROVAL STAMP.
- UNION LABOR, GOVERNMENT LABOR, OR PREVAILING WAGES REQUIRED FOR FINAL FIELD HOOK-UP.
- ANY AND ALL ELECTRICAL COMPONENTS/CONNECTIONS REQUIRED TO SHUT DOWN FANS, SHUT OFF DEVICE FOR ELECTRIC COOKING EQUIPMENT (SHUNT TRIP BREAKER), OR ACTIVATE AN ALARM SYSTEM, ETC.
- ANY DISMANTLING OR REASSEMBLY REQUIRED TO GAIN ACCESS TO THE FIRE SUPPRESSION PIPING LOCATED ON THE TOP OF THE HOOD.
- ROUGH-IN HOOD CONDUIT FOR REMOTE PULL STATION OR GAS VALVE (FLUSH MOUNTED PULL STATION).
- INSTALLATION OF MORE THAN (1) REMOTE PULL STATIONS OR DISTANCES GREATER THAN 20 FT. (6.1 M.).
- PARTS OR LABOR REQUIRED TO CORRECT PIPING DUE TO COOKING EQUIPMENT CHANGES OR DEVIATION FROM PLANS, OR ANY CHARGES FOR MISSING OR ADDITIONAL PARTS OTHER THAN THOSE INDICATED ON THE FIRE SUPPRESSION DETAIL.

WIRING DIAGRAMS

W/D/POT MICRO SWITCH

DIPOT SWITCHES PROVIDED BY MANUFACTURER MAY BE WIRED PER TYPICAL EXAMPLES SHOWN, VERIFY WITH LOCAL CODES AND EQUIPMENT SUPPLIED AS THE CONNECTION NEEDED FOR YOUR INSTALLATION.

CONNECTION TO BUILDINGS ALARM

CONNECTION TO COOKING EQUIPMENT SHUT DOWN

CONNECTION TO FAN SHUT DOWN


NOTES:

- 1. --- DENOTES FIELD INSTALLATION.
- 2. --- DENOTES FACTORY INSTALLATION.
- 3. DO NOT USE BLACK WIRE ON SNAP-ACTION SWITCH IN NORMAL INSTALLATION. BLACK WIRE TO BE USED ONLY FOR EXTRANEUS ALARM, LIGHT CIRCUITS, ETC.

KLH ENGINEERS
MECHANICAL/ELECTRICAL ENGINEERS
WWW.KLHENGERS.COM
1538 ALEXANDRIA PIKE, SUITE 111
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8050
859-442-8058 FAX

LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK

your trusted advisor
engineers
architects
planners



SHARONVILLE FIRE STATION

FIRE SUPPRESSION

ACCUREX SOUTH OH KY IN
BRYAN OSBORN
BRYAN.OSBORN@ACCUREX.COM
(513)560-5511

ACCUREX

SHARONVILLE FIRE STATION 87 RENOVATION

CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241

MECHANICAL - DETAILS



















SCALE:	
HORIZ:	
VERT:	
CONTRACT NO:	170636
SHEET	M-506



















DATE	REV	REVISIONS	DATE	BY
11/20/2019	0	ISSUE FOR BIDDING AND PERMIT	11/20/2019	CMH
DRAWN BY:	DS			
CHECKED BY:	BAL			
APPROVED BY:				
F.B.				
NO.				

HVAC VENTILATION SCHEDULE																			
NUMBER	NAME	AREA	LEVEL	CEILING HEIGHT	AIR CHGS	OA CHGS	PEOPLE RED	OA PER PERSON	OA PER SQ.FT.	REQ SUP	ACT SUP	REQ OA	ACT OA	ACT RET	ACT EXH	CRIT OA	PRESSURE	PCT OPERABLE	NATURAL VENTILATION
100	VESTIBULE	76 SF	T/ FINISH FLOOR	9'-0"	0	0	0	0	0	47	50	7	8	50	0	0	E	0	
101	CORRIDOR	202 SF	T/ FINISH FLOOR	12'-0"	0	0	0	0	0.06	60	60	9	9	60	0	0.3166	E	0	
101	CORRIDOR	225 SF	T/ FINISH FLOOR	8'-0"	0	0	0	0	0.08	50	50	8	8	50	0	0.28	E	0	
102	SERVER	82 SF	T/ FINISH FLOOR	12'-0"	0	0	0	0	0	0	1040	0	0	1040	0	0	E	0	
103	FF OFFICE	124 SF	T/ FINISH FLOOR	9'-0"	0	0	1	5	0.06	100	100	15	15	100	0	0.15	E	0	
104	LT OFFICE	104 SF	T/ FINISH FLOOR	9'-0"	0	0	1	5	0.06	100	100	15	15	100	0	0.14	E	0	
105	LT BUNK	141 SF	T/ FINISH FLOOR	8'-11 31/32"	0	0	1	5	0.06	94	100	15	16	100	0	0.16	E	0	
106	FF BUNK	141 SF	T/ FINISH FLOOR	8'-11 31/32"	0	0	1	5	0.06	94	100	15	16	100	0	0.16	E	0	
107	RESTROOM	110 SF	T/ FINISH FLOOR	9'-0"	0	0	0	0	0	69	70	11	11	0	70	0	E	0	
108	RESTROOM	113 SF	T/ FINISH FLOOR	9'-0"	0	0	0	0	0	69	70	11	11	0	70	0	E	0	
109	FF BUNK	117 SF	T/ FINISH FLOOR	8'-11 31/32"	0	0	1	5	0.06	106	110	17	18	110	0	0.1363	E	0	
110	FF BUNK	129 SF	T/ FINISH FLOOR	8'-11 31/32"	0	0	1	5	0.06	94	100	15	16	100	0	0.16	E	0	
111	FF BUNK	128 SF	T/ FINISH FLOOR	8'-11 31/32"	0	0	1	5	0.06	94	100	15	16	100	0	0.16	E	0	
112	LAUNDRY	114 SF	T/ FINISH FLOOR	8'-11 31/32"	0	0	0	5	0.06	88	90	14	14	90	0	0.1	E	0	
115	JANITOR'S CLOSET	40 SF	T/ FINISH FLOOR	12'-0"	0	0	0	0	0	80	80	12	12	80	20	0	N	0	
116	CORRIDOR	Not Placed	Not Placed				1			0	0	0	0	0	0	0	E	0	
117	TOOLS/STORAGE	107 SF	T/ FINISH FLOOR	8'-7 3/16"	0	0	0	5	0.12	0	100	0	0	100	0	0	E	0	
118	SCBA	110 SF	T/ FINISH FLOOR	8'-6 27/32"	0	0	0	5	0.12	0	700	0	0	700	0	0	E	0	
119	DECON	256 SF	T/ FINISH FLOOR	8'-6 5/8"	0	0	0	5	0.12	0	200	0	0	200	0	0	E	0	
119	SCBA	Redundant Space	T/ FINISH FLOOR	8'-6 5/8"	0	0	0	0	0	0	0	0	0	0	0	0	E	0	
120	TURNOUT GEAR	246 SF	T/ FINISH FLOOR	8'-6 5/8"	0	0	0	5	0.12	0	500	0	0	500	0	0	E	0	
121	EMS SUPPLY	56 SF	T/ FINISH FLOOR	12'-0"	0	0	0	5	0.12	0	50	0	0	50	0	0	E	0	
122	STORAGE	53 SF	T/ FINISH FLOOR	12'-0"	0	0	0	5	0.12	0	50	0	0	50	0	0	E	0	
123	RESTROOM	61 SF	T/ FINISH FLOOR	12'-0"	0	0	0	0	0	0	50	0	0	0	50	0	E	0	
124	ELECTRICAL	62 SF	T/ FINISH FLOOR	7'-4 11/16"	0	0	0	0	0	0	30	0	0	30	0	0	E	0	
125	APPARATUS BAY	1783 SF	T/ FINISH FLOOR	11'-5 5/32"	0	0	0	0	0	1030	0	0	0	1030	0	0	E	0	
126	CLOSET	20 SF	T/ FINISH FLOOR	12'-0"	0	0	0	0	0	20	0	0	0	20	0	0	E	0	
129	STAIR	257 SF	T/ FINISH FLOOR	12'-0"	0	0	0	0	0.06	173	180	26	27	180	0	0.1055	E	0	
129	STAIR	269 SF	T/ FINISH FLOOR 2	11'-6 1/4"	0	0	0	0	0.06	88	90	7	7	90	0	0.2222	E	0	
200	CORRIDOR	Redundant Space	T/ FINISH FLOOR 2		0	0	0	0	0.06	38	40	3	3	40	0	0.275	E	0	
200	CORRIDOR	414 SF	T/ FINISH FLOOR 2	12'-8"	0	0	0	0	0.06	50	60	4	5	60	0	0.3166	E	0	
201	KITCHEN	494 SF	T/ FINISH FLOOR 2	11'-3 31/32"	0	0	2	0	0	1138	1250	91	100	1250	0	0	E	0	
202	DAYROOM	374 SF	T/ FINISH FLOOR 2	11'-10"	0	0	4	5	0.06	312	340	25	27	340	0	0.1529	E	0	
203	RESTROOM	108 SF	T/ FINISH FLOOR 2	10'-6"	0	0	0	0	0	50	60	4	5	0	70	0	N	0	
204	RESTROOM	119 SF	T/ FINISH FLOOR 2	10'-6"	0	0	0	0	0	62	70	5	6	0	70	0	E	0	
205	FITNESS	652 SF	T/ FINISH FLOOR 2	10'-7 23/32"	0	0	4	20	0.06	789	800	150	152	800	0	0.1875	E	0	
206	MECHANICAL	147 SF	T/ FINISH FLOOR 2	12'-8"	0	0	0	0	0	110	0	0	0	110	0	0	E	0	
207	JANITOR'S CLOSET	70 SF	T/ FINISH FLOOR 2	12'-0"	0	0	0	0	0	0	0	0	0	0	0	0	E	0	
208	CLOSET	10 SF	T/ FINISH FLOOR	11'-11 31/32"	0	0	0	0	0	0	0	0	0	0	0	0	E	0	
TOTAL		7511 SF																	

HVAC ELECTRICAL COORDINATION SCHEDULE

ABBREVIATIONS		CONTRACTOR TYPE										MOTOR CONTROL TYPE										CONTROL TYPE															
DC	LOCAL DISCONNECT	EC	ELECTRICAL CONTRACTOR	CS	COMBINATION STARTER	TC	TIMECLOCK	MC	MOTOR CONTROL (POWER)	EX	EXISTING	MCC	MOTOR CONTROL STARTER	CPT	CONTROL POWER TRANSFORMER	SD	DUCT SMOKE DETECTOR	FC	FIRE PROTECTION CONTRACTOR	MG	MAGNETIC STARTER OR CONTACT	BAS	BUILDING AUTOMATION SYSTEM	LOW	LOW VOLTAGE CONTROLS	LINE	LINE VOLTAGE CONTROLS	RLINE	REVERSE ACTING LINE VOLTAGE THERMOSTAT	MAN	MANUAL	FA	FIRE ALARM	CO	CARBON MONOXIDE SENSOR	INT	INTEGRAL TO EQUIPMENT
CN	CONTROLS	GC	GENERAL CONTRACTOR	MS	MANUAL STARTER	MSR	MANUAL STARTER W/ CONTROL RELAY	OV	OVERCURRENT PROTECTION	OR	OWNER OR OTHERS																										
TS	TOGGLE SWITCH	HC	HVAC CONTRACTOR	VFD	VARIABLE FREQUENCY DRIVE																																
C/B	H.A.C.R. CIRCUIT BREAKER AT SOURCE PANELBOARD	MFR	MANUFACTURER																																		
FUSE	FUSE AT LOCAL DISCONNECT (VERIFY FIELD RATING)	PC	PLUMBING CONTRACTOR																																		
FLA	OPERATING FULL LOAD AMPS																																				
MCA	MINIMUM CIRCUIT AMPACITY																																				
CP	CORD AND PLUG CONNECTION																																				
EQUIPMENT MARK	DESCRIPTION	VOLTS (V)	PHASE	EMERGENCY	BHP (HP)	HP (HP)	HTG (kW)	WATTS	Fed From	FLA (A)	MCA (A)	OCF (A)	DC TYPE	DC FURN	DC INST	DC WIRE	MC TYPE	MC FURN	MC INST	MC WIRE	CN TYPE	CN FURN	CN INST	CN WIRE	SD TYPE	AVAILABLE FAULT CURRENT (A)											
ACCU-01	AIR COOLED REFRIGERANT CONDENSERS	208	1							4.5	7			EC	EC	EC	MG	MFR	MFR	MFR	LOW	HC	HC	HC		1711											
ACU-01	DEHUMIDIFICATION UNIT	208	1								32	50		EC	EC	EC	MG	MFR	MFR	MFR	LOW	HC	HC	HC	DUCT SMOKE	7026											
CF-01	CEILING FAN	120	1			1/16								EC	EC	EC	VFD	MFR	MFR	MFR	LINE	EC	EC	EC													
CF-02	CEILING FAN	120	1			1/16								EC	EC	EC	VFD	MFR	MFR	MFR	LINE	EC	EC	EC													
CU-01	AIR COOLED CONDENSING UNIT	208	1							14.1	20			EC	EC	EC	MG	MFR	MFR	MFR	LOW	HC	HC	HC		2315											
CU-02	AIR COOLED CONDENSING UNIT	208	1							11.7	20			EC	EC	EC	MG	MFR	MFR	MFR	LOW	HC	HC	HC		2824											
CU-03	AIR COOLED CONDENSING UNIT	208	1							27.5	40			EC	EC	EC	MG	MFR	MFR	MFR	LOW	HC	HC	HC		5127											
CU-04	AIR COOLED CONDENSING UNIT	208	1							14.1	20			EC	EC	EC	MG	MFR	MFR	MFR	LOW	HC	HC	HC		1906											
DS-01	DUCTLESS SPLIT HIGH WALL UNIT	208	1						DSCU-01					EC	EC	EC	MG	MFR	MFR	MFR	LOW	MFR	MFR	MFR													
DSCU-01	DUCTLESS SPLIT OUTDOOR CONDENSING UNIT	208	1							18	25			EC	EC	EC	MG	MFR	MFR	MFR	LOW	MFR	MFR	MFR		3234											
ECP	ENVIRONMENTAL CONTROL PANEL	120	1											EC	EC	EC	---	---	---	---	BAS	HC	HC	HC													
EDH-01	ELECTRIC FURNACE	208	3				18							EC	EC	EC	MG	MFR	MFR	MFR	LOW	HC	HC	HC		5698											
EF-01	CENTRIFUGAL ROOF VENTILATOR	208	1			25				3.2				EC	EC	EC	MG	MFR	MFR	MFR	LINE	EC	EC	EC		1793											
EF-02	CEILING MOUNTED VENTILATOR	120	1							0.58				EC	EC	EC	MG	MFR	MFR	MFR	OCC	EC	EC	EC		1872											
EF-03	CEILING MOUNTED VENTILATOR	120	1							0.58				EC	EC	EC	MG	MFR	MFR	MFR	OCC	EC	EC	EC		1495											
EF-04	CEILING MOUNTED VENTILATOR	120	1							0.58				EC	EC	EC	MG	MFR	MFR	MFR	OCC	EC	EC	EC		1062											
EF-05	CEILING MOUNTED VENTILATOR	120	1							0.58				EC	EC	EC	MG	MFR	MFR	MFR	OCC	EC	EC	EC		915											
EF-06	CEILING MOUNTED VENTILATOR	120	1							0.27				EC	EC	EC	MG	MFR	MFR	MFR	LINE	EC	EC	EC		1680											
EF-07	CEILING MOUNTED VENTILATOR	120	1							0.34				EC	EC	EC	MG	MFR	MFR	MFR	OCC	EC	EC	EC		1973											
EF-08	CENTRIFUGAL ROOF VENTILATOR	120	1			1/10				2.6				EC	EC	EC	MG	MFR	MFR	MFR	LINE	EC	EC	EC		1377											
EF-09	CEILING MOUNTED VENTILATOR	120	1							0.34				EC	EC	EC	MG	MFR	MFR	MFR	OCC	EC	EC	EC		1680											
EW-01	WALL AND CEILING HEATER	120	1				1.5			12.5				EC	EC	EC	---	---	---	---	INT	MFR	MFR	MFR		1438											
EW-02	WALL AND CEILING HEATER	120	1				1.5			12.5				EC	EC	EC	---	---	---	---	INT	MFR	MFR	MFR		2389											
EW-03	WALL AND CEILING HEATER	120	1				1.5			12.5				EC	EC	EC	---	---	---	---	INT	MFR	MFR	MFR		795											
EW-04	WALL AND CEILING HEATER	120	1				1.5			12.5				EC	EC	EC	---	---	---	---	INT	MFR	MFR	MFR		875											
FCU-01	FANCOIL UNIT	120	1							7	15			EC	EC	EC	MG	MFR	MFR	MFR	LOW	HC	HC	HC	DUCT SMOKE	4911											
FCU-02	FANCOIL UNIT	120	1							5.1	15			EC	EC	EC	MG	MFR	MFR	MFR	LOW	HC	HC	HC	DUCT SMOKE	5035											
FCU-03	FANCOIL UNIT	120	1							14.8	20			EC	EC	EC	MG	MFR	MFR	MFR	LOW	HC	HC	HC	DUCT SMOKE	3860											
FCU-04	FANCOIL UNIT	120	1							7	15			EC	EC	EC	MG	MFR	MFR	MFR	LOW	HC	HC	HC	DUCT SMOKE	3906											
GPUH-01	GAS FIRED UNIT HEATER	120	1							3.9				EC	EC	EC	MG	MFR	MFR	MFR	LINE	HC	EC	EC		1327											
KEF-01	CENTRIFUGAL WALL VENTILATOR	120	1			25				5.8				EC	EC	EC	MG	MFR	MFR	MFR	LINE	EC	EC	EC		1800											
MOD		120																																			

ELECTRIC LEGEND		ELECTRIC LEGEND	
SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
LIGHTING AND LIGHTING CONTROLS		SINGLE LINE DIAGRAM	
	LUMINAIRE (REFER TO THE LUMINAIRE SCHEDULE) NOTE THAT OTHER SHAPES MAY ALSO BE USED TO REPRESENT LUMINAIRES		ELECTRIC UTILITY COMPANY METER AND ASSOCIATED CURRENT TRANSFORMERS
	SHADED LUMINAIRES DENOTE THOSE CONNECTED TO EMERGENCY OR STANDBY POWER AS APPLICABLE (UNSWITCHED LUMINAIRES ARE EGRESS LIGHTS AND/OR NIGHT-LIGHTS THAT OPERATE 24/7)		CUSTOMER ELECTRIC METER AND ASSOCIATED CURRENT TRANSFORMERS HD = HIGH DENSITY METERING CABINET/BANK MOUNTED TO TIGHTLY GROUP ALL METERS TOGETHER
	TRACK LIGHTING IN LENGTH SHOWN AND WITH NUMBER OF LUMINAIRE HEADS AS INDICATED PROVIDE ALL REQUIRED ACCESSORIES (FITTINGS, END CAPS, POWER FEEDS, ETC.)		GROUNDING ELECTRODE PER NFPA 70 ARTICLE 250 MINIMUM
	SINGLE / DOUBLE SIDED EXIT SIGN CONNECT AHEAD OF SWITCHING & CONFIGURE ARROWS TO INDICATE DIRECTION OF EGRESS TRAVEL		ELECTRICAL PANELBOARD OR DISTRIBUTION BOARD
	EMERGENCY LIGHTING UNIT WITH 90-MINUTE BATTERY BACKUP AND ASSOCIATED REMOTE HEADS WHERE APPLICABLE. CONNECT TO LOCAL LIGHTING CIRCUIT AHEAD OF SWITCHING		AUTOMATIC TRANSFER SWITCH
	OUTDOOR AREA SITE LIGHTING STANDARD NUMBER OF LUMINAIRE HEADS AS INDICATED ON DRAWINGS.		SURGE PROTECTIVE DEVICE
	A = LUMINAIRE TYPE, NL = NIGHT-LIGHT (UNSWITCHED), a = SWITCHING DESIGNATION, EL = EGRESS LUMINAIRE (ILLUMINATES PATH OF EGRESS, ON ALL TIMES SPACE IS OCCUPIED)	WIRE / CABLE / RACEWAY	
	LIGHTING SWITCH (KEYS: 2 = 2-POLE, 3 = 3-WAY, 4 = 4-WAY, D=DIMMER, K=KEYED, LV = LOW VOLTAGE M = MOMENTARY-CONTACT 1PDT W/CENTER-REST, P = SWITCH W/PILOT LIGHT, T = TIMER SWITCH)		BRANCH CIRCUIT HOME RUN WITH PANEL NAME AND CIRCUIT NUMBER(S)
	CEILING-MOUNTED OCCUPANCY SENSOR. DUAL TECHNOLOGY UNLESS OTHERWISE NOTED BY TYPE. TYPE "IR" = INFRARED, TYPE "US" = ULTRASONIC	CABLING / RACEWAY INSTALLED CONCEALED IN WALLS OR ABOVE CEILING	
	WALL-MOUNTED OCCUPANCY SENSOR SWITCH. DUAL TECHNOLOGY UNLESS OTHERWISE NOTED BY TYPE. TYPE "IR"-INFRARED, TYPE "US"-ULTRASONIC, "V"-VACANCY SENSOR, "F" = CONTROLLED CIRCUITS.	CABLING / RACEWAY INSTALLED BELOW FLOOR OR GRADE	
	PHOTOCELL / LIGHT-SENSOR / PHOTO-SENSOR	CABLE TRAY	

ELECTRIC LEGEND	
SYMBOL	DESCRIPTION
SINGLE LINE DIAGRAM	
 	ELECTRIC UTILITY COMPANY METER AND ASSOCIATED CURRENT TRANSFORMERS
HD  	CUSTOMER ELECTRIC METER AND ASSOCIATED CURRENT TRANSFORMERS HD = HIGH DENSITY METERING CABINET/BANK MOUNTED TO TIGHTLY GROUP ALL METERS TOGETHER
	GROUNDING ELECTRODE PER NFPA 70 ARTICLE 250 MINIMUM
	ELECTRICAL PANELBOARD OR DISTRIBUTION BOARD
	AUTOMATIC TRANSFER SWITCH
	SURGE PROTECTIVE DEVICE
WIRE / CABLE / RACEWAY	
 LPA-1.3	BRANCH CIRCUIT HOME RUN WITH PANEL NAME AND CIRCUIT NUMBER(S)
	CABLING / RACEWAY INSTALLED CONCEALED IN WALLS OR ABOVE CEILING
	CABLING / RACEWAY INSTALLED BELOW FLOOR OR GRADE
	CABLE TRAY
	FEEDER DUCT / BUS DUCT
	JUNCTION BOX ABOVE ACCESSIBLE CEILING JUNCTION BOX AT OVERHEAD STRUCTURE IN AREAS WITH NO CEILING
	FLUSH MOUNTED JUNCTION BOX OR PULL BOX AS APPLICABLE FOR APPLICATION
	FLUSH MOUNTED PULL BOX
	UTILITY POLE
UP  DN	CONDUIT UP OR DOWN

ELECTRIC DESIGN CRITERIA	
APPLICABLE BUILDING CODES	
2017 OHIO BUILDING CODE (BASED ON THE INTERNATIONAL BUILDING CODE) 2017 NFPA 70 - NATIONAL ELECTRICAL CODE 2017 OHIO FIRE CODE (BASED ON NATIONAL FIRE ALARM AND SIGNALING CODE) 2015 INTERNATIONAL ENERGY CONSERVATION CODE (IECC)	
TESTING/COMMISSIONING FOR LIGHTING CONTROLS	
LIGHTING CONTROL DEVICES AND SYSTEMS SHALL BE TESTED TO ENSURE THE HARDWARE AND SOFTWARE IS CALIBRATED, PROGRAMMED, AND IN PROPER WORKING ORDER. INSTALLING CONTRACTOR SHALL BE RESPONSIBLE FOR ALL REQUIRED INSTALLATION CERTIFICATES AND SHALL PROVIDE MANUALS FOR LIGHTING CONTROL DEVICES TO OWNER PRIOR TO PROJECT CLOSE-OUT. INSTALLING CONTRACTOR SHALL BE RESPONSIBLE FOR CONTRACTING WITH APPROPRIATE PARTIES TO ARRANGE REQUIRED FUNCTIONAL TESTING FORMS ARE COMPLETED AND SUBMITTED TO THE OWNER AND LOCAL AHJ PRIOR TO PROJECT CLOSE-OUT.	
DWELLING UNITS	
THE FOLLOWING SPACES ARE CONSIDERED DWELLING AREAS AND SHALL BE COMPLIANT WITH REQUIREMENTS SET FORTH IN NEC 210.52: <ul style="list-style-type: none"> - SLEEPING ROOMS - SHOWER ROOMS IN LIVING QUARTERS - KITCHEN AND DAYROOM 	
UTILITY COORDINATION	
COORDINATE UTILITY SERVICE WORK CONTAINED WITHIN THIS DRAWING SET WITH RESPECTIVE LOCAL UTILITY COMPANY. KLH HAS STARTED THIS COORDINATION PROCESS WITH UTILITY COMPANY REPRESENTATIVE LISTED BELOW AS PART OF THE DESIGN PHASE. CONTINUE THIS COORDINATION PROCESS PRIOR TO STARTING ANY WORK AND CONTINUE THROUGHOUT CONSTRUCTION PHASE.	
OBTAIN AND COMPLY WITH UTILITY INSTALLATION DETAILS AND STANDARDS.	
CONTACT 811 "CALL BEFORE YOU DIG" SERVICE PRIOR TO COMMENCING ANY UNDERGROUND WORK.	
ELECTRIC SERVICE	
UTILITY COMPANY	DUKE ENERGY
UTILITY CONTACT	CHARLIE NORDIN
PHONE NUMBER	513-287-1194
EMAIL ADDRESS	Charles.Nordin@duke-energy.com
DATE(S) CONTACTED	10/25/2019
KLH CONTACT	KEELY HUSTON


















<u>ELECTRICAL SECONDARY SERVICE (OWNER-PURCHASED SECONDARY)</u>		
TRANSFORMER		
OWNERSHIP	UTILITY	
NEW OR EXISTING	EXISTING	
SECONDARY VOLTAGE (V)	208Y/120V	
MAX NUMBER OF CONDUITS IN SECONDARY COMPARTMENT	8	
AVAILABLE FAULT CURRENT AT SECONDARY LUGS (A)	55,600A	
METERING		
CURRENT TRANSFORMER (CT) LOCATION	CT CABINET	
<u>RESPONSIBILITY MATRIX (X = FURNISH AND INSTALL)</u>	<u>UTILITY</u>	<u>DIVISION 26 CONTRACTOR</u>
TRANSFORMER	EXISTING	
PRIMARY CABLE	EXISTING	
SECONDARY CONDUIT		X
SECONDARY CONDUCTORS		X
TERMINATE SECONDARY CONDUCTORS, 1) AT UTILITY END	X	
2) AT SERVICE DISTRIBUTION EQUIPMENT		X
METER SOCKET		X
CT CABINET		X






ELECTRIC CONDUIT AND WIRE MATERIAL SCHEDULE	
MC - METAL CLAD CABLE	ARC - ALUMINUM RIGID CONDUIT
MI - MINERAL INSULATED CABLE	EMT - ELECTRIC METALLIC TUBING
USE - UNDERGROUND SERVICE ENTRANCE CABLE	ENT - ELECTRIC NON-METALLIC TUBING
SE - SERVICE ENTRANCE CABLE	FMC - FLEXIBLE METALLIC CONDUIT
UF - UNDERGROUND FEEDER	GRC - GALVANIZED RIGID STEEL CONDUIT
UMC - NON-METALLIC SHEATHED CABLE	HDPE - HIGH DENSITY POLYETHYLENE CONDUIT
RMC - RIGID METAL CONDUIT	IMC - INTERMEDIATE METAL CONDUIT
RNC - RIGID NON-METALLIC CONDUIT	LFMC - LIQUID-TIGHT FLEXIBLE METALLIC CONDUIT
RT/RC - REINFORCED THERMOSETTING RESIN CONDUIT	LFMC - LIQUIT-TIGHT FLEXIBLE NON-METALLIC CONDUIT
SCH 80 PVC - SCHEDULE 80 POLYVINYL CHLORIDE CONDUIT	SCH 40 PVC - SCHEDULE 40 POLYVINYL CHLORIDE CONDUIT


















CONDUIT APPLICATION	CONDUCTOR TYPE	RACEWAY TYPE	RACEWAY AND CONDUCTOR NOTES
---FIRE ALARM---			
EXISTING HOLLOW PARTITIONS	PLENUM OR NON-PLENUM RATED	EMT	
CONCEALED	PLENUM OR NON-PLENUM RATED	EMT	
EXPOSED, WALL	PLENUM OR NON-PLENUM RATED	EMT	
CONCEALED, ABOVE ACCESSIBLE CEILINGS	PLENUM OR NON-PLENUM RATED	J-HOOKS	
CONCEALED, ABOVE INACCESSIBLE CEILINGS	PLENUM OR NON-PLENUM RATED	EMT	
EXPOSED, OVERHEAD	PLENUM OR NON-PLENUM RATED	EMT	
BELOW GRADE OR CONCRETE SLAB	PLENUM OR NON-PLENUM RATED	RNC (SCH 40 PVC)	


---POWER - INDOOR---			
EXISTING HOLLOW PARTITIONS	THHN	MC OR FMC	
CONCEALED	THHN	MC	
CONCEALED, DAMP LOCATIONS	XHHW-2	LFMC	
CONCEALED, MASONRY	THHN	EMT	
VERTICAL RISERS FROM BELOW GRADE INCLUDING ELBOW	THHN	RMC (GRC)	
BELOW GRADE OR CONCRETE SLAB	THHN	RNC (SCH 40 PVC)	
LUMINAIRE WHIPS IN ACCESSIBLE CEILING, 72" MAX	THHN	MC	
CONNECTION TO VIBRATING EQUIPMENT, 72" MAX	THHN	LFMC	
EXPOSED	THHN	EMT	
UNDERGROUND	XHHW-2	RNC (SCH 40 PVC)	

---POWER - OUTDOOR---			
EXPOSED	XHHW-2	RMC (GRC)	
CONCEALED	XHHW-2	EMT	
UNDERGROUND	XHHW-2	RNC (SCH 40 PVC)	
CONNECTION TO VIBRATING EQUIPMENT, 72" MAX	XHHW-2	LFMC	
EXPOSED TO DIRECT SUNLIGHT, ROOF	XHHW-2	RMC (GRC)	

RECEPTACLES AND MISCELLANEOUS OUTLETS	
	SINGLE ("SIMPLEX"), DUPLEX, AND DOUBLE DUPLEX ("QUAD") RECEPTACLE RESPECTIVELY
	RECEPTACLES ON EMERGENCY OR STANDBY POWER CIRCUIT DIAMOND OUTLINE MAY BE APPLIED TO ANY SPECIALTY RECEPTACLE SYMBOL
	GFI / GFOI RECEPTACLES
	RECEPTACLES WITH USB OUTLETS
	SPECIAL PURPOSE RECEPTACLE
	CEILING DUPLEX RECEPTACLE WITH ADJACENT REEL-MOUNTED DROP CORD.
	RECEPTACLE ATTRIBUTES 42" = MOUNT RECEPTACLE AT THIS HEIGHT ABOVE GRADE / FINISHED FLOOR C = INSTALL ABOVE COUNTER AND BACKSPASH H = INSTALL RECEPTACLE HORIZONTALLY L = LIT (PROVIDE ILLUMINATED FACE OR INDICATOR LIGHT TO INDICATE THERE IS POWER TO RECEPTACLE) SW = SPLIT WIRED T = TAMPER-RESISTANT W = WEATHER PROOF WHILE IN USE COVER AND WEATHER RESISTANT RECEPTACLE
DOOR OPERATORS/DEVICES	
	SECURITY JUNCTION BOX - WALL-MOUNT ABOVE ACCESSIBLE CEILING ON SECURE SIDE OF DOOR
FIRE ALARM DEVICES	
	FIRE ALARM SYSTEM MANUAL PULL STATION
	FIRE ALARM SYSTEM SMOKE DETECTOR - PHOTOELECTRIC TYPE UNLESS OTHERWISE NOTED L = LASER TYPE, S = PROVIDE SOUNDER BASE
	FIRE ALARM SMOKE ALARM UNIT - M = SINGLE/MULTI-STATION SMOKE ALARM UNIT, MC = SINGLE/MULTI-STATION COMBINATION SMOKE/CARBON MONOXIDE ALARM UNIT
	FIRE ALARM SYSTEM DUCT SMOKE DETECTOR AND SAMPLING TUBE
	FIRE ALARM SYSTEM CONTROL / RELAY MODULE (LEFT) FIRE ALARM SYSTEM MONITOR MODULE (RIGHT)
	FIRE ALARM SYSTEM STROBE-ONLY DEVICE (PROVIDE CANDELA (cd) RATING FOR STROBE AS INDICATED ON DRAWINGS)
	FIRE ALARM SYSTEM HORN / STROBE DEVICE (PROVIDE CANDELA (cd) RATING FOR STROBE AS INDICATED ON DRAWINGS)
	FIRE ALARM PANELS - (DIMENSIONS MAY VARY / FLUSH OR SURFACE MOUNTED AS INDICATED) FACP - FIRE ALARM CONTROL PANEL FARP - FIRE ALARM REMOTE BATTERY PANEL / CABINET FAVE - FIRE ALARM VOICE EVACUATION PANEL FSCP - FIREFIGHTER'S SMOKE CONTROL PANEL FASP - FIRE ALARM SPRINKLER MONITOR OR PANEL FARA - FIRE ALARM REMOTE ANNUNCIATOR
ENVIRONMENTAL CONTROLS AND ALARMS	
	VOLATILE ORGANIC COMPOUNDS (VOC) SENSOR (MONITORED BY ENVIRONMENTAL CONTROL PANEL)

FEEDER DUCT / BUS DUCT			
	JUNCTION BOX ABOVE ACCESSIBLE CEILING JUNCTION BOX AT OVERHEAD STRUCTURE IN AREAS WITH NO CEILING		
	FLUSH MOUNTED JUNCTION BOX OR PULL BOX AS APPLICABLE FOR APPLICATION		
	FLUSH MOUNTED PULL BOX		
	UTILITY POLE		
	CONDUIT UP OR DOWN		
ABBREVIATIONS			
(R)	RELOCATE FIXTURE, EQUIPMENT OR DEVICE	IG	ISOLATED GROUND
42"	DISTANCE ABOVE FINISHED FLOOR / GRADE / PAVEMENT	LR	LEGALLY REQUIRED STANDBY
AF	AMP FRAME OF FUSED SWITCH OR CIRCUIT BREAKER	LI	LONG - INSTANTANEOUS
AFCI	ARC-FAULT CIRCUIT INTERRUPTER	LSIG	LONG - SHORT - INSTANTANEOUS
AIC	AMPS INTERRUPTING CURRENT	MCB	MAIN CIRCUIT BREAKER
ATS	ATM TRIP OF FUSED SWITCH OR CIRCUIT BREAKER	MFR	MANUFACTURER
AT	AUTOMATIC TRANSFER SWITCH	MLO	MAIN LUGS ONLY
BAS	BUILDING AUTOMATION SYSTEM	MTS	MANUAL TRANSFER SWITCH
C.T.C.	WORK UNDER DIVISION 27 OR 28 AS APPLICABLE	MW	MICROWAVE OVEN
C/B	CIRCUIT BREAKER	C.N.C.	NOT IN CONTRACT (SHOWN FOR REFERENCE ONLY)
CH	COUNTER HEIGHT OR SPECIAL HEIGHT DEVICE	NTS	NOT TO SCALE
DW	DISHWASHER	OFE	OWNER-FURNISHED EQUIPMENT - INSTALLED AND WIRED BY E.C.
E	EMERGENCY	OS	OPTIONAL STANDBY
E.C.	WORK UNDER DIVISION 26	P.C.	WORK UNDER DIVISION 22
EMS	ENERGY MANAGEMENT SYSTEM	(R)	RELOCATED
EPO	EMERGENCY POWER OFF	S.C.	WORK UNDER DIVISION 21
ER	EQUIPMENT ROOM	SCCR	SHORT CIRCUIT CURRENT RATING
ERM	ENERGY REDUCTION MAINTENANCE SWITCH	SPD	SURGE PROTECTIVE DEVICE
ESP	EMERGENCY STANDBY RATING	ST	SHUNT TRIP
ETR	EXISTING TO REMAIN	TAAC	TO ABOVE ACCESSIBLE CEILING
EW	ELECTRIC WATER COOLER	TR	TAMPER RESISTANT
EX	EXISTING	TYP	TELEPHONE TERMINAL BOARD TYPICAL
FBO	FURNISHED BY OTHERS - INSTALLED AND WIRED BY E.C.	UCR	UNDER COUNTER REFRIGERATOR
FIBO	FURNISHED AND INSTALLED BY OTHERS - WIRED BY E.C.	U.L.S.E.	UNDERWRITERS' LABORATORY LISTED FOR SERVICE ENTRANCE
FP	RECEPTACLE TO BE USED FOR A FLAT PANEL DISPLAY.	UNO	UNLESS NOTED OR INDICATED OTHERWISE ON DRAWINGS OR IN SPECIFICATIONS
FWE	FURNISHED WITH EQUIPMENT BY OTHERS - INSTALLED AND WIRED BY E.C.	VFD / VSD	VARIABLE FREQUENCY / SPEED DRIVE
GD	GARBAGE DISPOSAL	VFI	VERIFY IN FIELD
GFI / GFOI	GROUND FAULT EQUIPMENT PROTECTION	VM	VENDING MACHINE
GND	GROUND FAULT CIRCUIT INTERRUPTER DEVICE	VP	VANDAL PROOF
H.C.	WORK UNDER DIVISION 23	W / WP	WEATHERPROOF
H.O.A.	"HAND - OFF - AUTO" SWITCH	WG	WIRE GUARD
		WR	WEATHER RESISTANT

MISCELLANEOUS		PLAN-VIEW AND GRAPHIC LINE TYPES	
	INDICATES DIRECT CONNECTION TO EQUIPMENT	WORK SHOWN BOLD-CONTINUOUS INDICATES NEW WORK (UNLESS OTHERWISE INDICATED)	
  	MOTOR RATED TOGGLE SWITCH, MANUAL STARTER WITH PILOT LIGHT, AND MANUAL STARTER WITH PILOT LIGHT WITH EXTERNAL RELAY FOR CONTROL OR MONITORING RESPECTIVELY - ALL MAY BE KEYED "K"	WORK SHOWN FADED INDICATES EXISTING WORK TO REMAIN OR NEW WORK BY OTHERS AS APPLICABLE (UNLESS OTHERWISE INDICATED)	
 	HEAVY DUTY DISCONNECT SWITCH (NON-FUSED) (LEFT) HEAVY DUTY DISCONNECT SWITCH (FUSED) (RIGHT)	WORK SHOWN BOLD-DASHED INDICATES SELECTIVE DEMOLITION WORK (UNLESS OTHERWISE INDICATED)	
	MOTOR		
	VARIABLE FREQUENCY DRIVE / VARIABLE SPEED DRIVE		
	LINE VOLTAGE MOTOR OPERATED DAMPER		
	EMERGENCY-POWER-OFF (EPO) PUSHBUTTON STATION WITH DESCRIPTIVE ENGRAVED PLATE AND MEANS TO PREVENT ACCIDENTAL ACTIVATION		
	CONTROL STATION WITH DESCRIPTIVE ENGRAVED PLATE		
	CONTACTOR		
	PLYWOOD EQUIPMENT BOARD		
	ELECTRICAL PANELBOARD OR DISTRIBUTION BOARD (DIMENSIONS MAY VARY / FLUSH OR SURFACE MOUNTED AS INDICATED)		
  	OIL FILLED TRANSFORMER		



**KLH
ENGINEERS**

MECHANICAL/ELECTRICAL ENGINEERS

WWW.KLHENGRS.COM

1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075

800-354-9763
859-442-8050
859-442-8058 FAX

LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK

ESSENTIAL FACILITY SEISMIC REQUIREMENTS

SEISMIC BRACING FOR ALL NON-STRUCTURAL COMPONENTS INCLUDING BUT NOT LIMITED TO EQUIPMENT, PIPING, CONDUIT AND DUCTWORK IS REQUIRED FOR THIS PROJECT. THE DESIGN AND INSTALLATION OF THE SEISMIC RESTRAINT DEVICES IS DELEGATED TO THE CONTRACTOR. REFER TO SEISMIC CONTROLS SPECIFICATION FOR DELEGATED DESIGN SUBMITTAL REQUIREMENTS.

GENERAL ELECTRICAL INSTALLATION NOTES

A. CODE COMPLIANCE: PROVIDE ALL ELECTRICAL WORK COMPLIANT WITH ALL PREVAILING CODES.

B. LISTINGS: PROVIDE MATERIALS, COMPONENTS AND ASSEMBLED COMPONENTS WITH LISTINGS AND LABELS FROM A NATIONALLY RECOGNIZED TESTING LABORATORY (NRTL), MANUFACTURED, LISTED AND LABELED FOR THEIR INTENDED USE.

C. RATED BUILDING SURFACES: SEPARATE DEVICE BOXES BY A MINIMUM OF 6 INCHES WHERE INSTALLED

SHARONVILLE FIRE STATION 87 RENOVATION

CITY OF SHARONVILLE

11210 READING RD, SHARONVILLE, OH 45241

ELECTRIC COVER SHEET

11/04/19

your trusted advisor
engineers
architects
planners
consultants

SCALE: 1/8" = 1'-0"

HORIZ:



VERT:

CONTRACT NO: 170636


SHEET

E-001

DATE:	REV	REVISIONS	DATE	BY
11/26/2019	0	ISSUE FOR BIDDING AND PERMIT	11/20/2019	CAM
DRAWN BY: JCL				
CHECKED BY: PJA				
APPROVED BY:				
PL NO:				
PG:				



ELECTRIC SITE PLAN



SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241
ELECTRIC SITE PLAN

DATE:	11/20/2019	PM	ISSUE FOR BIDDING AND PERMIT	11/20/2019	CAM
DRAWN BY:	KH				
CHECKED BY:	PM				
APPROVED BY:					
g. No.					
g. PG.					

SCALE: 3/32" = 1'-0"

HORIZ:

VERT:


CONTRACT NO:

170636

SHEET

ES101

GENERATOR
TO BE DEMOLISHED
AND TURNED OVER
TO OWNER




1
E-101
1/8" = 1'-0"

FIRST FLOOR ELECTRIC DEMOLITION PLAN



2
E-101
1/8" = 1'-0"

SECOND FLOOR ELECTRIC DEMOLITION PLAN



3
E-101
1/8" = 1'-0"

ROOF ELECTRIC DEMOLITION PLAN

KEYED NOTES

- E5 DEMOLISH ELECTRICAL DISTRIBUTION EQUIPMENT AND SERVICE BACK TO TRANSFORMER. REFER TO NEW POWER PLAN AND SINGLE-LINE DIAGRAM FOR NEW SERVICE ENTRANCE REQUIREMENTS AND LOCATION.
- E6 UNLESS NOTED OTHERWISE, DEMOLISH EXISTING LIGHTING AND POWER IN THIS AREA. REMOVE ALL BRANCH WIRING AND ACCESSIBLE CONDUIT BACK TO SOURCE.

KLH ENGINEERS
MECHANICAL/ELECTRICAL ENGINEERS
WWW.KLHENGRS.COM

1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8050
859-442-8058 FAX

LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK

EXISTING CONDITIONS - GENERAL NOTES

- A. **INTENT OF DOCUMENTS:** IT IS NOT THE INTENT OF ELECTRICAL DOCUMENTS THAT EXISTING CONDITIONS BE ACCURATELY SHOWN. EXISTING ELECTRICAL WORK IS SHOWN TO A VERY LIMITED EXTENT ON DRAWINGS AND IS SHOWN FOR GENERAL PLANNING REFERENCE ONLY. LOCATIONS AND INFORMATION WERE DERIVED FROM CURSORY VISUAL OBSERVATIONS OR FROM PORTIONS OF DOCUMENTS THAT WERE PREPARED FOR PREVIOUSLY INSTALLED WORK (NOT FROM RECORD DRAWINGS OR "AS-BUILTS").
- B. **PRE-BID SURVEY:** PERFORM A DETAILED PRE-BID WALK-THROUGH FIELD INSPECTION AND SURVEY TO REVIEW THE EXISTING STRUCTURES AND PREMISES, TO ACCURATELY DETERMINE EXISTING CONDITIONS, AND TO DETERMINE SCOPE OF REQUIRED ELECTRICALLY RELATED WORK. INCLUDE APPLICABLE ACCESSIBLE CEILING CAVITY AREAS IN THIS INSPECTION.
- C. **RISK MITIGATION:** MINIMIZE RISKS TO INDIVIDUALS AND PROPERTY THROUGHOUT THE DURATION OF THE PROJECT. COORDINATE WITH, AND OBTAIN APPROVAL FROM, THE OWNER AND DESIGN PROFESSIONAL FOR ALL MATERIALS, METHODS, STEPS, LOCATIONS, INSTALLATIONS, ETC. PRIOR TO COMMENCEMENT OF WORK. DETERMINE AND EMPLOY MEANS AND METHODS AS REQUIRED TO SAFELY AND SECURELY IMPLEMENT ALL RELATED WORK.
- D. **REUSE OF REMOVED MATERIALS:** DO NOT REUSE REMOVED ELECTRICAL MATERIALS UNLESS SPECIFICALLY INDICATED IN PROJECT DOCUMENTS. EXISTING WIRING SYSTEMS MAY BE UTILIZED ONLY TO THE EXTENT INDICATED IN PROJECT DOCUMENTS, OR AS DIRECTED BY OWNER'S REPRESENTATIVE IN FIELD.
- E. **REASSIGNMENT OF EXISTING CIRCUITS:** IN CASES WHERE EXISTING CIRCUITS ARE REUSED (BASED ON INFORMATION SHOWN ON DRAWINGS OR BASED ON FIELD CONDITIONS) BUT MUST BE CONNECTED TO BREAKERS OTHER THAN THEIR ORIGINAL BREAKER, MODIFY COLOR-CODING AS REQUIRED IF THE NEW BREAKER ASSIGNMENT IS CONNECTED TO A DIFFERENT LINE/PHASE THAN THE ORIGINAL ONE. USE MEANS AND METHODS COMPLIANT WITH NFPA 70 AND WITH AUTHORITIES HAVING JURISDICTION.
- F. **PROTECTIVE BARRIERS:** PROVIDE AND MAINTAIN TEMPORARY PARTITIONS AND DUST BARRIERS ADEQUATE TO PREVENT THE SPREAD OF DUST AND DIRT TO ADJACENT FINISHED AREAS AND OTHER SYSTEM COMPONENTS. PROTECT ADJACENT INSTALLATIONS DURING CUTTING AND PATCHING OPERATIONS. REMOVE PROTECTION AND BARRIERS AFTER DEMOLITION OPERATIONS ARE COMPLETE. PREVENT AIRBORNE DUST AND PARTICULATE MATTER RESULTING FROM ELECTRICAL WORK FROM ENTERING OCCUPIED SPACES, AND FROM ENTERING AIR INTAKES TO OPERATING HVAC SYSTEMS. MEET WITH OWNER AND HVAC INSTALLER TO DETERMINE SPECIAL INDOOR AIR QUALITY (IAQ) REQUIREMENTS RELATED TO ELECTRICAL THAT MAY APPLY TO THIS PROJECT. COOPERATE FULLY WITH HVAC IAQ REQUIREMENTS THAT AFFECT ELECTRICAL WORK AND ARE AFFECTED BY ELECTRICAL WORK.
- G. **PENETRATIONS:** MAKE REQUIRED ELECTRICAL OPENINGS THROUGH WALLS, FLOORS, ETC. IMMEDIATELY PRIOR TO INSTALLATION OF WORK. PROPERLY AND PERMANENTLY SEAL ELECTRICAL OPENINGS IMMEDIATELY AFTER INSTALLATION OF WORK. PROVIDE TEMPORARY SEALS FOR APPLICATIONS WHERE PENETRATIONS ARE MADE BUT CANNOT BE PERMANENTLY SEALED WITHIN FOUR HOURS.
- H. **TEMPORARY LIGHTING AND POWER:** COMPLY WITH NFPA 70 (INCLUDING ARTICLE 590), NFPA 70E AND ALL OTHER PREVAILING CODES. PROVIDE SUFFICIENT LIGHTING AND POWER CENTERS THROUGHOUT INTERIOR OF NEW WORK OR RENOVATION SCOPE. PROVIDE GFCI PROTECTION FOR ALL WORK. COORDINATE WITH GENERAL CONTRACTOR AND OTHER TRADES, AND PROVIDE ANY ADDITIONAL TEMPORARY ELECTRICAL NEEDS THAT ARE REQUIRED. FULLY DEMOLISH TEMPORARY ELECTRIC BY END OF PROJECT. PROVIDE OVERCURRENT PROTECTION, DISCONNECTS, CABLES, CONDUCTORS, RACEWAY, ETC. ACCORDINGLY. PROVIDE TEMPORARY SERVICE FROM UTILITY. ARRANGE WITH LOCAL UTILITY FOR TEMPORARY SERVICE AND PAY ASSOCIATED FEES FOR INSPECTIONS, CONNECTIONS, ETC., AND PAY FOR UTILITY ELECTRIC USAGE/CONSUMPTION COSTS. RESTORE ASSOCIATED SITE AND BUILDING MATERIALS TO THEIR PRE-CONSTRUCTION STATE AND CONDITION AFTER TEMPORARY LIGHTING AND POWER IS NO LONGER NEEDED.

EXISTING CONDITIONS - DEMOLITION NOTES

- A. **DEFINITION OF DEMOLITION:** WHERE THE TERM "DEMOLITION" IS USED IN ELECTRICAL DOCUMENTS, INTERPRET IT TO MEAN "DEMOLITION" OR "SELECTIVE DEMOLITION" AS APPLICABLE FOR THE RESPECTIVE SCOPE OF WORK. WHERE THE TERM "DEMOLISH," "REMOVE" OR SIMILAR TERMS ARE USED IN ELECTRICAL DOCUMENTS, INTERPRET TO MEAN "DISCONNECT, REMOVE, DISPOSE OF, AND REMOVE ALL RELATED ELECTRICAL CONDUIT, RACEWAYS, WIRING, CABLES, BOXES, SUPPORTS, ETC."
- B. **GENERAL ACCOMMODATIONS:** PROVIDE ELECTRICAL DEMOLITION WORK AS REQUIRED TO ACCOMMODATE PROJECT DEMOLITION AND AS REQUIRED TO ACCOMMODATE NEW CONSTRUCTION. DISCONNECT AND REMOVE WORK TO BE ABANDONED, AND AS REQUIRED TO ACCOMMODATE WORK OF OTHER TRADES, IN AREAS AFFECTED BY THIS PROJECT UNLESS SPECIFICALLY NOTED OTHERWISE ON PLANS OR DETERMINED OTHERWISE DURING PRE-DEMOLITION SURVEY. COORDINATE WORK CAREFULLY WITH OWNER PRIOR TO BEGINNING ELECTRICAL DEMOLITION WORK.
- C. **REMOVAL OF ABANDONED WORK:** REMOVE ACCESSIBLE ABANDONED, INACTIVE AND OBSOLETE RACEWAY SYSTEMS, REMOVE ABANDONED, INACTIVE AND OBSOLETE EQUIPMENT, LUMINAIRES, DEVICES, CONDUIT, RACEWAYS, WIRING, CABLES, BOXES, SUPPORTS, CONTROLS, ETC. ABANDONED RACEWAYS EMBEDDED IN FLOORS, WALLS, AND CEILINGS MAY REMAIN IF SUCH MATERIALS DO NOT INTERFERE WITH NEW INSTALLATIONS. THIS APPLIES FOR ALL ELECTRICAL WORK, AND ALL COMMUNICATIONS AND INFORMATION TECHNOLOGY TYPE WORK, INCLUDING ALL SUCH WORK ABOVE CEILINGS, ETC. REMOVE RELATED ABANDONED UNUSED RACEWAY BACK TO THE NEAREST RESPECTIVE "UPSTREAM" JUNCTION BOX THAT REMAINS ACTIVE EVEN IF OUTSIDE OF THE CONFINES OF THE PROJECT AREA. REMOVE ABANDONED UNUSED WIRING AND CABLES BACK TO RESPECTIVE SOURCES SOURCE EVEN IF SOURCES ARE OUTSIDE THE CONFINES OF THE PROJECT AREA.
- D. **RE-USE OF EXISTING CONDUIT:** EXISTING BRANCH CIRCUIT AND SYSTEMS CONDUIT, NOT CONFLICTING WITH NEW CONSTRUCTION AND NOT CONFLICTING WITH OVERHEAD OR CEILING CAVITY REQUIREMENTS, MAY BE RE-USED AT THE DISCRETION OF THE ELECTRICAL INSTALLER AFTER ALL ABANDONED CONDUCTORS AND CABLES HAVE BEEN REMOVED FROM THEM. DO NOT EXCEED NFPA 70 REQUIRED CONDUIT FILL AND DO NOT INSTALL WIRING FED FROM DIFFERENT SOURCES IN COMMON CONDUIT.
- E. **CUTTING AND PATCHING:** PERFORM CUTTING AND PATCHING REQUIRED FOR DEMOLITION, RESTORED TO MATCH SURROUNDING REMAINING SURFACES, INCLUDING FIRE/SMOKE RATINGS.
- F. **DISPOSAL OF MATERIALS:** REFER TO OWNER'S REPRESENTATIVE FOR DISPOSAL INSTRUCTIONS FOR ABANDONED ELECTRICAL MATERIALS REMOVED DURING DEMOLITION AND THEREAFTER. NEATLY STORE ELECTRICAL MATERIALS THAT THE OWNER ELECTS TO RETAIN AT THE SITE AS DESIGNATED BY THE OWNER'S REPRESENTATIVE. LEGALLY DISPOSE OF MATERIALS THAT THE OWNER ELECTS NOT TO RETAIN. DISCONNECT AND REMOVE ELECTRICAL MATERIALS DESIGNATED FOR SALVAGE (REMOVAL AND REUSE, OR FOR TURNING OVER TO OWNER) UNDAMAGED. DISCONNECT AND REMOVE WIRING AND "WHIPS" FROM EQUIPMENT TERMINAL POINTS. CAREFULLY TRANSPORT SALVAGED ELECTRICAL MATERIALS TO A PROTECTED ON-SITE STORAGE LOCATION AS DIRECTED IN FIELD AND NEATLY STORE THEM GROUPED BY SYSTEM TYPE.


SHARONVILLE FIRE STATION 87 RENOVATION

CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241

ELECTRIC DEMOLITION PLAN

SCALE:	1/8" = 1'-0"
HORIZ:	
VERT:	
CONTRACT NO:	170636
SHEET	E-101

11/14/2019 10:21:11 AM



1
EL102
ELECTRIC LIGHTING - FIRST FLOOR
1/4" = 1'-0"

GENERAL LIGHTING PLAN NOTES

- A. EXIT SIGN CONNECTIONS: CONNECT ALL EXIT SIGNAGE AHEAD OF ANY SWITCHING.
B. INDOOR EGRESS LIGHTING: CONNECT ALL INDOOR EGRESS LIGHTING, DESIGNATED "EL", AHEAD OF ANY SWITCHING, UNLESS CONTROL METHODS ARE INDICATED OTHERWISE FOR A GIVEN AREA.
C. OUTDOOR EGRESS LIGHTING: CONNECT ALL OUTDOOR EGRESS LIGHTING AHEAD OF ANY SWITCHING ASIDE FROM PHOTOCELL CONTROL.


KEYED NOTES

- L1 PROVIDE DOOR POSITION INDICATOR LIGHT. PROVIDE POWER FROM DOOR OPERATOR CONTROL CIRCUIT.
L2 CONTROL LIGHTING IN THIS ROOM WITH MANUAL-ON VIA WALL SWITCH, AUTO-OFF VIA CEILING-MOUNTED SENSOR. ADJUST SENSOR SO THAT LIGHTING TURNS OFF WITHIN 30 MINUTES OF ROOM VACANCY.
L3 CONTROL LIGHTING IN THIS ROOM WITH MANUAL-ON, AUTO-OFF VIA WALL-MOUNTED SENSOR. ADJUST SENSOR SO THAT LIGHTING TURNS OFF WITHIN 30 MINUTES OF ROOM VACANCY.
L4 PROVIDE TIMER SWITCH FOR APRON OVERHEAD LIGHTING. REFER TO LIGHTING CONTROL WIRING DIAGRAM FOR MORE INFORMATION.
L5 SUSPEND LIGHTING IN THIS ROOM AT 7'-8" AFF TO BOTTOM OF FIXTURE.

KLH ENGINEERS
MECHANICAL/ELECTRICAL ENGINEERS
WWW.KLHENGRS.COM
1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8050
859-442-8058 FAX
LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK



your trusted advisor
consultants
engineers
architects
planners




REV	DATE	BY	DATE	REVISIONS
0	11/20/2019	CAM	11/20/2019	ISSUE FOR BIDDING AND PERMIT
1	11/20/2019	KLH	11/20/2019	ISSUE FOR BIDDING AND PERMIT
2	11/20/2019	KLH	11/20/2019	ISSUE FOR BIDDING AND PERMIT
3	11/20/2019	KLH	11/20/2019	ISSUE FOR BIDDING AND PERMIT
4	11/20/2019	KLH	11/20/2019	ISSUE FOR BIDDING AND PERMIT
5	11/20/2019	KLH	11/20/2019	ISSUE FOR BIDDING AND PERMIT
6	11/20/2019	KLH	11/20/2019	ISSUE FOR BIDDING AND PERMIT
7	11/20/2019	KLH	11/20/2019	ISSUE FOR BIDDING AND PERMIT
8	11/20/2019	KLH	11/20/2019	ISSUE FOR BIDDING AND PERMIT
9	11/20/2019	KLH	11/20/2019	ISSUE FOR BIDDING AND PERMIT
10	11/20/2019	KLH	11/20/2019	ISSUE FOR BIDDING AND PERMIT
11	11/20/2019	KLH	11/20/2019	ISSUE FOR BIDDING AND PERMIT
12	11/20/2019	KLH	11/20/2019	ISSUE FOR BIDDING AND PERMIT
13	11/20/2019	KLH	11/20/2019	ISSUE FOR BIDDING AND PERMIT
14	11/20/2019	KLH	11/20/2019	ISSUE FOR BIDDING AND PERMIT
15	11/20/2019	KLH	11/20/2019	ISSUE FOR BIDDING AND PERMIT
16	11/20/2019	KLH	11/20/2019	ISSUE FOR BIDDING AND PERMIT
17	11/20/2019	KLH	11/20/2019	ISSUE FOR BIDDING AND PERMIT
18	11/20/2019	KLH	11/20/2019	ISSUE FOR BIDDING AND PERMIT
19	11/20/2019	KLH	11/20/2019	ISSUE FOR BIDDING AND PERMIT
20	11/20/2019	KLH	11/20/2019	ISSUE FOR BIDDING AND PERMIT

SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241
ELECTRIC LIGHTING - FIRST FLOOR

SCALE:	As indicated
HORZ:	
VERT:	
CONTRACT NO:	170636
SHEET	EL102

11/14/2019 10:21:53 AM



1 **ELECTRIC LIGHTING - SECOND FLOOR**
EL103 1/4" = 1'-0"

KEYED NOTES

- L6 PROVIDE PHOTOCELL FOR CONTROL OF EXTERIOR LIGHTING. REFER TO EXTERIOR LIGHTING WIRING DIAGRAM FOR ADDITIONAL INFORMATION.
L8 CONTROL STAIRWAY LIGHTING TO BE AUTO-ON, AUTO-DIM TO 50% OF FULL OUTPUT AFTER 15 MINUTES OF INACTIVITY.

KLH ENGINEERS
MECHANICAL/ELECTRICAL ENGINEERS
WWW.KLHENGERS.COM
1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8050
859-442-8058 FAX
LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK




your trusted advisor
**engineers
architects
planners
consultants**

REV	DATE	BY	REVISIONS
0	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
1	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
2	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
3	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
4	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
5	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
6	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
7	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
8	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
9	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
10	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
11	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
12	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
13	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
14	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
15	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
16	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
17	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
18	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
19	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
20	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
21	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
22	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
23	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
24	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
25	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
26	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
27	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
28	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
29	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
30	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
31	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
32	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
33	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
34	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
35	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
36	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
37	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
38	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
39	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
40	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
41	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
42	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
43	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
44	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
45	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
46	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
47	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
48	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
49	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
50	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
51	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
52	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
53	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
54	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
55	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
56	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
57	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
58	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
59	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
60	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
61	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
62	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
63	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
64	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
65	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
66	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
67	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
68	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
69	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
70	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
71	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
72	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
73	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
74	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
75	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
76	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
77	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
78	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
79	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
80	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
81	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
82	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
83	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
84	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
85	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
86	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
87	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
88	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
89	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
90	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
91	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
92	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
93	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
94	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
95	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
96	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
97	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
98	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
99	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT
100	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT

SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241
ELECTRIC LIGHTING - SECOND FLOOR

SCALE: 1/4" = 1'-0"
HORIZ:
VERT:
CONTRACT NO:
170636
SHEET
EL103




265100.00-05 - EXTERIOR LIGHTING CONTROL WIRING DIAGRAM

SCALE: NONE

KEYED NOTES:

1. PROVIDE 1" MINIMUM SCHEDULE 40 ELECTRICAL PVC CONDUIT. BACKFILL WITH EXCAVATED OR BORROWED MATERIAL. MATERIAL SHALL BE FREE OF ROCKS 1" DIAMETER AND LARGER. COMPACT TO 90% IN MAX 8" LIFTS OF LOOSE SOIL.
2. PROVIDE 3000# CONCRETE BASE (CLASS A FORMED SURFACE WHERE EXPOSED).
3. INSTALL ACCORDING TO LUMINAIRE MANUFACTURER'S INSTRUCTIONS. PROVIDE STANCHION THAT IS SUITABLE FOR INSTALLATION IN CONCRETE AND EMBED IN CONCRETE BASE. IF SURFACE STANCHION IS UTILIZED, IT SHALL BE VERY SHORT SO THAT MAXIMUM HEIGHT INDICATED IS NOT EXCEEDED. PROVIDE FINISHED STANCHION THAT MATCHES LUMINAIRE FINISH. PROVIDE STAINLESS STEEL HARDWARE AND WATER-TIGHT GASKETED COVERS/SEALS.
4. FOR BASES FLUSH WITH PAVEMENT, DO NOT PROVIDE CHAMFER. SEAL THE PERIMETER OF THE BASE TOP INSTEAD.
5. PROVIDE 24" MINIMUM RADIUS. PROVIDE NUMBER OF CONDUITS AS NEEDED. PROVIDE CONDUIT(S) SIZED SO THAT THEY FIT EASILY WITHIN THE STANCHION. ONE HALF INCH CONDUIT MAY BE USED WITHIN STANCHION IF NEEDED TO ENSURE PROPER FIT.
6. PROVIDE CYLINDRICAL MESH CAGE STARTING AT 3" FROM BOTTOM OF BASE AND ENDING 3" FROM TOP OF BASE.
7. PROVIDE ROUND CONCRETE BASE.
8. PROVIDE FINAL AIMING AT NIGHT IN PRESENCE OF OWNER'S REPRESENTATIVE.



BASE DIMENSIONS		
LUMINAIRE TYPE	"X"	"Y"
GAZ	0"	18"


SECTION VIEW PLAN VIEW

265100.00-02 - ABOVE GRADE LIGHTING - POINT SOURCE

SCALE: NONE

KEYED NOTES:

1. PROVIDE 1" MINIMUM SCHEDULE 40 ELECTRICAL PVC CONDUIT. BACKFILL WITH EXCAVATED OR BORROWED MATERIAL. MATERIAL SHALL BE FREE OF ROCKS 1" DIAMETER AND LARGER. COMPACT TO 90% IN MAX 8" LIFTS OF LOOSE SOIL.
2. PROVIDE 3000# CONCRETE BASE (CLASS A FORMED SURFACE WHERE EXPOSED).
3. INSTALL ACCORDING TO LUMINAIRE MANUFACTURER'S INSTRUCTIONS. IF SURFACE OUTLET BOX IS UTILIZED, PROVIDE FINISHED COMPONENTS THAT MATCH PENDANT AND LUMINAIRE FINISH, AND THAT ARE SUITABLE FOR EXTERIOR FACE-UP INSTALLATION DIRECTLY ON CONCRETE. IF RECESSED OUTLET BOX IS UTILIZED, PROVIDE MATERIALS SUITABLE FOR BEING EMBEDDED IN CONCRETE. PROVIDE STAINLESS STEEL HARDWARE AND WATER-TIGHT GASKETED COVERS/SEALS.
4. FOR BASES FLUSH WITH PAVEMENT, DO NOT PROVIDE CHAMFER. SEAL THE PERIMETER OF THE BASE TOP INSTEAD.
5. PROVIDE 24" MINIMUM RADIUS. PROVIDE NUMBER OF CONDUITS AS NEEDED, 1" MINIMUM.
6. PROVIDE CYLINDRICAL MESH CAGE STARTING AT 3" FROM BOTTOM OF BASE AND ENDING 3" FROM TOP OF BASE.
7. PROVIDE ROUND CONCRETE BASE. PROVIDE ONE BASE FOR EACH LUMINAIRE HUB SUPPORT, REGARDLESS OF POWER FEED LOCATION. CONDUIT IS NOT REQUIRED FOR BASES THAT ARE PROVIDED FOR SUPPORT ONLY.
8. PROVIDE FINAL AIMING AT NIGHT IN PRESENCE OF OWNER'S REPRESENTATIVE.
9. PEDESTAL MOUNT.



BASE DIMENSIONS		
LUMINAIRE TYPE	"X"	"Y"
SL1	0"	18"

SECTION VIEW PLAN VIEW

265100.00-01 - SIGN LIGHTING - LINEAR SOURCE

SCALE: NONE

ELECTRIC LUMINAIRE SCHEDULE

TYPE	DESCRIPTION	MANUFACTURER / SERIES	SIZE	HOUSING / MOUNTING	MATERIAL	LENS DESCRIPTION	LAMP QTY	LAMP TYPE	LAMP BASE	BALLAST / DRIVER QTY	BALLAST / DRIVER	FINISH	COMMENTS	FIXTURE LOAD	VOLTAGE
A	LED FLAT PANEL	LITHONIA EPANL DAY-BRITE 2FX2 COLUMBIA CFP22 METALUX 22FP	2'x2'x2"	RECESSED	STEEL	SATIN WHITE FLAT LUMINOUS ACRYLIC LENS	1	LED, 3500K, 80 CRI	3400 NOMINAL LUMENS	1	ELECTRONIC DRIVER, 120V-277V, 0-10V DIMMING	WHITE		33 VA	120 V
AB4	AREA LIGHTING LUMINAIRE	LITHONIA RADPT LED OR APPROVED EQUAL	24" DIAx26"	EXISTING POLE, ADJUSTABLE TENON SLIPFITTER	ALUMINUM	TYPE IV WIDE OPTIC	1	LED, 4000K, 70 CRI	11000 NOMINAL LUMENS	1	ELECTRONIC DRIVER	SILVER, MATCH EXISTING	WET LISTED; VERIFY OUTSIDE DIMENSION OF TOP OF POLE IN FIELD, PROVIDE ADAPTER TO MATCH	86 VA	120 V
AB5	AREA LIGHTING LUMINAIRE	LITHONIA RADPT LED OR APPROVED EQUAL	24" DIAx26"	EXISTING POLE, ADJUSTABLE TENON SLIPFITTER	ALUMINUM	TYPE V WIDE OPTIC	1	LED, 4000K, 70 CRI	11000 NOMINAL LUMENS	1	ELECTRONIC DRIVER	SILVER, MATCH EXISTING	WET LISTED; VERIFY OUTSIDE DIMENSION OF TOP OF POLE IN FIELD, PROVIDE ADAPTER TO MATCH	86 VA	120 V
D6	LED PERFORATED FRONT WALL BRACKET	FINELITE S17LED VCF PRUDENTIAL WALL-LED H.E. WILLIAMS WMAUD LITECONTROL 67L-W-D AXIS PWMLED	5'x4'x4"	SURFACE WALL	STEEL	PERFORATED METAL DIFFUSER, TOP AND BOTTOM FROSTED ACRYLIC DIFFUSER	1	LED, 3500K, 80 CRI	3000 NOMINAL LUMENS	1	ELECTRONIC DRIVER	WHITE		36 VA	120 V
DD	LED WALL MOUNT CUTOFF	GARCOO 101L LITHONIA WST H.E. WILLIAMS WPTZ HUBBELL TRP MCGRAW-EDISON IST	16-3/8"x9"x7-1/4"	SURFACE	ALUMINUM	CLEAR FLAT TEMPERED GLASS LENS, MEDIUM THROW OPTIC	1	LED, 4000K, 70 CRI	6000 NOMINAL LUMENS	1	ELECTRONIC INTEGRAL DRIVER, 120V-277V	WHITE	WET LISTED, PROVIDE FIXTURE WITH INTEGRAL PHOTOCELL CONTROL	50 VA	120 V
DDB	LED WALL MOUNT CUTOFF - BATTERY	GARCOO 101L LITHONIA WST H.E. WILLIAMS WPTZ HUBBELL TRP MCGRAW-EDISON IST	16-3/8"x9"x7-1/4"	SURFACE WALL	ALUMINUM	CLEAR FLAT TEMPERED GLASS LENS, MEDIUM THROW OPTIC	1	LED, 4000K, 70 CRI	2700 NOMINAL LUMENS	1	ELECTRONIC INTEGRAL DRIVER, 120V-277V	WHITE	WET LISTED, PROVIDE FIXTURE WITH INTEGRAL PHOTOCELL CONTROL, INTEGRAL 1100 LUMEN EMERGENCY BATTERY PACK RATED FOR 2 HOUR OPERATION	28 VA	120 V
ELU	EMERGENCY LIGHTING UNIT - THERMOPLASTIC	LITHONIA ELM6 LED EMER-LITE EL-2 DUAL-LITE EV SURE-LITES LEM2	11-3/4"x7-1/2"x4"	WALL	THERMOPLASTIC		2	3W LED, WITH UNIT, 270 NOMINAL LUMENS		0	NO BALLAST	WHITE	6V UNIT, SEALED LEAD ACID BATTERY OPERATION, 9W OUTPUT REMOTE CAPABILITY, UL924 COMPLIANT	6 VA	120 V
EXM	EXIT/EMERGENCY LIGHTING UNIT COMBO	LITHONIA LHQM LED DUAL-LITE EV CVC SURELITES APC7	21"x10"x4"	UNIVERSAL	THERMOPLASTIC	STENCIL FACE	2	1.5W LED, WITH UNIT		0	NO BALLAST	WHITE	EXIT SIGNAGE COLOR TO BE BASED ON OWNER PREFERENCE OR EXISTING CONDITIONS, 6V UNIT, 3W OUTPUT LEAD CALCIUM BATTERY OPERATION	3 VA	120 V
F8	RECESSED LED LINEAR	LITECONTROL 4L-R-D NULITE R64 FINELITE HP-4	4'x8'x4"	RECESSED, GYP. BD. CEILING	STEEL	SATIN WHITE FLAT LUMINOUS ACRYLIC LENS	1	LED, 3500K, 80 CRI, 3.4W/FT	3200 NOMINAL LUMENS	1	ELECTRONIC DRIVER, 120V-277V, 0-10V DIMMING	WHITE		29 VA	120 V
GAZ	ARCHITECTURAL LED FLAG POLE SPOT LIGHT	FC LIGHTING FCF1105 OR APPROVED EQUAL	5-1/2"x5" x 8-1/2" x 12" OAH	HEAVY DUTY GROUND STAKE, REFER TO MOUNTING DETAIL	ALUMINUM	CLEAR TEMPERED GLASS LENS, 15" SPOT OPTIC	1	LED, 4000K	2000 NOMINAL LUMENS	1	ELECTRONIC DRIVER	BRONZE	WET LISTED, PROVIDE UPPER VISOR, SINGLE-FUSE, PROVIDED WITH 1/2" NPT MOUNTING STEM	21 VA	120 V
K	LED ENCLOSED NON-METALLIC INDUSTRIAL	LITHONIA FEM COLUMBIA LKEM DAY-BRITE DWA METALUX VT2	6'x4'x4-1/8"	SURFACE OR CHAIN	FIBERGLASS	GASKETED ACRYLIC LINEAL FROSTED DIFFUSER	1	LED, 3500K, 80 CRI	4000 NOMINAL LUMENS	1	ELECTRONIC DRIVER	WHITE	IP67 RATING	31 VA	120 V
L14	LED SPECIFICATION STRIP	LITHONIA ZL10 DAY-BRITE FSS COLUMBIA MPS METALUX SNLED	2'x4'x2-7/8"	SURFACE OR CHAIN	STEEL	ACRYLIC DIFFUSE LENS	1	LED, 3500K, 80 CRI	3000 NOMINAL LUMENS	1	ELECTRONIC DRIVER, 120V-277V, 0-10V DIMMING	WHITE		20 VA	120 V
LE	EXTERIOR LED STRIP	ALIGHTS G2 OR APPROVED EQUAL	5'x4'x5"	SURFACE, CANOPY	STEEL	ACRYLIC DIFFUSE LENS, SYMMETRIC DISTRIBUTION	1	LED, 4000K, 80 CRI	1700 NOMINAL LUMENS	1	ELECTRONIC DRIVER	WHITE	WET LISTED, PROVIDE INTEGRAL EMERGENCY BATTERY BACKUP	20 VA	120 V
PS1	RED LED NOTIFICATION LIGHT	LUMENPULSE LMDM BRUOK 135341 PHOENIX CL	6-3/4"x7-1/4"	SURFACE	ALUMINUM	FLAT POLYCARBONATE LENS	1	LED, STATIC RED LED	1000 NOMINAL LUMENS	1	ELECTRONIC, REMOTE DRIVER TO BE ABOVE ACCESSIBLE CEILING	WHITE	FIELD REPLACABLE LED MODULE AND DRIVER	14 VA	120 V
PS3	RED LED STRIP	SSL CVLWET LUMENPULSE LOGP CALI ALS450T	2'x4'x3"	SUSPENDED	STEEL	POLYCARBONATE DIFFUSE LENS, MEDIUM DISTRIBUTION	1	LED, STATIC RED	1600 NOMINAL LUMENS	1	ELECTRONIC INTEGRAL DRIVER, 120V-277V	WHITE	MOUNTING AS INDICATED ON PLANS, IP66 RATING, PROVIDE LUMINAIRE SAFETY CABLE, WET LISTED	22 VA	120 V
PS4	RED LED NOTIFICATION LIGHT	LUMENPULSE LMDM BRUOK 135341 PHOENIX CL	6-3/4"x7-1/4"	SURFACE WALL, AT 9'4" A.F.G.	ALUMINUM	FLAT POLYCARBONATE LENS	1	LED, STATIC RED LED	100 NOMINAL LUMENS	1	ELECTRONIC, REMOTE DRIVER TO BE ABOVE ACCESSIBLE CEILING	WHITE	WET LISTED	14 VA	120 V
SL1	LINEAR LED SIGN LIGHT	LUMENPULSE LOG HO OR APPROVED EQUAL	5'x4'x4"	UNIVERSAL ADJUSTABLE MOUNT, REFER TO DETAIL	ALUMINUM	CLEAR ACRYLIC LENS, ANODIZED ALUMINUM REFLECTOR, 30x60 DEGREE OPTIC	1	LED, 4000K, 80 CRI	3800 NOMINAL LUMENS	1	ELECTRONIC DRIVER	BRONZE	WET LISTED	61 VA	120 V
TL	EXTERIOR LED TAPE LIGHT	ACOLYTE RB OR APPROVED EQUAL	3/4"X LENGTH AS SHOWN ON PLAN	SURFACE	EXTRUDED ALUMINUM CHANNEL	CLEAR ACRYLIC LENS	1	LED, 4000K, 80 CRI, 300 LUMENS PER FOOT	125 LUMENS PER FOOT	0	PER MANUFACTURER'S RECOMMENDATIONS	WHITE	IP68, PROVIDE ALL REQUIRED CORDS, TERMINATIONS, AND ACCESSORIES REQUIRED FOR A FULLY FUNCTIONAL INSTALLATION. VERIFY LENGTH AND INSTALLATION WITH ARCHITECTURAL DRAWINGS	35 VA	120 V
X4	ENCLOSED AND GASKETED LED - APPARATUS BAY	LITHONIA FEM4 COLUMBIA LKEM4 METALUX 4VT2 LED DAYBRITE V2WA	7'x52"x6"	SUSPENDED	FIBERGLASS	CLEAR SPECULAR REFLECTOR, MEDIUM DISTRIBUTION, NO UPLIGHT, FROSTED ACRYLIC LENS	1	LED, 3500K, 80 CRI	10000 NOMINAL LUMENS	1	ELECTRONIC INTEGRAL DRIVER, 120V-277V	WHITE	PROVIDE LUMINAIRE SAFETY CABLE, WET LISTED, IP66 AND IP67 RATING	92 VA	120 V
Y1	ENCLOSED GLOBE & GUARD - LED	LITHONIA QLV1WM HUBBELL VWGL-1 CANLET LEDVP	4-9/16"x7-7/16"x11-5/16"	SURFACE WALL	ALUMINUM	ENCLOSED TEMPERED FROSTED GLASS GLOBE, CAST ALUMINUM HOOD & GUARD	1	LED, 4000K, 74 CRI	600 NOMINAL LUMEN	1	ELECTRONIC DRIVER	GRAY	WET LISTED	15 VA	120 V
Z1	LED DOWNLIGHT	LITHONIA WF4 OR APPROVED EQUAL	4" DIAx1'x5-1/2"	RECESSED	ALUMINUM	POLYCARBONATE LENS, MEDIUM DOWNLIGHT OPTIC	1	LED, 3500K, 80 CRI	675 NOMINAL LUMENS	1	ELECTRONIC DRIVER, 120V-277V, 0-10V DIMMING	MATTE WHITE		9 VA	120 V
Z4	LED SHOWER LIGHT	GOTHAM EVO HALO COMMERCIAL HC6 LIGHTOLIER C8P PRESCOLITE LP6	6" DIAx14-1/2"x5-5/8"	RECESSED	STEEL	FLAT CLEAR POLYMER LENS, WHITE SPLAY	1	LED, 3500K, 80 CRI	1000 NOMINAL LUMENS	1	ELECTRONIC DRIVER	WHITE POLYCARBONATE NON-CONDUCTIVE TRIM	WET LISTED	12 VA	120 V
Z7	SQUARE LED DOWNLIGHT	JUNO ICJLB-JFSQ OR APPROVED EQUAL	7"x7"x3/4"	SURFACE, JUNCTION BOX, IC RATED	ALUMINUM	SEMI-SPECULAR REFLECTOR, MEDIUM DOWNLIGHT OPTIC	1	LED, 4000K, 80 CRI	1000 NOMINAL LUMENS	1	ELECTRONIC DRIVER	WHITE	WET LISTED; FIELD REPLACABLE LED, MODULE, AND DRIVER	13 VA	120 V

Interior Lighting Compliance Certificate

2012 IECC Section 1: Project Information

Project Type: Alterations

Section 2: Interior Lighting and Power Calculation

Floor Area (sq. ft.)	Watts per sq. ft.	Allowed Watts	Proposed Watts	Complies
8440 sq. ft.	0.8 (Fire Station)	6752 W	See Below	Yes

Section 3: Interior Lighting Fixture Schedule

TYPE	LAMP TYPE	BALLAST / DRIVER	LAMP QTY	COUNT	LOAD	TOTAL LOAD
A	LED, 3500K, 80 CRI	ELECTRONIC DRIVER, 120V-277V, 0-10V DIMMING	1	60	33 VA	1980 VA
D6	LED, 3500K, 80 CRI	ELECTRONIC DRIVER	1	4	36 VA	144 VA
F8	LED, 3500K, 80 CRI, 3.4W/FT	ELECTRONIC DRIVER, 120V-277V, 0-10V DIMMING	1	4	29 VA	116 VA
K	LED, 3500K, 80 CRI	ELECTRONIC DRIVER	1	14	31 VA	434 VA
L14	LED, 3500K, 80 CRI	ELECTRONIC DRIVER, 120V-277V, 0-10V DIMMING	1	18	20 VA	360 VA
PS3	LED, STATIC RED	ELECTRONIC INTEGRAL DRIVER, 120V-277V	1	7	22 VA	154 VA
X4	LED, 3500K, 80 CRI	ELECTRONIC INTEGRAL DRIVER, 120V-277V	1	13	92 VA	1196 VA
Y1	LED, 4000K, 74 CRI	ELECTRONIC DRIVER	1	10	15 VA	150 VA
Z1	LED, 3500K, 80 CRI	ELECTRONIC DRIVER, 120V-277V, 0-10V DIMMING	1	10	9 VA	90 VA
Z4	LED, 3500K, 80 CRI	ELECTRONIC DRIVER	1	13	12 VA	156 VA
Z7	LED, 4000K, 80 CRI	ELECTRONIC DRIVER	1	8	13 VA	104 VA
						4884 VA

Exterior Lighting Compliance Certificate

2012 IECC Section 1: Project Information

Project Type: Alterations

Exterior Lighting Zone: Neighborhood Business District

Section 2: Exterior Lighting Area/Surface Power Calculation

Exterior Area/Surface	Quantity	Allowed Watts / Unit	Tradable Watts	Allowed Supplemental Watts	Proposed Watts	Complies
Parking Area	11,000 SF	0.06 W/SF	Yes	660 W	See Below	Yes
Front Apron	1,500 SF	0.06 W/SF	Yes	90 W		
Entry Canopy	250 SF	0.25 W/SF	Yes	62.5 W		
				812 W		

Section 3: Exterior Lighting Fixture Schedule

TYPE	LAMP TYPE	BALLAST / DRIVER	LAMP QTY	COUNT	LOAD	TOTAL LOAD
AB4	LED, 4000K, 70 CRI	ELECTRONIC DRIVER	1	1	86 VA	86 VA
AB5	LED, 4000K, 70 CRI	ELECTRONIC DRIVER	1	1	86 VA	86 VA
DD	LED, 4000K, 70 CRI	ELECTRONIC INTEGRAL DRIVER, 120V-277V	1	3	50 VA	150 VA
DDB	LED, 4000K, 70 CRI	ELECTRONIC INTEGRAL DRIVER, 120V-277V	1	2	28 VA	84 VA
GAZ	LED, 4000K	ELECTRONIC DRIVER	1	2	21 VA	42 VA
LE	LED, 4000K, 80 CRI	ELECTRONIC DRIVER	1	3	20 VA	60 VA
SL1	LED, 4000K, 80 CRI	ELECTRONIC DRIVER	1	4	61 VA	244 VA
TL	LED, 4000K, 80 CRI, 300 LUMENS PER FOOT	PER MANUFACTURER'S RECOMMENDATIONS	1	1	35 VA	35 VA
						787 VA

KLH ENGINEERS
MECHANICAL/ELECTRICAL ENGINEERS
WWW.KLHENGRS.COM
1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075
800-354-0793
859-442-8050
859-442-8058 FAX
LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK



GENERAL NOTES

- REFER TO DRAWINGS FOR MOUNTING TYPE, NUMBER OF FACES AND ARROWS OF EXIT SIGNS. VERIFY IN FIELD PRIOR TO INSTALLATION.
- VERIFY COMPATIBILITY WITH VOLTAGE, CONTROLS, ETC. FOR ALL LUMINAIRE COMPONENTS
- COORDINATE EACH LUMINAIRE LOCATION WITH THE ARCHITECTURAL REFLECTED CEILING PLAN(S), CEILING INSTALLERS, ETC. AND PROVIDE APPROPRIATE MOUNTING SYSTEM REQUIRED FOR EACH LUMINAIRE. ALSO, PROVIDE PLASTER FRAMES, WALL BRACKETS, SUPPORTS, OR OTHER APPURTENANCES AS REQUIRED FOR PROPER AND COMPLETE INSTALLATIONS
- WEAR CLEAN WHITE COTTON GLOVES WHEN HANDLING EXPOSED REFLECTIVE LUMINAIRE SURFACES. REMOVE PLASTIC SHIPPING BAGS ONLY AFTER INTERIOR WORK IS COMPLETE, AND CLEAN ALL SURFACES WITH CLEAN DRY CHEESE CLOTH
- MOUNTING HEIGHTS INDICATED ARE TO THE BOTTOM OF THE LUMINAIRE, UNLESS OTHERWISE NOTED.
- PRODUCTS: PROVIDE PRODUCTS INDICATED ON DRAWINGS AND SCHEDULES. WHERE MULTIPLE MANUFACTURER SERIES/MODEL NUMBERS ARE LISTED FOR A SINGLE LUMINAIRE, PROVIDE ONE OF THOSE LISTED. WHERE A SPECIFIC MANUFACTURER SERIES/MODEL NUMBER IS LISTED AS BASIS-OF-DESIGN, AND WHERE IT IS STATED THAT EQUIVALENTS WILL BE CONSIDERED, ANY PROPOSED NON-LISTED LUMINAIRES ARE SUBJECT TO REVIEW BY DESIGN PROFESSIONAL(S). SUBMITTALS FOR WHICH SHALL BE FURNISHED AT LEAST (10) DAYS PRIOR TO BID DUE DATE OR THEY WILL NOT BE CONSIDERED. THESE PRE-BID SUBMITTALS SHALL CLEARLY STATE EXACTLY WHAT IS BEING PROPOSED AND SHALL DEMONSTRATE COMPLIANT EQUIVALENCY. SIMILAR REQUESTS FOR PROPOSED SUBSTITUTIONS MAY BE MADE ONLY AFTER BIDS ARE RECEIVED, AND ONLY IF OWNER CHOOSES TO CONSIDER SUBSTITUTION REQUESTS. DESIGN PROFESSIONAL(S) AND OWNER RESERVE THE RIGHT TO REJECT ALL PRODUCTS THAT ARE NOT DEEMED TO BE FULLY EQUIVALENT TO THE BASIS-OF-DESIGN LISTING(S). SUBMIT ALL REQUESTS AND QUESTIONS THROUGH THE FORMALLY-ESTABLISHED BIDDING PROCESS, NOT DIRECTLY TO ENGINEER.


ELECTRIC INVERTER SCHEDULE

Provide UL924 listed inverters / battery backup for emergency egress as specified below and per specifications. See floor plans for individual luminaires to be connected to each inverter. Luminaires are labeled with "IN". Coordinate final inverter sizes with final luminaire selection and maximum inverter loading requirements prior to purchase / rough in. Where a luminaire on an inverter is specified to be controlled / dimmed, provide UL924 control bypass devices to force luminaires to 100% on when power is lost. Mount inverters in an easily accessible location. Coordinate final inverter locations in field.

INVERTER ID	125% LOAD	PANEL	CIRCUIT	VOLTAGE	INVERTER SIZE
INV1	193 VA	OSL1A	13	120 V	250 VA
INV2	248 VA	OSL2A	23	120 V	250 VA

SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241
ELECTRIC LIGHTING - LUMINAIRE SCHEDULE
SCALE: 1/8" = 1'-0"
HORIZ:
VERT:
CONTRACT NO: 170636
SHEET EL601
KLH JOB#: 21459.00

11/14/2019 10:22:11 AM



1 **ELECTRIC POWER - FIRST FLOOR**
EP102 1/4" = 1'-0"

KEYED NOTES

- E1 PROVIDE (2) TOTAL CONTROL STATIONS FOR EACH OVERHEAD DOOR, AND PROVIDE (1) MASTER CONTROL STATIONS TO OPEN ALL DOORS SIMULTANEOUSLY. INSTALL AND WIRE 3-BUTTON OVERHEAD DOOR CONTROL STATIONS AT LOCATION AS DIRECTED BY OWNER IN FIELD. COORDINATE WITH OVERHEAD DOOR INSTALLER PRIOR TO ROUGH-IN.
- E2 THIS EQUIPMENT RECEIVES POWER FROM ANOTHER. PROVIDE ALL POWER AND CONTROL WIRING BETWEEN EQUIPMENT AS REQUIRED BY THE MANUFACTURER. REFER TO EQUIPMENT COORDINATION SCHEDULES FOR MORE INFORMATION.
- E3 INTERLOCK THE EXHAUST FAN OPERATION WITH THE OCCUPANCY SENSORS CONTROLLING THE LIGHTING IN THE ROOM(S) THE EXHAUST FAN SERVES. REFER TO MECHANICAL DRAWINGS FOR WHICH ROOM(S) APPLY.
- E7 EQUIPMENT TO BE PROVIDED BY OWNER. PROVIDE BREAKER, WIRING, AND DISCONNECT TO MATCH EQUIPMENT VOLTAGE AND LOAD. COORDINATE POWER REQUIREMENTS PRIOR TO ROUGH-IN.

KLH ENGINEERS
MECHANICAL/ELECTRICAL ENGINEERS
WWW.KLHENGRS.COM
1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8050
859-442-8058 FAX
LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK




your trusted advisor
engineers
architects
consultants
planners

REV	DATE	BY	REVISIONS
0	11/20/2019	CAM	ISSUE FOR BIDDING AND PERMIT

SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241
ELECTRIC POWER - FIRST FLOOR

SCALE: 1/4" = 1'-0"
HORIZ:
VERT:
CONTRACT NO:
170636
SHEET
EP102

11/14/2019 10:22:21 AM



1 **ELECTRIC POWER - SECOND FLOOR**
EP103 1/4" = 1'-0"

KEYED NOTES

E3 INTERLOCK THE EXHAUST FAN OPERATION WITH THE OCCUPANCY SENSORS CONTROLLING THE LIGHTING IN THE ROOM(S) THE EXHAUST FAN SERVES. REFER TO MECHANICAL DRAWINGS FOR WHICH ROOM(S) APPLY.

KLH ENGINEERS
MECHANICAL/ELECTRICAL ENGINEERS
WWW.KLHENGERS.COM
1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8050
859-442-8058 FAX
LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK




your trusted advisor
consultants
engineers
architects
planners

REV	DATE	REVISIONS	BY
0	11/20/2019	ISSUE FOR BIDDING AND PERMIT	CAM

SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241
ELECTRIC POWER - SECOND FLOOR

SCALE:	1/4" = 1'-0"
HORIZ:	
VERT:	
CONTRACT NO:	170636
SHEET	EP103

11/14/2019 10:22:27 AM



KLH ENGINEERS
MECHANICAL/ELECTRICAL ENGINEERS
WWW.KLHENGERS.COM

1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8050
859-442-8058 FAX

LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK



your trusted advisor
consultants

engineers
architects
planners


REV	REVISIONS	DATE	BY
0	ISSUE FOR BIDDING AND PERMIT	11/20/2019	CAM
1			
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			
13			
14			
15			
16			
17			
18			
19			
20			

DATE:	11/20/2019
DRAWN BY:	DCL
CHECKED BY:	PAL
APPROVED BY:	
F.B. NO.	
P.G.	

SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241


ELECTRIC POWER - ROOF

SCALE: 1/4" = 1'-0"
HORIZ:
VERT:
CONTRACT NO:
170636
SHEET
EP104




260590.00-03 - OVERHEAD DOOR STATUS LIGHT SCHEMATIC

SCALE: NONE



260580.00-03 - DHW W.D.

SCALE: NONE



260580.00-06 - KITCHEN HOOD WIRING DIAGRAM

SCALE: NONE

GENERAL NOTES:


- PROVIDE WIRING AND CONNECTION WORK ASSOCIATED WITH ELECTRICALLY OPERATED GAS SOLENOID SHUT-OFF VALVE(S) FOR GAS LINES THAT SERVE COOKING EQUIPMENT. PROVIDE INTERLOCK CONTROL WIRING BETWEEN THE SHUT-OFF VALVE AND THE KITCHEN HOOD FIRE SUPPRESSION SYSTEM AS DIRECTED IN FIELD BY HOOD FIRE SUPPRESSION SYSTEM INSTALLER. CONFIGURE CONTROLS SO THAT LOSS OF POWER RESULTS IN FAIL-SAFE CONDITIONS (GAS VALVE(S) OPEN, EQUIPMENT MOTORS OFF, ETC.).
- PROVIDE POWER WIRING TO INDOOR HOOD BODIES AND FIRE SUPPRESSION SYSTEMS FOR HOOD LIGHTS AND CONTROL CIRCUITS.
- PROVIDE POWER AND CONTROL WIRING FROM INDOOR HOOD BODIES TO RESPECTIVE FAN UNITS AND FROM FAN UNITS TO REMOTE DUCT-STATS.
- PROVIDE CONTROL WIRING TO AND FROM DUCT HEAT SENSORS.
- PROVIDE POWER AND CONTROL WIRING FROM INDOOR HOOD BODIES TO CONTACTS ON FACTORY MICRO-SWITCH IN RESPECTIVE HOOD FIRE SUPPRESSION SYSTEM, AND TO THE CONTACTOR (OR SHUNT TRIP AS APPLICABLE) CONTROL CIRCUIT.
- PROVIDE CONTROL WIRING FROM THE MICRO-SWITCH IN THE HOOD FIRE SUPPRESSION SYSTEMS TO RESPECTIVE DEDICATED FIRE ALARM SYSTEM ADDRESSABLE MONITOR MODULES TO INITIATE ALARM SIGNAL WHEN RESPECTIVE HOOD FIRE PROTECTION SYSTEM IS ACTIVATED.
- INSTALL AND WIRE DUCT-STAT(S) AND HEAT SENSOR(S), WHICH WILL BE FURNISHED BY HOOD MANUFACTURER (SHIPPED LOOSE).
- INSTALL AND WIRE HOOD FAN SWITCH AND HOOD LIGHTING SWITCH, WHICH WILL BE FURNISHED BY HOOD MANUFACTURER (SHIPPED LOOSE).
- IN AUTOMATIC MODE THE HEAT SENSOR SHALL DETECT HEAT FROM FOOD PREPARATION EQUIPMENT BELOW, AND SHALL AUTOMATICALLY ENERGIZE THE RESPECTIVE KITCHEN HOOD EXHAUST FAN IN THE EVENT THAT THE FAN IS NOT ALREADY OPERATING FROM HAVING BEEN TURNED ON MANUALLY AT THE HOOD.
- PROVIDE SHUNT TRIP OR CONTACTOR CONTROL FOR AUTOMATIC SHUT-OFF FOR ALL ELECTRICALLY OPERATED OR CONTROLLED EQUIPMENT BENEATH THE HOOD UPON ACTIVATION OF THE HOOD FIRE SUPPRESSION SYSTEM.
- PROVIDE EMPTY OCTAGON BOX FOR MECHANICAL MANUAL PULL STATION (AND INSTALL PULL STATION) FOR EACH HOOD FIRE PROTECTION SYSTEM (MOUNTED AT 48" TO TOP OF OUTLET BOX ABOVE FINISHED FLOOR) WITH (1) 1/2" EMPTY CONDUIT ROUTED UP AND OVER TO HOOD AS DIRECTED IN FIELD BY HOOD INSTALLER (WITH SWEEP 90°). INSTALL PULL STATION NEAR MEANS OF EGRESS, BETWEEN 10 AND 20 FEET FROM THE COOKING AREA. DETERMINE LOCATIONS IN FIELD.
- FURNISH, INSTALL & WIRE ALL REQUIRED POWER WIRING, CONTROL AND INTERLOCK WIRING, CONNECTIONS, CONTACTORS, ETC. AS REQUIRED FOR COMPLETE OPERATIONAL HOOD AND ANCILLARY SYSTEMS. THIS DETAIL IS SCHEMATIC IN NATURE. FIELD VERIFY ALL SPECIFICS WITH RESPECTIVE INSTALLERS AND PROVIDE ALL NECESSARY WORK AS REQUIRED TO RENDER THE SYSTEM AND SEQUENCING FULLY OPERABLE. REFER TO FOOD SERVICE DOCUMENTS AND SUBMITTALS FOR MORE SPECIFIC INFORMATION, AND PROVIDE ALL ELECTRICAL WORK ACCORDINGLY. NOTE THAT MULTIPLE HOODS MAY EXIST, AND ANY SHOWN HOOD MAY CONSIST OF MULTIPLE SECTIONS.

KEYED NOTES:

- PROVIDE TRENCH IN UNDISTURBED OR ENGINEERED COMPACTED SOIL AS APPLICABLE.
- PROVIDE 3" WIDE DETECTABLE CAUTION TAPE 8" BELOW FINISHED SURFACE.
- PROVIDE FLOWABLE BACKFILL. BACKFILL USING EXCAVATED OR BORROWED MATERIAL, FREE OF ROCKS 1" DIAMETER & LARGER. COMPACT TO 90% IN MAXIMUM 8" LIFTS OF LOOSE SOIL.


GENERAL NOTES:

- THIS DETAIL APPLIES FOR ALL SERVICE ENTRANCE, FEEDER, TECHNOLOGY SERVICE AND SIMILAR APPLICATIONS WHERE ELECTRICAL CONDUITS ARE REQUIRED TO BE INSTALLED BELOW GRADE, PAVEMENT OR SLABS.
- THIS DETAIL IS TYPICAL FOR ALL CONDUITS/DUCTS, REGARDLESS OF QUANTITY.
- SEE PLANS AND SPECIFICATIONS FOR SIZES AND QUANTITIES OF CONDUITS/DUCTS.
- PROVIDE AT LEAST 3" OF SEPARATION BETWEEN CONDUITS AND AT LEAST 4" OF SEPARATION BETWEEN ANY CONDUIT & ADJACENT TRENCH BOTTOM OR WALL. ALIGN CONDUITS ON CHAIRS AND ENSURE ALL BACKFILL ENCASES CONDUITS WITH EVEN BEARING AND WITHOUT DAMAGING CONDUITS OR CHAIRS.
- COORDINATE TRENCH LOCATION IN REFERENCE TO OTHER UNDERGROUND UTILITIES. ENSURE NO OTHER UTILITIES ARE PLACED DIRECTLY ABOVE OR BELOW, WHEN PARALLEL TO CONDUITS.




260508.00-05 - U.G. SERVICE CONDUIT DETAIL (ONE LAYER BACKFILL)

SCALE: NONE



260502.00-01 - DEVICE ALIGNMENT DETAIL

SCALE: NONE




GENERAL NOTES:

- THIS DETAIL APPLIES AT EACH REMOTE ("SATELLITE") ELECTRIC ROOM/CLOSET/AREA OR OTHER GROUPING OF PANELBOARDS THAT IS REMOTE FROM THE SERVICE ENTRANCE LOCATION, OR OTHER GROUPING OF PANELS. REFER TO FLOOR PLANS FOR GROUND BAR LOCATIONS, AND IF NOT SHOWN IN PLAN-VIEW INSTALL AS CLOSE AS POSSIBLE TO AFFECTED EQUIPMENT.
- PROVIDE ALL GROUNDING ELECTRODE CONDUCTORS SIZED PER NEC TABLE 250.66 UNLESS NOTED OTHERWISE.
- PROVIDE GROUND BAR EQUAL TO ERICO EQUIPMENT GROUND BAR W/INSULATORS AND BRACKET, HOLE PATTERN TYPE "CC".
- PROVIDE ALL BONDING JUMPERS SIZED PER NEC TABLE 250.122 UNLESS NOTED OTHERWISE.
- PROVIDE ALL WORK COMPLIANT WITH APPLICABLE REQUIREMENTS OF ARTICLE 250 OF NFPA 70 AS A MINIMUM.
- COORDINATE WITH ELECTRICAL INSPECTOR. MODIFY SPECIFIC MEANS & METHODS IF SO DIRECTED. COORDINATE WITH WORK OF ALL CONSTRUCTION DIVISIONS.

260526.00-03 - GROUND DETAIL - SATELLITE

SCALE: NONE



GENERAL NOTES:


- THIS DETAIL APPLIES AT EACH SERVICE ENTRANCE. REFER TO FLOOR PLANS FOR GROUND BAR LOCATIONS. IF NOT SHOWN IN PLAN VIEW INSTALL AS CLOSE AS POSSIBLE TO SERVICE ENTRANCE EOT.
- PROVIDE ALL GROUNDING ELECTRODE CONDUCTORS PER NEC TABLE 250.66 UNLESS NOTED OTHERWISE.
- PROVIDE SERVICE GROUND BAR EQUAL TO ERICO EQUIPMENT GROUND BAR W/INSULATORS AND BRACKET, HOLE PATTERN TYPE "CC".
- SIZE GROUND CONDUCTORS BETWEEN ROOM GROUND BARS AS GROUND ELECTRODE CONDUCTORS.
- SIZE ALL BONDING JUMPERS PER NEC TABLE 250.122 UNLESS NOTED OTHERWISE.
- PROVIDE ALL WORK COMPLIANT WITH APPLICABLE REQUIREMENTS OF ARTICLE 250 OF NFPA 70.
- COORDINATE WITH ELECTRICAL INSPECTOR. MODIFY SPECIFIC MEANS & METHODS IF SO DIRECTED. COORDINATE WITH WORK OF ALL CONSTRUCTION DIVISIONS.
- IN ADDITION TO WORK SHOWN IN DETAIL, PROVIDE BONDING JUMPERS FROM SERVICE GROUND BAR TO NATURAL GAS PIPING, WATER PIPING, DUCTWORK, AIR-DUCT EOT, WATER HEATERS, MISC. PIPING, ETC. AS APPLICABLE TO THE PROJECT AND COMPLIANT WITH NFPA 70 (INCLUDING ARTICLE 250).

260526.00-01 - GROUND DETAIL - SERVICE

SCALE: NONE



1538 ALEXANDRIA PIKE, SUITE 1
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8050
859-442-8058 FAX

engineers
architects
plannersyour trusted advisor
consultants

REV	ISSUE FOR BIDDING AND PERMIT	DATE	BY
0		11/20/2019	CAM

SHARONVILLE FIRE STATION 87 RENOVATION

CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241

ELECTRIC POWER - DETAILS


SCALE:	1/8" = 1'-0"
HORZ:	
VERT:	
CONTRACT NO:	
170636	
SHEET	
EP502	

KLH JOB#: 21459.01

UPON RECEIPT OF SIGNAL FROM DISPATCH RADIO EQUIPMENT, TIME DELAY RELAY ACTIVATES AND THE FOLLOWING SEQUENCE SHALL OCCUR:

- GENERAL NOTES:

- A. THIS WIRING DIAGRAM IS INTENDED TO SCHEMATICALLY DEFINE FUNCTIONALITY AND GENERAL SCOPE OF WORK. MEET AND COORDINATE WITH OWNER AND DISPATCH RADIO INSTALLER PRIOR TO BEGINNING ANY RELATED WORK. PROVIDE SPECIFIC WIRING, CONTACTOR, RELAY, ETC. WORK AS REQUIRED TO ACCOMMODATE OWNER'S INTENDED OPERATION.
- B. TYPE PS2 LUMINAIRES IN APPARATUS BAY SHALL AUTOMATICALLY TURN OFF WHEN TYPE X4 LUMINAIRES ARE ON, AND SHALL AUTOMATICALLY TURN ON WHEN THE TYPE X4 LUMINAIRES ARE OFF.



260590.00-10 - TONE DROP AUXILIARY CONTROL WIRING DIAGRAM

SCALE: NONE

UPON ACTIVATION OF EMERGENCY-POWER-OFF (EPO) PUSHBUTTON, CONTACTOR COIL IS DEENERGIZED AND THE FOLLOWING SEQUENCE SHALL OCCUR:


1. ACTIVE CONTACTS OPEN.
2. GAS SOLENOID VALVES OPEN. GAS SOLENOID VALVES MUST BE MANUALLY RESET. GAS SOLENOID VALVES SHALL NOT AUTOMATICALLY REOPEN AFTER THE TIMER COUNTDOWN.
3. ASSOCIATED ELECTRICALLY OPERATED KITCHEN LOADS ARE DEENERGIZED.
4. CONTACTOR MUST BE MANUALLY RESET BY PULLING THE EPO PUSHBUTTON BACK OUT TO ITS NORMAL POSITION.

A THIS WIRING DIAGRAM IS INTENDED TO SCHEMATICALLY DEFINE FUNCTIONALITY AND GENERAL SCOPE OF WORK. MEET AND COORDINATE WITH ALL OTHER TRADES TO VERIFY ALL WORK IS IN ACCORD WITH THE PROJECT MANUAL. PROVIDE SPECIFIC WIRING, CONTACTOR, ETC. WORK AS REQUIRED TO ACCOMMODATE OWNER'S INTENDED OPERATION.

B CONDENSATE PUMP SHALL BE INSTALLED IN THE CONDENSATE TRAP AND AUTOMATICALLY CLOSE WITH LOSS OF ANY POWER. COORDINATE WITH PLUMBING INSTALLER TO ENSURE THAT CONTACTOR RESET WILL BE COMPLETED BY THE PLUMBING INSTALLER. CONTACTOR MUST BE RESET MANUALLY, AND MUST NOT BE ABLE TO BE RESET UNTIL POWER IS AVAILABLE AT THE SOLENOID VALVE.

C FROM THE CONDENSATE PUMP, A 120VAC LINE VOLTAGE RESET PUSHBUTTON TO READ: "GAS VALVE RESET; TO RESET, TURN OFF ALL VALVES & CONTROLS ON RANGE INCLUDING OVEN, THEN PUSH THIS BUTTON."

D PROVIDE ENGRAVED PLATE AT PATIO GAS SOLENOID VALVE RESET. RESET TO READ: "GAS VALVE RESET; TO RESET, TURN OFF ALL VALVES & CONTROLS ON RANGE, THEN PUSH THIS BUTTON."



260590.00-09 - KITCHEN EQUIPMENT EMERGENCY-POWER-OFF DETAIL

SCALE: NONE

2 SECURE-DOOR JUNCTION BOX ("SJ"): PROVIDE 4" X 4" OUTLET BOX ON
3 SECURE SIDE OF DOOR. ABOVE ACCESS-CONTROL SYSTEM COMPONENT
4 BOX. FLUSH TO FACE OF DOOR. PROVIDE 1/2" CLEARANCE TO
5 SERVE AS LOCAL DISCONNECT WHEN SERVICING THE POWER SUPPLY.
6 PROVIDE 120VAC POWER WIRING IN 3/4" CONDUIT FROM BUILDING
7 POWER SOURCE TO ACCESS-CONTROL SYSTEM COMPONENT BOX.
8 PROVIDE 120VAC POWER WIRING IN 3/4" CONDUIT FROM KEY-SWITCH AT
9 "SJ" TO DOOR HARDWARE POWER SUPPLY.
10 DOOR HARDWARE POWER SUPPLY
11 PROVIDE 3/4" EMPTY CONDUIT BETWEEN DOOR HARDWARE POWER
12 SUPPLY BOX AND ACCESS-CONTROL SYSTEM COMPONENT BOX.
13 PROVIDE 1/2" X 2" X 1/2" WALL MOUNTED JUNCTION BOX. ACCESS-CONTROL
14 SYSTEM INSTALLER DOES NOT PROVIDE THIS BOX. THEN PROVIDE 8" X 8"
15 4" DEEP SURFACE MOUNTED JUNCTION BOX. VERIFY BOX DIMENSIONS
16 AND LOCATION WITH ACCESS-CONTROL SYSTEM INSTALLER.
17 PROVIDE 3/4" EMPTY CONDUIT(S) TO CABLE TRAY OR HORIZONTAL
18 OR OTHER PATHWAY AS APPLICABLE.
19 PROVIDE 1/2" X 2" X 1/2" WALL MOUNTED JUNCTION BOX WITH JOINT
20 RING FOR REQUEST-TO-EXIT ("REX") DEVICE AND 3/4" CONDUIT FROM
21 ACCESS-CONTROL SYSTEM COMPONENT BOX TO "REX" BOX.
22 PROVIDE 1/2" X 2" X 1/2" WALL MOUNTED JUNCTION BOX WITH JOINT
23 RING FOR REQUEST-TO-EXIT ("REX") DEVICE AND 3/4" CONDUIT FROM
24 ACCESS-CONTROL SYSTEM COMPONENT BOX TO "REX" BOX.
25 PROVIDE 3/4" CONDUIT CONDUIT DOWN TO WITHIN 6" OF DOOR
26 FRAME. THEN CONVERT TO CONCEALED 3/4" FLEXIBLE STEEL CONDUIT
27 FOR ACCESS-CONTROL SYSTEM WIRING. PROVIDE 1/2" X 2" X 1/2" WALL
28 INSTALLATION, AND TERMINATE AT FRAME AT LOCATION, AS DIRECTED
29 BY ACCESS-CONTROL SYSTEM INSTALLER AND DOOR HARDWARE
30 INSTALLER.
31 THIS CONDUIT IS FOR DOOR STATUS MONITORING CABLE.
32 THIS CONDUIT IS FOR DOOR HARDWARE WIRING.
33 PROVIDE WIRING FOR ACCESS-CONTROL SYSTEM CONTROL MODULE
34 WHEN RESPECTIVE DOOR IS ALONG A BUILDING EGRESS PATH.

A. THIS IS A SCHEMATIC DETAIL. MODIFY MEANS AND METHODS AS NEEDED FOR DOUBLE DOORS, ROOF HATCHES, "STOREFRONT" GLASS DOORS, ETC. PRE-COORDINATE ALL WORK WITH DOOR AND ACCESS CONTROL SYSTEM INSTALLERS.

B. INSTALL ALL WORK ON SECURE SIDE OF DOOR UNLESS NOTED OTHERWISE. INSTALL OVERHEAD WORK ABOVE NEAREST SECURE-SIDE ACCESSIBLE CEILING FOR APPLICATIONS WHERE NON-ACCESSIBLE CEILING EXISTS ABOVE DOOR. INSTALL IN OVERHEAD STRUCTURAL SPACE FOR APPLICATIONS WHERE THERE ARE NO FINISHED CEILINGS.

260590.00-04 - SECURE DOOR ROUGH-IN DETAIL

SCALE: NONE

11/14/2019 10:22:37 AM

ELECTRIC SINGLE LINE EQUIPMENT SCHEDULE			
NOTES: ALL CONDUIT SIZES INDICATED ARE MINIMUM SIZES. INCREASE SIZES AS REQUIRED TO ACCOMMODATE CONDUCTOR (S) + 480V/277V, L - 208V/120V) "CU" = COPPER CONDUCTOR, "AL" = ALUMINUM CONDUCTOR		TYPICAL EQUIPMENT NAME NOMENCLATURE: 1 - POWER DISTRIBUTION SYSTEM (BLANK - NORMAL, E - EMERGENCY, S - STANDBY, L - LIFE SAFETY) 2 - DESCRIPTION (H1 - 480V/277V, L - 208V/120V) 3 - FLOOR / LEVEL 4 - SEQUENCE	
		FEEDER ID NOMENCLATURE: - INDICATES FEEDER SIZE TO COMPENSATE FOR VOLTAGE DROP - GROUND TYPE (NOT TO BE BLANK) U = EQUIPMENT GROUND CONDUCTOR REMOVED FOR SERVICE ENTRANCE FROM UTILITY P = PARTI-SIZED EQUIPMENT GROUND X = EXISTING FEEDER TO REMAIN UNLESS OTHERWISE NOTED T = UPSIZED GROUND CONDUCTORS FOR TRANSFORMER SECONDARY	
		2 - CONDUCTOR AMPACITY - TOTAL NUMBER OF PHASE AND GROUNDED ("NEUTRAL") CONDUCTORS 4 - CONDUCTOR MATERIAL: C = COPPER, A = ALUMINUM 5 - SPECIAL CONDUCTOR I = ISOLATED GROUND (PROVIDE CONTINUOUS INSULATED ISOLATED EQUIPMENT GROUNDING CONDUCTOR(S) FROM INSULATED ISOLATED GROUND BAR(S) TO RESPECTIVE UPSTREAM SERVICE ENTRANCE OR DERIVED SYSTEM GROUNDING ELECTRODE CONDUCTOR AS APPLICABLE.	

EQUIPMENT	PHASE	POWER BRANCH	EQUIPMENT TYPE	SUPPLY FROM	SPACE NUMBER	SPACE NAME	VOLTAGE	PHASE	WIRES	DEMAND (kVA)	DEMAND (A)	MAINS RATING (A)	MAINS FRAME RATING (A)	MAINS TYPE	FEEDER ID	FEEDER	VD %	LUGS TYPE	SPD	ULSE	GEC	ENCLOSURE TYPE	200% NEUTRAL	K-RATING	FAULT CURRENT (A)	SHORT CIRCUIT RATING (A)	NOTES	
GENERATOR	New Construction	OPTIONAL STANDBY	Generator				208	3		87.2 kVA	242 A											NEMA 3R			2891			
-- ATS-OS	New Construction	OPTIONAL STANDBY	ATS - Emergency Connection	GENERATOR	124	ELECTRICAL	208	3	4	87.2 kVA	242 A	300	300		300-4A	(4) #500 KCMIL AL, (1) #2 AWG AL GND. IN 4" CONDUIT	1.006					NEMA 1			3171	10000		
UTILITY	Existing	NORMAL	Pole Mounted Transformer				208	3		122.1 kVA	339 A			MAIN LUGS ONLY								NEMA 3R			56600			
-- MDP	New Construction	NORMAL	Distribution Panelboard	UTILITY	124	ELECTRICAL	208	3	4	122.1 kVA	339 A	600	600	THERMAL MAGNETIC	U600-4A	(2) SETS OF (4) #500 KCMIL AL IN 4" CONDUIT EACH	0.59			Yes	Yes	Yes	NEMA 1			36434	42000	
---- L1A	New Construction	NORMAL	Branch Panelboard	MDP	124	ELECTRICAL	208	3	4	14.4 kVA	40 A	125	125	MAIN LUGS ONLY	125-4A	(4) #20 AWG AL, (1) #4 AWG AL GND. IN 2" CONDUIT	0.727	FEED-THROUGH				NEMA 1			29527	42000		
---- L2A	New Construction	NORMAL	Branch Panelboard	MDP	206	MECHANICAL	208	3	4	33.1 kVA	92 A	200	200	MAIN LUGS ONLY	200-4A	(4) #250 KCMIL AL, (1) #4 AWG AL GND. IN 3" CONDUIT	1.238					NEMA 1			16509	22000		
---- ATS-OS	New Construction	OPTIONAL STANDBY	3-Pole ATS	MDP	124	ELECTRICAL	208	3	4	87.2 kVA	242 A	300	300	MAIN LUGS ONLY	300-4A	(4) #500 KCMIL AL, (1) #2 AWG AL GND. IN 4" CONDUIT	0.7					NEMA 1			34483	42000		
----- OSDP	New Construction	OPTIONAL STANDBY	Branch Panelboard	ATS-OS	124	ELECTRICAL	208	3	4	87.2 kVA	242 A	300	300	THERMAL MAGNETIC	300-4A	(4) #500 KCMIL AL, (1) #2 AWG AL GND. IN 4" CONDUIT	0.81			Yes		NEMA 1			32060	42000		
----- OSL1A	New Construction	OPTIONAL STANDBY	Branch Panelboard	OSDP	124	ELECTRICAL	208	3	4	18.3 kVA	51 A	125	125	MAIN LUGS ONLY	125-4A	(4) #20 AWG AL, (1) #4 AWG AL GND. IN 2" CONDUIT	0.947			Yes		NEMA 1			29717	42000		
----- OSL1B	New Construction	OPTIONAL STANDBY	Branch Panelboard	OSDP	112	LAUNDRY	208	3	4	20.6 kVA	57 A	100	100	MAIN LUGS ONLY	100-4A	(4) #10 AWG AL, (1) #6 AWG AL GND. IN 2" CONDUIT	1.664			Yes		NEMA 1			8439	22000		
----- OSL2A	New Construction	OPTIONAL STANDBY	Branch Panelboard	OSDP	206	MECHANICAL	208	3	4	16.2 kVA	45 A	125	125	MAIN LUGS ONLY	125-4A	(4) #20 AWG AL, (1) #4 AWG AL GND. IN 2" CONDUIT	1.515			Yes		NEMA 1			11256	22000		

A. PARALLEL CONDUCTOR SETS: CUT PARALLEL SERVICE/FEEDER CONDUCTORS TO EXACTLY THE SAME LENGTHS AND USE CONDUCTORS FROM THE SAME FACTORY RUN. TORQUE ALL CONNECTIONS FOR PARALLEL SERVICE/FEEDER CONDUCTORS TO IDENTICAL VALUES.

- A. PARALLEL CONDUCTOR SETS: CUT PARALLEL SERVICE/FEEDER CONDUCTORS TO EXACTLY THE SAME LENGTHS AND USE CONDUCTORS FROM THE SAME FACTORY RUN. TORQUE ALL CONNECTIONS TO MANUFACTURER'S SPECIFICATIONS.
- B. OVERCURRENT PROTECTION RATINGS: UNLESS INDICATED OTHERWISE, PROVIDE FULLY-RATED OR SERIES-RATED OVERCURRENT PROTECTION (OCP) AS REQUIRED TO COMPLY WITH ALL APPLICABLE ELECTRICAL CODES AND STANDARDS. PROVIDE OCP IN ACCORDANCE WITH THE FOLLOWING AVAILABLE SERIES-RATED FAULT CURRENT AT THE RESPECTIVE NODE IN THE POWER DISTRIBUTION SYSTEM. SERIES-RATED BREAKERS/SYSTEMS ARE NOT PERMITTED WHERE PROHIBITED BY PRELIMING CODES AND STANDARDS INCLUDING ANY CONDITIONS IN THE FACTORY CONTRIBUTION ADDENDUM TO THIS SPECIFICATION. PROVIDE TWO (2) UNWRAPPED COPIES OF THE ELECTRICAL DOCUMENTS TO THE MANUFACTURER'S REPRESENTATIVE AND/OR EQUIPMENT SUPPLIER SO THAT PROPERLY RATED AND BRACED EQUIPMENT IS PROVIDED UNDER BASE BID. IF FAULT CURRENT IS NOT KNOWN, NOTIFY ARCHITECT IMMEDIATELY FOR RECALCULATIONS AND/OR FURNISH RESULTS WITH EQUIPMENT SUBMITTALS.
- C. GROUNDING ELECTRODE CONDUCTOR SYSTEM: PROVIDE GROUNDING ELECTRODE CONDUCTOR SYSTEM IN ACCORDANCE WITH THE FOLLOWING: PROVIDE A MINIMUM OF ONE (1) COPPER CLAD COTICAL CODE (NFFA 70), INCLUDING ARTICLE 250 AND TABLE 250.66. THESE CONDUCTORS MAY OR MAY NOT BE INDICATED ON SINGLE-LINE DIAGRAMMS, BUT SHALL BE PROVIDED UNDER BASE BID NEARBY.
- D. FLUSH MOUNTED EQUIPMENT: PROVIDE FLUSH MOUNTED POWER DISTRIBUTION AND RELATED EQUIPMENT FOR APPLICATIONS IN FINISHED AREAS AND COORDINATE THESE LOCATIONS AND TYPES OF EQUIPMENT WITH ARCHITECT. PROVIDE FLUSH MOUNTED EQUIPMENT TO MATCH SURFACE MOUNTED EQUIPMENT UNLESS FLUSH MOUNTED EQUIPMENT IS SHOWN ON DRAWINGS OR OTHERWISE NEEDED TO ACCOMMODATE UNUSUAL CONDITIONS.
- E. POWER DISTRIBUTION EQUIPMENT LABELS: IN ADDITION TO LABELS REQUIRED WITHIN THE SPECIFICATION, PROVIDE THE FOLLOWING MAXIMUM AIC (AVAILABLE FLUSH CURRENT) AND SHORT-CIRCUIT CURRENT RATING (SCCR) FOR EACH TYPE OF POWER DISTRIBUTION EQUIPMENT, ALONG WITH ARC FLASH LABELS COMPLIANT WITH ARTICLE 10.16 OF NFPA 70. ALSO INCLUDE CONDUCTOR SIZES TO FIT INTO THE BUILDING STRUCTURE.
- F. CONDUCTOR TERMINATIONS: IN CASES WHERE CONDUCTOR SIZES ARE TOO LARGE TO FIT INTO LUGS/TERMINALS, PROVIDE APPROPRIATE FACTORY LUG KITS FOR AFFECTED EQUIPMENT IF AVAILABLE. IF SUCH KIT IS NOT AVAILABLE, PROVIDE AN APPROVED FIELD-APPLIED KIT THAT TAILS SIZED TO FIT LUGS/TERMINALS. PROVIDE SPLICES IN SEPARATE BOXES IF REQUIRED BASED ON FIELD CONDITIONS, BOX SIZE LIMITATIONS, ETC. CONCEAL BOXES IN ACCESSIBLE OVERHEAD JOIST SPACES.
- G. ALUMINUM CONDUCTORS: PROVIDE THE FOLLOWING SUPPLEMENTAL WORK FOR ALUMINUM CONDUCTOR ELECTRICAL EQUIPMENT CONNECTIONS, REGARDLESS OF WHO FURNISHES THE EQUIPMENT: REMOVE EQUIPMENT SUBMITTALS, INSTALLATION INSTRUCTIONS AND INSTRUCTIONS TO DETERMINE: ARE THERE ANY WARRANTY CONCERNS REGARDING THE USE OF ALUMINUM WIRE/ALUMINUM JOINING CONNECTIONS AT EQUIPMENT; IF THERE ARE ANY LIMITATIONS, PROVIDE A LOCAL DISCONNECT AT OR NEAR EQUIPMENT (EXTERNAL TO THE EQUIPMENT) AND TERMINATE ALUMINUM CONDUCTORS TO THE DISCONNECT SWITCH. IF THERE ARE NO LIMITATIONS, PROVIDE COPPER CONDUCTORS FROM LOAD-SIDE LUGS/TERMINALS OF THE DISCONNECT SWITCH TO THE RESPECTIVE EQUIPMENT FACTORY DISCONNECT OR LUG/TERMINALS AS APPLICABLE; COORDINATE ALL RELATED WORK WITH ALL OTHER TRADES.
- H. FEEDER TAPS: "PERFORM FEEDER TAPS IN ACCORDANCE WITH NFPA 70. PERFORM FEEDER TAPS TO PARALLELED SELF FEEDERS BY RESPECTIVELY TAPPING ALL PHASE, GROUNDED AND GROUNDING LINE CONDUCTORS."
- I. BREAKER FRAME SIZES: AMPERE RATINGS INDICATED ON DRAWINGS FOR CIRCUIT BREAKERS ARE NOT TO DEFINE OVERCURRENT REQUIREMENTS/TRIP RATINGS. PROVIDE BREAKER FRAMES IN ACCORDANCE WITH THE FOLLOWING: PROVIDE DEPENDENT TRIP DEVICES AND/OR COORDINATION NECESSARY TO ACHIEVE THE REQUIRED SELECTIVE COORDINATION, AND/OR AS NECESSARY FOR ANY OTHER APPLYING REASONS.
- J. HOUSEKEEPING PADS: SEE SPECIFICATION SECTION 260529.00 FOR REQUIREMENTS ASSOCIATED WITH HOUSEKEEPING PADS.
- K. PLYWOOD EQUIPMENT BOARDS: SEE SPECIFICATION SECTION 260529.00 FOR REQUIREMENTS ASSOCIATED WITH PLYWOOD EQUIPMENT BOARDS.
- L. FIELD ADJUSTABLE OVERCURRENT TRIP VALUES: PROVIDE FIELD-ADJUSTABLE OVERCURRENT TRIP VALUES AS INDICATED ON DRAWINGS (UNLESS OTHERWISE SPECIFIED IN OVERCURRENT PROTECTED DEVICE COORDINATION STUDY). UNLESS INDICATED OTHERWISE ON DRAWINGS, OR DIRECTED OTHERWISE BY ARCHITECT, PROVIDE FIELD-ADJUSTABLE OVERCURRENT TRIP COORDINATION BASED ON PROJECT REQUIREMENTS AND PREVAILING CODES, WHILE MINIMIZING THE POSSIBILITY OF nuisance tripping. MANUFACTURER SHALL PROVIDE REMOVABLE AND SEALABLE COVERS OVER ALL FIELD-ADJUSTABLE OVERCURRENT TRIP SETTINGS.
- M. ELECTRIC UTILITY SERVICE WORK: PROVIDE ALL ELECTRIC UTILITY SERVICE WORK IN STRICT COMPLIANCE WITH PREVAILING REQUIREMENTS OF THE UTILITY COMPANY. THE DRAWINGS INDICATE RELATED REQUIREMENTS AT A SCHEMATIC LEVEL. IT IS NOT THE INTENT OF THESE DRAWINGS TO REQUIRE THE CONTRACTOR TO IDENTIFY THE LOCATION OF THE UTILITY COMPANY'S TRANSFORMER(S), PROVIDE METER SOCKET(S) AND EMPTY CONDUIT (WITH DRAG LINE) FROM METER TO CURRENT TRANSFORMER LOCATION. PROVIDE CURRENT TRANSFORMER (CT) CABINET (WHICH MUST BE WITH STANDING MAIN PANEL) AND ALL UTILITY COMPANY AS REQUIRED TO PROVIDE COMPLETE OPERATIONAL ELECTRIC SERVICE(S).

A. **COMPLIANCE WITH CODES & STANDARDS:** PROVIDE ALL WORK COMPLIANT WITH ALL PREVAILING CODES, ORDINANCES, STANDARDS, ETC. THAT APPLY. THIS SHALL INCLUDE, BUT NOT BE LIMITED TO THE FOLLOWING:

B. **MONITORING & CONTROL:** PROVIDE WIRING IN CONDUIT (1-1/2" MINIMUM) FROM GENERATOR SET(S) TO TRANSFER SWITCHES, AS REQUIRED FOR COMPLETELY OPERATIONAL MONITORING AND CONTROL OF GENERATOR SET(S) AND TRANSFER SWITCHES. PROVIDE ALL WIRING IN ACCORDANCE WITH THE GENERATOR SET MANUFACTURER. CONTROL CONDUCTORS INSTALLED BETWEEN THE TRANSFER EQUIPMENT AND THE GENERATOR SHALL BE KEPT ENTIRELY INDEPENDENT OF ALL OTHER WIRING AND SHALL BE IDENTIFIED BY THE FOLLOWING: (1) GENERATOR SET(S) AND (2) TRANSFER SWITCH(S). THE COLLECTIVE GENERATOR SYSTEM, INCLUDING GENERATOR CONTROL WIRING, SHALL BE CONTINUOUSLY MONITORED. ANY MALFUNCTION OF THE COLLECTIVE GENERATOR SYSTEM, INCLUDING LOSS OF GENERATOR SET(S) OR TRANSFER SWITCH(S), SHALL BE INDICATED BY AN ANNUNCIATOR. IN THE EVENT OF GENERATOR MALFUNCTION AT THE GENERATOR LOCAL AND REMOTE ANNUNCIATOR(S), LOSS OF INTEGRITY OF THE REMOTE START CIRCUIT(S) SHALL START THE GENERATOR(S).

C. **ANNUNCIATION:** PROVIDE AT LEAST ONE (1) REMOTE ANNUNCIATOR SET(S) AND TRANSFER SWITCHES TO REMOTE GENERATOR ANNUNCIATOR FOR MONITORING OF GENERATOR SYSTEM STATUS. DETERMINE SPECIFIC REQUIREMENTS FROM GENERATOR SET MANUFACTURER. DETERMINE EXACT LOCATION OF ANNUNCIATOR IN FIELD WITH OWNER, AND WITH AUTHORITY HAVING JURISDICTION IF APPROPRIATE.

D. **ACCESSORY COMPONENT POWER:** PROVIDE POWER WIRING FOR GENERATOR SET ACCESSORY COMPONENTS AS DIRECTED BY GENERATOR SET MANUFACTURER. POWER SHALL BE FED FROM A MAIN ELECTRICAL ENGINEERING ROOM OR FROM THE CLOSEST AVAILABLE SOURCE OF POWER THAT HAS THE HIGHEST PRIORITY FOR TRANSFER.

E. **SIGNAL SERVICE ENTRANCE:** PROVIDE IN-ENGINEERED NAMEPLATE TYPE SIGN AT SERVICE ENTRANCE(S) INDICATING THE LOCATION OF THE SERVICE ENTRANCE(S) AND THE SOURCE OF POWER.


F. **SHORT-CIRCUIT CURRENT RATING DOCUMENTATION:** PROVIDE FIELD MARKING (NEATLY PRINTED OR ENGRAVED LABEL) ON THE EXTERIOR OF ALL TRANSFER EQUIPMENT THAT INDICATES THE RESPECTIVE RATED SHORT-CIRCUIT CURRENT RATING OF THE EQUIPMENT. PROVIDE APPROPRIATE PROTECTIVE DEVICE TYPE AND SETTINGS PROTECTING THE RESPECTIVE TRANSFER EQUIPMENT.

G. **MAINTENANCE RECEIPTABLE:** PROVIDE AT LEAST ONE WEATHERPROOF TYPE WR GFCI DUPLEX RECEPTACLE FOR EACH GENERATOR SET AND TRANSFER SWITCH.

H. **OUTDOOR LIGHTING AT GENERATOR:** PROVIDE AT LEAST ONE UL LISTED LUMINAIRE NEAR GENERATOR SET FOR OUTDOOR APPLICATIONS.

I. **COORDINATION:** COORDINATE AIR INTAKES, RADIATOR AIR DISCHARGE AND ENGINE EXHAUST DISCHARGE LOCATIONS WITH HVAC INTAKES SO THAT RADIATOR AIR DISCHARGE AND ENGINE EXHAUST DISCHARGE ARE AS FAR AS POSSIBLE (AT LEAST 25 FEET) AWAY FROM ANY HVAC AIR INTAKES, AND DOWNWIND FROM ANY HVAC AIR INTAKES BASED ON LOCAL PREVAILING WIND PATTERNS.


GROUNDING BUSBAR(S): PROVIDE GROUNDING BUSBAR FOR BUILDING GROUNDING ELECTRODE SYSTEM. SEE DETAILS AND SPECIFICATIONS. PROVIDE ONE AT EACH GROUPING OF ONE OR MORE PIECES OF POWER DISTRIBUTION EQUIPMENT, AND IN EACH TECHNOLOGY EQUIPMENT ROOM, AND PROVIDE CONTINUOUS BUILDING GROUNDING ELECTRODE CONDUCTOR BETWEEN ALL BUSBARS. PROVIDE BONDING JUMPERS FROM SERVICE GROUND BAR TO NATURAL GAS PIPING, WATER PIPING, DUCTWORK, AIR-DUCT EQ., WATER HEATERS, MISC. PIPING, ETC. AS APPLICABLE TO THE PROJECT AND COMPLIANT WITH NFPA 70 (INCLUDING ARTICLE 250).



SCALE: NONE



engineers
architects
planners



REV	REVISIONS	DATE	BY
0	ISSUE FOR BIDDING AND PERMIT	11/20/2019	CAN
DATE:	11/20/2019		
DRAWN BY:	KH		
CHECKED BY:	PM		
APPROVED BY:			
F.B.	PG.		

SHARONVILLE FIRE STATION 87 RENOVATION

CITY OF SHARONVILLE

ELECTRIC POWER - SINGLE LINE DIAGRAM

SCALE: $1/8" = 1'-4"$

VERT: _____

CONTRACT NO:

170636

170030

SHEET


EP601



1538 ALEXANDRIA PIKE, SUITE 1
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8050
859-442-8058 FAX

LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK

engineers
architects
planners



DATE	REV	ISSUE FOR BIDDING AND PERMIT	REVISIONS	DATE	BY
1/26/2019	0			11/20/2019	GAM
DRAWN BY:	KH				
CHECKED BY:	PM				
APPROVED BY:					
F.B.	PQ.				

SHARONVILLE FIRE STATION 87 RENOVATION

CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241

ELECTRIC POWER - PANEL SCHEDULES

SCALE:	
HORZ:	
VERT:	
CONTRACT NO:	
170636	
SHEET	
EP602	

SUPPLY FROM: MDP				MAINS RATING (A): 200				FAULT CURRENT (A): 16509				SURGE SUPPRESSION: ULSE:								
LOCATION: MECHANICAL 206				MAINS TYPE: MAIN LUGS ONLY				SHORT CIRCUIT RATING (A): 22000												
DISTRIBUTION SYSTEM: 208/120V 3PH 4W				FEEDER ID: 200-4A				LUGS TYPE:				200% NEUTRAL:								
FEEDER: (4) #250 KCMIL AL, (1) #4 AWG AL GND, IN 3" CONDUIT				ENCLOSURE TYPE: NEMA 1				ISOLATED GROUND:												
CKT	CIRCUIT DESCRIPTION	VD%	AWG	GND	TRIP	FRAME	POLE	A	B	C	POLE	FRAME	TRIP	GND	AWG	VD%	CIRCUIT DESCRIPTION	CKT		
1	LIGHTING MECHANICAL 206	1.308	#12	#12	20 A	20 A	1	0.14	0.55		1	15 A	15 A	#12	#12	1.333	FCU-02 MOTOR MECHANICAL 206	2		
3	LIGHTING FITNESS 205	1.269	#12	#12	20 A	20 A	1		0.03	1.32		2	20 A	20 A	#12	2.39	CU-01 MOTOR	4		
5	RECEPTACLE RESTROOM 203	1.945	#12	#12	20 A	20 A	1			0.36	1.32		1	20 A	20 A	#12	1.882	FCU-03 MOTOR MECHANICAL 206	6	
7	FITNESS EQPT. RECEPTACLE FITNESS 205	2.642	#12	#12	20 A	20 A	1	1.50	1.60			1	20 A	20 A	#12	#12	1.882	FCU-03 MOTOR MECHANICAL 206	8	
9	FITNESS EQPT. RECEPTACLE FITNESS 205	3.037	#12	#12	20 A	20 A	1		1.50	2.57		2	40 A	40 A	#10	#8	2.051	CU-03 MOTOR	10	
11	FITNESS EQPT. RECEPTACLE FITNESS 205	3.468	#12	#12	20 A	20 A	1			1.50	2.57		1	15 A	15 A	#12	1.539	FCU-04 MOTOR MECHANICAL 206	12	
13	FITNESS EQPT. RECEPTACLE FITNESS 205	3.933	#12	#12	20 A	20 A	1	1.50	0.76			1	15 A	15 A	#12	#12	1.539	FCU-04 MOTOR MECHANICAL 206	14	
15	TREADMILL MOTOR FITNESS 205	4.344	#12	#12	20 A	20 A	1		1.50	1.10		2	20 A	20 A	#12	#12	1.992	CU-02 MOTOR	16	
17	RECEPTACLE FITNESS 205	2.612	#12	#12	20 A	20 A	1			0.72	1.10		2	20 A	20 A	#12	#12	1.992	CU-02 MOTOR	18
19	(G) EWC NON-CONTINUOUS FITNESS 205	1.709	#12	#12	20 A	20 A	1	0.60	0.36			1	20 A	20 A	#12	1.625	(A) RECEPTACLE, NON-CONTINUOUS KITCHEN 201	20		
21	RECEPTACLE 207.206	1.334	#12	#12	20 A	20 A	1		0.36	0.54		1	20 A	20 A	#12	1.654	(A) RECEPTACLE KITCHEN 201	22		
23	(A) RECEPTACLE KITCHEN 201	1.838	#12	#12	20 A	20 A	1			0.54	1.20		1	20 A	20 A	#12	1.902	(G) ICE NON-CONTINUOUS	24	
25	RECEPTACLE	1.796	#12	#12	20 A	20 A	1	0.36	1.00			1	20 A	20 A	#12	1.879	(G) DISHWASHER MOTOR, NON-CONTINUOUS...	26		
27	EXTERIOR RECEPTACLE	1.656	#12	#12	20 A	20 A	1			0.36	1.14		1	15 A	15 A	#12	1.957	(A) GD1 MOTOR, NON-CONTINUOUS KITCHEN 201	28	
29	RECEPTACLE 201.202	2.684	#12	#12	20 A	20 A	1			0.72	0.50	1	20 A	20 A	#12	#12	1.663	(ST) HOOD FANS HOOD LIGHTS TOGGLE SWITCH L...	30	
31	(A) RECEPTACLE DAYROOM 202	3.43	#12	#12	20 A	20 A	1	1.08	0.00		--	--	--	--	--	--	--	SHUNT TRIP	32	
33	(A) RECEPTACLE CORRIDOR 200	2.17	#12	#12	20 A	20 A	1		0.54	0.75		1	20 A	20 A	#12	1.938	(ST) RANGE NON-CONTINUOUS KITCHEN 201	34		
35	NON-CONTINUOUS FITNESS 205	2.097	#12	#12	20 A	20 A	1			0.60	0.00	--	--	--	--	--	--	SHUNT TRIP	36	
37	FAN NON-CONTINUOUS FITNESS 205	1.398	#12	#12	20 A	20 A	1	0.10	0.05			1	20 A	20 A	#12	1.251	C2 NON-CONTINUOUS JANITOR'S CLOSET 207	38		
39	EWI-H-01 HEATING CORRIDOR 200	4.542	#12	#12	20 A	20 A	1	1.50	0.18			1	20 A	20 A	#12	1.423	(A) RECEPTACLE KITCHEN 201	40		
41	SPARE	--	--	--	20 A	--	1			0.00	1.50	1	20 A	20 A	#12	12.428	EWI-H-03 HEATING CORRIDOR 101	42		
43	SPARE	--	--	--	20 A	--	1	0.00	0.00			1	--	20 A	--	--	--	SPARE	44	
45	SPARE	--	--	--	20 A	--	1		0.00	0.00		1	--	20 A	--	--	--	SPARE	46	

SUPPLY FROM: UTILITY						MAINS RATING (A): 600						FAULT CURRENT (A): 36434						SURGE SUPPRESSION: Yes								
LOCATION: ELECTRICAL 124						MAINS TYPE: THERMAL MAGNETIC						SHORT CIRCUIT RATING (A): 42000						ULSE: Yes								
DISTRIBUTION SYSTEM: 208/120V 3PH 4W						FEEDER ID: U600-4A						LUGS TYPE:						200% NEUTRAL:								
FEEDER: (2) SETS OF (4) #500 KCMIL AL IN 4" CONDUIT EACH						ENCLOSURE TYPE: NEMA 1						ISOLATED GROUND:														
CKT	CIRCUIT DESCRIPTION					VD%	AWG	GND	TRIP	FRAME	POLE	A	B	C	POLE	FRAME	TRIP	GND	AWG	VD%	CIRCUIT DESCRIPTION					CKT
1	L1A I NON-CONTINUOUS ELECTRICAL 124					SL	SL	SL	125 A	125 A	3	6.90	0.00		3	--	20 A	--	--	--	SPARE					2
3													2.94	0.00												4
5														3.96	0.00											6
7	ATS-OS I NON-CONTINUOUS ELECTRICAL 124					SL	SL	SL	300 A	300 A	3	31....	0.00		3	--	20 A	--	--	--	SPARE					8
9													29.21	0.00												10
11														26.90	0.00											12
13	L2A					SL	SL	SL	200 A	200 A	3	9.59														14
15													13.39													16
17														12.63												18
19																										20
21																										22
23																										

SUPPLY FROM: MDP				MAINS RATING (A): 125				SHORT CIRCUIT RATING (A): 42000				SURGE SUPPRESSION:							
LOCATION: ELECTRICAL 124				MAIN TYPE: MAIN LUGS ONLY				LUGS TYPE: FEED-TROUGH				ULSE:							
DISTRIBUTION SYSTEM: 208/120V 3PH 4W				FEEDER ID: 125-4A								200% NEUTRAL:							
FEEDER: (4) #2/0 AWG AL, (1) #4 AWG AL GND, IN 2" CONDUIT				ENCLOSURE TYPE: NEMA 1								ISOLATED GROUND:							
CKT	CIRCUIT DESCRIPTION	VD%	AWG	GND	TRIP	FRAME	POLE	A	B	C	POLE	FRAME	TRIP	GND	VD%	CIRCUIT DESCRIPTION	CKT		
1	(G) VENDING NON-CONTINUOUS APPARATUS BA...	1.881	#12	#12	20 A	20 A	1	0.80	0.17				1	20 A	#12	1.48	(-) PARKING LOT LIGHTING	2	
3	LIGHTING	1.367	#12	#12	20 A	20 A	1		0.24	0.24			1	20 A	#12	1.363	EXTERIOR LIGHTING	4	
5	(G) EWC RECEPTACLE, NON-CONTINUOUS...	2.444	#12	#12	20 A	20 A	1			0.96	0.04		1	20 A	#12	0.849	FLAG POLE LIGHTING	6	
7	RECEPTACLE	1.311	#12	#12	20 A	20 A	1	0.36	0.04				1	20 A	#12	0.794	LIGHTING	8	
9	EF-06 MOTOR JANITOR'S CLOSET 115	0.764	#12	#12	15 A	15 A	1		0.03	0.10			1	20 A	#12	1.057	LIGHTING	10	
11	RECEPTACLE JANITOR'S CLOSET 115	0.954	#12	#12	20 A	20 A	1			0.18	0.54		1	20 A	#12	2.193	RECEPTACLE	12	
13	RECEPTACLE, NON-CONTINUOUS CORRIDOR 101	1.583	#12	#12	20 A	20 A	1	0.72	1.50				1	20 A	#12	1.898	EW-02 HEATING VESTIBULE 100	14	
15	(G) WASHER NON-CONTINUOUS DECON 119	3.295	#12	#12	20 A	20 A	1		1.20	0.54			1	20 A	#12	1.598	RECEPTACLE TOOLS/STORAGE 117	16	
17	DRYER NON-CONTINUOUS DECON 119	2.34	#10	#10	30 A	30 A	2		1.88	1.44			1	20 A	#12	2.344	RECEPTACLE SCBA 118	18	
19	RECEPTACLE APPARATUS BAY 125	1.308	#12	#12	20 A	20 A	1		0.54	0.04			1	15 A	15 A	#12	0.767	EF-07 MOTOR RESTROOM 123	22
23	SPARE	--	--	--	20 A	--	1			0.00	0.00	1	--	20 A	--	--	SPARE	24	
25	SPARE	--	--	--	20 A	--	1	0.00	0.00				1	--	20 A	--	--	SPARE	26
27	SPARE	--	--	--	20 A	--	1		0.00	0.00			1	--	20 A	--	--	SPARE	28
29	SPARE	--	--	--	20 A	--	1			0.00	0.00	1	--	20 A	--	--	SPARE	30	
31	SPACE	--	--	--	--	--	--	0.00	0.00			--	--	--	--	--	SPACE	32	
33	SPACE	--	--	--	--	--	--		0.00	0.00		--	--	--	--	--	SPACE	34	
35	SPACE	--	--	--	--	--	--			0.00	0.00	--	--	--	--	--	SPACE	36	
37	SPACE	--	--	--	--	--	--	0.00	0.00			--	--	--	--	--	SPACE	38	
39	SPACE	--	--	--	--	--	--		0.00	0.00		--	--	--	--	--	SPACE	40	
41	SPACE	--	--	--	--	--	--			0.00	0.00	--	--	--	--	--	SPACE	42	
TOTAL CONNECTED LOAD: 6.9 kVA 2.9 kVA 4.0 kVA																			
LOAD CLASSIFICATION		CONNECTED LOAD		DEMAND FACTOR		ESTIMATED DEMAND		NOTES:		BREAKER QUANTITIES (NEW ONLY)									
Heating		1500 VA		100.00%		1500 VA				(2) 15A / 1P, (23) 20A / 1P, (3) 20A / 1P									
Lighting		832 VA		125.00%		1040 VA				(6), (1) 30A / 2P									
Motor		1513 VA		123.79%		1873 VA													
Non-Continuous		6350 VA		100.00%		6350 VA													

(EX) = EXISTING CIRCUIT TO REMAIN
(#) = NEW CIRCUIT TO EXISTING CIRCUIT BREAKER
(G) = PROVIDE GROUND-FAULT CIRCUIT INTERRUPTER (GFCI) CIRCUIT BREAKER
(GE) = PROVIDE GROUND-FAULT EQUIPMENT PROTECTION (GFE) CIRCUIT BREAKER
(ST) = PROVIDE SHUNT TRIP CIRCUIT BREAKER
(A) = PROVIDE ARC FAULT CIRCUIT INTERRUPTER (AFCI) CIRCUIT BREAKER
(L) = PROVIDE LOCK-ON DEVICE

(LT)	=	PROVIDE LOCK-OUT/TAG-OUT DEVICE
(->)	=	CONNECT BRANCH CIRCUIT, WHICH WAS DISCONNECTED FROM ANOTHER SOURCE AS PART OF SELECTIVE DEMOLITION, TO POLE SPACE(S) INDICATED, DETERMINE EXACT POLE ASSIGNMENT(S) BASED ON EXISTING COLOR-CODING OF THE BRANCH CIRCUIT CONDUCTOR INSULATION. PROVIDE NEW BREAKER IF REQUIRED.
*	=	WIRE SIZED TO COMPENSATE FOR VOLTAGE DROP
==	=	REFER TO DRAWINGS FOR SPECIFICATIONS
SL	=	SEE THE SINGLE LINE DIAGRAM / SCHEDULE FOR WIRE SIZE AND VOLTAGE DROP

- A. PROVIDE HACR RATED BREAKERS ON ALL MOTOR LOADS.
- B. PROVIDE LOCKING TYPE BREAKER FOR ALL LIFE SAFETY AND NIGHT LIGHTING BRANCH CIRCUITS
- C. ALL VOLTAGE DROP CALCULATIONS AND COMPENSATED WIRE SIZES ARE BASED ON RIGHT ANGLE CIRCUIT LENGTHS TO THE LAST DEVICE. ACTUAL VOLTAGE DROP VARIES BASED ON INSTALLED WIRE LENGTH.

--	--	--
--	--	L2A
--	L1A	MDP

KLH

ENGINEERS

MECHANICAL/ELECTRICAL ENGINEERS

WWW.KLHENGRS.COM

1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8050
859-442-8058 FAX

LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK

engineers
architects
planners

REV	DATE	BY	REVISIONS	DATE	BY
0	11/20/2019	CLM	ISSUE FOR BIDDING AND PERMIT	11/20/2019	CLM
1					
2					
3					
4					
5					
6					
7					
8					
9					
10					
11					
12					
13					
14					
15					
16					
17					
18					
19					
20					
21					
22					
23					
24					
25					
26					
27					
28					
29					
30					
31					
32					
33					
34					
35					
36					
37					
38					
39					
40					
41					
42					

SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241
ELECTRIC POWER - PANEL SCHEDULES

SCALE:	
HORIZ:	
VERT:	
CONTRACT NO:	170636
SHEET	EP603

PANEL NAME: OSL2A		SUPPLY FROM: OSDP	MAINS RATING (A): 125	FAULT CURRENT (A): 11256	SURGE SUPPRESSION: Yes														
		LOCATION: MECHANICAL 206	MAINS TYPE: MAIN LUGS ONLY	SHORT CIRCUIT RATING (A): 22000	ULSE:														
		DISTRIBUTION SYSTEM: 208/120V 3PH 4W	FEEDER ID: 125-4A	LUGS TYPE:	200% NEUTRAL:														
		FEEDER: (4) #20 AWG AL, (1) #4 AWG AL GND, IN 2" CONDUIT	ENCLOSURE TYPE: NEMA 1	ISOLATED GROUND:															
CKT	CIRCUIT DESCRIPTION	VD%	AWG	GND	TRIP	FRAME	POLE	A	B	C	POLE	FRAME	TRIP	GND	AWG	VD%	CIRCUIT DESCRIPTION	CKT	
1	(A) EF-04 EF-05 LIGHTING KITCHEN 201	3.49	#12	#12	20 A	20 A	1	0.78	0.80			1	20 A	20 A	#12	#12	1.933	(G) REF. I MOTOR	2
3	(A) NON-CONTINUOUS CORRIDOR 200	1.761	#12	#12	20 A	20 A	1		0.30	0.80		1	20 A	20 A	#12	#12	1.871	(G) REF. I MOTOR	4
5	GWH1 I NON-CONTINUOUS MECHANICAL 206	1.67	#12	#12	15 A	15 A	1			0.60	0.80	1	20 A	20 A	#12	#12	1.829	(G) REF. I MOTOR	6
7	RCP1 I MOTOR MECHANICAL 206	1.555	#12	#12	15 A	15 A	1	0.16	0.80			1	20 A	20 A	#12	#12	1.881	(G) REF. I MOTOR	8
9	KEF-01 I MOTOR	2.175	#12	#12	20 A	20 A	1		0.70	0.25		1	20 A	20 A	#12	#12	1.684	ANSUL SYSTEM I NON-CONTINUOUS JANITOR'S...	10
11	DSD I MOTOR JANITOR'S CLOSET 207	1.577	#12	#12	20 A	20 A	1			0.10	1.69	2	25 A	25 A	#10	#10	2.387	DSCU-01 I MOTOR	12
13	EF-08 I MOTOR	1.921	#12	#12	15 A	15 A	1	0.31	1.69										14
15	EF-01 I MOTOR	1.882	#12	#12	20 A	20 A	2		0.33	0.76		1	15 A	15 A	#12	#12	1.71	FCU-01 I MOTOR MECHANICAL 206	16
17										0.33	1.32	2	20 A	20 A	#12	#12	2.866	CU-04 I MOTOR	18
19	ACCU-01 I MOTOR	2.061	#12	#12	15 A	15 A	2	0.47	1.32										20
21									0.47	0.05		1	20 A	20 A	#12	#12	1.618	SECURE DOOR NON-CONTINUOUS CORRIDOR 200	22
23	LIGHTING STAIR 129	1.678	#12	#12	20 A	20 A	1			0.20	0.10	1	20 A	20 A	#12	#12	1.561	MOD MOTOR MECHANICAL 206	24
25	SPARE	--	--	--	20 A	--	1	0.00	0.00			1	--	20 A	--	--	--	SPARE	26
27	SPARE	--	--	--	20 A	--	1		0.00	0.00		1	--	20 A	--	--	SPARE	28	
29	SPARE	--	--	--	20 A	--	1			0.00	0.00	1	--	20 A	--	--	SPARE	30	
31	SPARE	--	--	--	20 A	--	1	0.00	0.00			1	--	20 A	--	--	SPARE	32	
33	SPACE	--	--	--	--	--	--		0.00	0.00		--	--	--	--	--	SPACE	34	
35	SPACE	--	--	--	--	--	--			0.00	0.00	--	--	--	--	--	SPACE	36	
37	SPACE	--	--	--	--	--	--	0.00	0.00			--	--	--	--	--	SPACE	38	
39	SPACE	--	--	--	--	--	--		0.00	0.00		--	--	--	--	--	SPACE	40	
41	SPACE	--	--	--	--	--	--			0.00	0.00	--	--	--	--	--	SPACE	42	
		TOTAL CONNECTED LOAD:		6.3 kVA		3.7 kVA		5.1 kVA		ESTIMATED DEMAND		NOTES:		BREAKER QUANTITIES (NEW ONLY)					
LOAD CLASSIFICATION		CONNECTED LOAD		DEMAND FACTOR		100.00%		3576 VA						(4) 15A / 1P, (1) 15A / 2P, (14) 20A / 1P, (2) 20A / 1P (A), (4) 20A / 1P (G), (2) 20A / 2P, (1) 25A / 2P					
Cooling		3576 VA																	
Lighting		840 VA				125.00%		1050 VA											
Motor		9496 VA				106.87%		10339 VA											
Non-Continuous		1200 VA				100.00%		1200 VA											
		PANEL TOTALS																	
		TOTAL CONNECTED LOAD:		15.1 kVA															
		DEMAND CALCULATION NOTES:																	
		TOTAL DEMAND:		16.2 kVA															
		TOTAL DEMAND AMPS:		45 A															

PANEL NAME: OSL1A		SUPPLY FROM: OSDP	MAINS RATING (A): 125	FAULT CURRENT (A): 29717	SURGE SUPPRESSION: Yes														
		LOCATION: ELECTRICAL 124	MAINS TYPE: MAIN LUGS ONLY	SHORT CIRCUIT RATING (A): 42000	ULSE:														
		DISTRIBUTION SYSTEM: 208/120V 3PH 4W	FEEDER ID: 125-4A	LUGS TYPE:	200% NEUTRAL:														
		FEEDER: (4) #20 AWG AL, (1) #4 AWG AL GND, IN 2" CONDUIT	ENCLOSURE TYPE: NEMA 1	ISOLATED GROUND:															
CKT	CIRCUIT DESCRIPTION	VD%	AWG	GND	TRIP	FRAME	POLE	A	B	C	POLE	FRAME	TRIP	GND	AWG	VD%	CIRCUIT DESCRIPTION	CKT	
1	(L) FACP I NON-CONTINUOUS ELECTRICAL 124	1.076	#12	#12	20 A	20 A	1	0.50	0.75			1	20 A	20 A	#12	#12	2.55	OVERHEAD DOOR I MOTOR APPARATUS BAY 125	2
3	(G) RECEPTACLE APPARATUS BAY 125	1.445	#12	#12	20 A	20 A	1		0.50	0.75		1	20 A	20 A	#12	#12	1.517	OVERHEAD DOOR I MOTOR APPARATUS BAY 125	4
5	(G) RECEPTACLE APPARATUS BAY 125	1.701	#12	#12	20 A	20 A	1			0.50	0.75	1	20 A	20 A	#12	#12	2.209	OVERHEAD DOOR I MOTOR APPARATUS BAY 125	6
7	(G) RECEPTACLE APPARATUS BAY 125	1.53	#12	#12	20 A	20 A	1	0.50	0.30			1	20 A	20 A	#12	#12	1.242	SECURE DOOR NON-CONTINUOUS 101,102,104	8
9	RECEPTACLE APPARATUS BAY 125	2.709	#12	#12	20 A	20 A	1		1.08	0.47		1	15 A	15 A	#12	#12	1.632	GFUJH-01 I HEATING	10
11	LIGHTING ELECTRICAL 124	2.493	#12	#12	20 A	20 A	1			0.77	0.15	1	20 A	20 A	#12	#12	1.254	LIGHTING	12
13	LIGHTING APPARATUS BAY 125	1.164	#12	#12	20 A	20 A	1	0.15	0.20			1	20 A	20 A	#12	#12	1.558	EXTERIOR LIGHTING	14
15	LIGHTING APPARATUS BAY 125	4.132	#12	#12	20 A	20 A	1		1.20	0.50		1	20 A	20 A	#12	#12	1.619	PPE DRYER I MOTOR APPARATUS BAY 125	16
17	GEN ACCESSORY I NON-CONTINUOUS	2.061	#12	#12	20 A	20 A	1			0.50	0.80	1	20 A	20 A	#12	#12	1.567	(G) VENDING I NON-CONTINUOUS EMS SUPPLY 121	18
19	BLOCK HTR I NON-CONTINUOUS	3.139	#12	#12	20 A	20 A	1	1.00	0.10			1	20 A	20 A	#12	#12	1.137	MOD I MOTOR APPARATUS BAY 125	20
21	BATTERY HTR I NON-CONTINUOUS	3.105	#12	#12	20 A	20 A	1		1.00	0.54		1	20 A	20 A	#12	#12	2.009	RECEPTACLE 119,118,117	22
23	RECEPT I NON-CONTINUOUS	1.711	#12	#12	20 A	20 A	1			0.36	0.72	1	20 A	20 A	#12	#12	1.991	RECEPTACLE SCBA 118	24
25	RECEPTACLE, NON-CONTINUOUS 125,124,123	1.196	#12	#12	20 A	20 A	1	0.66	0.72			1	20 A	20 A	#12	#12	1.576	RECEPTACLE TOOLS/STORAGE 117	26
27	RECEPTACLE EMS SUPPLY 121	1.396	#12	#12	20 A	20 A	1		0.54	0.36		1	20 A	20 A	#12	#12	1.407	RECEPTACLE TURNOUT GEAR 120	28
29	RECEPTACLE STORAGE 122	1.412	#12	#12	20 A	20 A	1			0.54	0.50	1	--	20 A	--	--	--	NOTIFICATION SYSTEM	30
31	SPARE	--	--	--	20 A	--	1	0.00	0.00			1	--	20 A	--	--	--	SPARE	32
33	SPARE	--	--	--	20 A	--	1		0.00	0.00		1	--	20 A	--	--	--	SPARE	34
35	SPARE	--	--	--	20 A	--	1			0.00	0.00	1	--	20 A	--	--	--	SPARE	36
37	SPARE	--	--	--	20 A	--	1	0.00	0.00			1	--	20 A	--	--	--	SPARE	38
39	SPACE	--	--	--	--	--	--		0.00	0.00		--	--	--	--	--	--	SPACE	40
41	SPACE	--	--	--	--	--	--			0.00	0.00	--	--	--	--	--	--	SPACE	42
		TOTAL CONNECTED LOAD:		5.0 kVA		6.9 kVA		5.6 kVA		ESTIMATED DEMAND		NOTES:		BREAKER QUANTITIES (NEW ONLY)					
LOAD CLASSIFICATION		CONNECTED LOAD		DEMAND FACTOR		100.00%		468 VA											

ELECTRIC EQUIPMENT SUPPLY SCHEDULE														
EQUIPMENT MARK	SUPPLY FROM	CKT	EMERG.	LOAD (KVA)	AVAILABLE FAULT CURRENT	VOLTS	POLE	HTG KW	WATT	HP	FLA (A)	MCA (A)	RCD OCP (A)	BREAKER RATING (A)
AC1	OSDP	1,3		1.20	4141	208 V	2				4.5	7		20
ACCU-01	OSL2A	19,21		0.94	1711	208 V	2							15
ACU-01	OSDP	5,7		5.99	7026	208 V	2					32	50	50
CU-01	L2A	4,6		2.64	2315	208 V	2					14.1	20	20
CU-02	L2A	16,18		2.19	2824	208 V	2					11.7	20	20
CU-03	L2A	10,12		5.15	5127	208 V	2					27.5	40	40
CU-04	OSL2A	18,20		2.64	1906	208 V	2					14.1	20	20
DS-01				0.00		208 V	2							
DSCU-01	OSL2A	12,14		3.37	3234	208 V	2					18	25	25
EDH-01	OSDP	21,23,25		18.00	5698	208 V	3	18						60
EF-01	OSL2A	15,17		0.67	1793	208 V	2			25	3.2			20
EF-02	OSL1B	12		0.07	1872	120 V	1					0.58		20
EF-03	OSL1B	12		0.07	1495	120 V	1					0.58		20
EF-04	OSL2A	1		0.07	1062	120 V	1					0.58		20
EF-05	OSL2A	1		0.07	915	120 V	1					0.58		20
EF-06	L1A	9		0.03	1680	120 V	1					0.27		15
EF-07	L1A	22		0.04	1973	120 V	1					0.34		15
EF-08	OSL2A	13		0.31	1377	120 V	1			1/10	2.6			15
EW-01	OSL1B	16		1.50	1438	120 V	1	1.5				12.5		20
EW-02	L1A	31		1.50	2389	120 V	1	1.5				12.5		20
EW-03	L2A	42		1.50	795	120 V	1	1.5				12.5		20
EW-04	L2A	39		1.50	875	120 V	1	1.5				12.5		20
FCU-01	OSL2A	16		0.76	4911	120 V	1				7	15		15
FCU-02	L2A	2		0.55	5035	120 V	1				5.1	15		15
FCU-03	L2A	8		1.60	3860	120 V	1				14.8	20		20
FCU-04	L2A	14		0.76	3906	120 V	1				7	15		15
GD1	L2A	28		1.14	2697	120 V	1					9.5		15
GFU-01	OSL1A	10		0.47	1327	120 V	1				3.9			15
GWH1	OSL2A	5		0.60	5900	120 V	1					5.0		15
KEF-01	OSL2A	9		0.70	1800	120 V	1			25	5.8			20
RCP1	OSL2A	7		0.16	5593	120 V	1		85	1/12	1.3			15

HVAC ELECTRICAL COORDINATION SCHEDULE																											
ABBREVIATIONS				CONTRACTOR TYPE								MOTOR CONTROL TYPE								CONTROL TYPE							
DC	LOCAL DISCONNECT	EC	ELECTRICAL CONTRACTOR	CS	COMBINATION STARTER								TC	TIMECLOCK													
MC	MOTOR CONTROL (POWER)	EX	EXISTING	MCC	MOTOR CONTROL STARTER								CPT	CONTROL POWER TRANSFORMER													
SD	DUCT SMOKE DETECTOR	FC	FIRE PROTECTION CONTRACTOR	MG	MAGNETIC STARTER OR CONTACT								BAS	BUILDING AUTOMATION SYSTEM													
CN	CONTROLS	GC	GENERAL CONTRACTOR	MS	MANUAL STARTER								LOW	LOW VOLTAGE CONTROLS													
TS	TOGGLE SWITCH	HC	HVAC CONTRACTOR	VFD	VARIABLE FREQUENCY DRIVE								LINE	LINE VOLTAGE CONTROLS													
C/B	H.A.C.R. CIRCUIT BREAKER AT SOURCE PANELBOARD	MFR	MANUFACTURER	MSR	MANUAL STARTER W/ CONTROL RELAY								RLINE	REVERSE ACTING LINE VOLTAGE THERMOSTAT													
FUSE	FUSE AT LOCAL DISCONNECT (VERIFY FIELD RATING)	PC	PLUMBING CONTRACTOR	OV	OVERCURRENT PROTECTION								MAN	MANUAL													
MCA	MINIMUM CIRCUIT AMPACITY	OR	OWNER OR OTHERS										FA	FIRE ALARM													
CP	CORD AND PLUG CONNECTION												CO	CARBON MONOXIDE SENSOR													
													INT	INTEGRAL TO EQUIPMENT													
EQUIPMENT MARK	DESCRIPTION	VOLTS (V)	PHASE	EMERGENCY	BHP (HP)	HP (HP)	HTG (KW)	WATTS	Fed From	FLA (A)	MCA (A)	OCP (A)	DC TYPE	DC FURN	DC INST	DC WIRE	MC TYPE	MC FURN	MC INST	MC WIRE	CN TYPE	CN FURN	CN INST	CN WIRE	SD TYPE	AVAILABLE FAULT CURRENT (A)	
ACCU-01	AIR COOLED REFRIGERANT CONDENSERS	208	1							4.5	7			EC	EC	EC	MG	MFR	MFR	MFR	LOW	HC	HC	HC		1711	
ACU-01	DEHUMIDIFICATION UNIT	208	1								32	50		EC	EC	EC	MG	MFR	MFR	MFR	LOW	HC	HC	HC	DUCT SMOKE	7026	
CF-01	CEILING FAN	120	1			1/16								EC	EC	EC	VFD	MFR	MFR	MFR	LINE	EC	EC	EC			
CF-02	CEILING FAN	120	1			1/16								EC	EC	EC	VFD	MFR	MFR	MFR	LINE	EC	EC	EC			
CU-01	AIR COOLED CONDENSING UNIT	208	1							14.1	20			EC	EC	EC	MG	MFR	MFR	MFR	LOW	HC	HC	HC		2315	
CU-02	AIR COOLED CONDENSING UNIT	208	1							11.7	20			EC	EC	EC	MG	MFR	MFR	MFR	LOW	HC	HC	HC		2824	
CU-03	AIR COOLED CONDENSING UNIT	208	1							27.5	40			EC	EC	EC	MG	MFR	MFR	MFR	LOW	HC	HC	HC		5127	
CU-04	AIR COOLED CONDENSING UNIT	208	1							14.1	20			EC	EC	EC	MG	MFR	MFR	MFR	LOW	HC	HC	HC		1906	
DS-01	DUCTLESS SPLIT HIGH WALL UNIT	208	1						DSCU-01					EC	EC	EC	MG	MFR	MFR	MFR	LOW	MFR	MFR	MFR			
DSCU-01	DUCTLESS SPLIT OUTDOOR CONDENSING UNIT	208	1							18	25			EC	EC	EC	MG	MFR	MFR	MFR	LOW	MFR	MFR	MFR		3234	
ECP	ENVIRONMENTAL CONTROL PANEL	120	1											EC	EC	EC	---	---	---	---	BAS	HC	HC	HC			
EDH-01	ELECTRIC FURNACE	208	3				18							EC	EC	EC	MG	MFR	MFR	MFR	LOW	HC	HC	HC		5698	
EF-01	CENTRIFUGAL ROOF VENTILATOR	208	1			25				3.2				EC	EC	EC	MG	MFR	MFR	MFR	LINE	EC	EC	EC		1793	
EF-02	CEILING MOUNTED VENTILATOR	120	1							0.58				EC	EC	EC	MG	MFR	MFR	MFR	OCC	EC	EC	EC		1872	
EF-03	CEILING MOUNTED VENTILATOR	120	1							0.58				EC	EC	EC	MG	MFR	MFR	MFR	OCC	EC	EC	EC		1495	
EF-04	CEILING MOUNTED VENTILATOR	120	1							0.58				EC	EC	EC	MG	MFR	MFR	MFR	OCC	EC	EC	EC		1062	
EF-05	CEILING MOUNTED VENTILATOR	120	1							0.58				EC	EC	EC	MG	MFR	MFR	MFR	OCC	EC	EC	EC		915	
EF-06	CEILING MOUNTED VENTILATOR	120	1							0.27				EC	EC	EC	MG	MFR	MFR	MFR	LINE	EC	EC	EC		1680	
EF-07	CEILING MOUNTED VENTILATOR	120	1							0.34				EC	EC	EC	MG	MFR	MFR	MFR	OCC	EC	EC	EC		1973	
EF-08	CENTRIFUGAL ROOF VENTILATOR	120	1			1/10				2.6				EC	EC	EC	MG	MFR	MFR	MFR	LINE	EC	EC	EC		1377	
EF-09	CEILING MOUNTED VENTILATOR	120	1							0.34				EC	EC	EC	MG	MFR	MFR	MFR	OCC	EC	EC	EC		1680	
EW-01	WALL AND CEILING HEATER	120	1				1.5			12.5				EC	EC	EC	---	---	---	---	INT	MFR	MFR	MFR		1438	
EW-02	WALL AND CEILING HEATER	120	1				1.5			12.5				EC	EC	EC	---	---	---	---	INT	MFR	MFR	MFR		2389	
EW-03	WALL AND CEILING HEATER	120	1				1.5			12.5				EC	EC	EC	---	---	---	---	INT	MFR	MFR	MFR		795	
EW-04	WALL AND CEILING HEATER	120	1				1.5			12.5				EC	EC	EC	---	---	---	---	INT	MFR	MFR	MFR		875	
FCU-01	FANCOIL UNIT	120	1							7	15			EC	EC	EC	MG	MFR	MFR	MFR	LOW	HC	HC	HC	DUCT SMOKE	4911	
FCU-02	FANCOIL UNIT	120	1							5.1	15			EC	EC	EC	MG	MFR	MFR	MFR	LOW	HC	HC	HC	DUCT SMOKE	5035	
FCU-03	FANCOIL UNIT	120	1							14.8	20			EC	EC	EC	MG	MFR	MFR	MFR	LOW	HC	HC	HC	DUCT SMOKE	3860	
FCU-04	FANCOIL UNIT	120	1							7	15			EC	EC	EC	MG	MFR	MFR	MFR	LOW	HC	HC	HC	DUCT SMOKE	3906	
GFU-01	GAS FIRED UNIT HEATER	120	1							3.9				EC	EC	EC	MG	MFR	MFR	MFR	LINE	HC	EC	EC		1327	
KEF-01	CENTRIFUGAL WALL VENTILATOR	120	1			25				5.8				EC	EC	EC	MG	MFR	MFR	MFR	LINE	EC	EC	EC		1800	
MOD		120																									

PLUMBING ELECTRICAL COORDINATON SCHEDULE																								
ABBREVIATIONS			CONTRACTOR TYPE							MOTOR CONTROL TYPE										CONTROL TYPE				
DC	LOCAL DISCONNECT	EC	ELECTRICAL CONTRACTOR	CS	COMBINATION STARTER	TC	TIMECLOCK																	
MC	MOTOR CONTROL (POWER)	EX	EXISTING	MCC	MOTOR CONTROL STARTER	CPT	CONTROL POWER TRANSFORMER																	
SD	DUCT SMOKE DETECTOR	FC	FIRE PROTECTION CONTRACTOR	MG	MAGNETIC STARTER OR CONTACT	BAS	BUILDING AUTOMATION SYSTEM																	
CN	CONTROLS	GC	GENERAL CONTRACTOR	MS	MANUAL STARTER	LOW	LOW VOLTAGE CONTROLS																	
TS	TOGGLE SWITCH	HC	HVAC CONTRACTOR	VFD	VARIABLE FREQUENCY DRIVE	LINE	LINE VOLTAGE CONTROLS																	
C/B	H.A.C.R. CIRCUIT BREAKER AT SOURCE PANELBOARD	MFR	MANUFACTURER	MSR	MANUAL STARTER W/ CONTROL RELAY	RLINE	REVERSE ACTING LINE VOLTAGE THERMOSTAT																	
FUSE	FUSE AT LOCAL DISCONNECT (VERIFY FIELD RATING)	PC	PLUMBING CONTRACTOR	OV	OVERCURRENT PROTECTION	MAN	MANUAL																	
FLA	OPERATING FULL LOAD AMPS	OR	OWNER OR OTHERS						FA	FIRE ALARM														
MCA	MINIMUM CIRCUIT AMPACITY						CO	CARBON MONOXIDE SENSOR																
CP	CORD AND PLUG CONNECTION						INT	INTEGRAL TO EQUIPMENT																
EQUIPMENT MARK	DESCRIPTION	VOLTS (V)	PHASE	EMERGENCY	BHP (HP)	HP (HP)	HTG KW (KW)	WATTS (W)	FLA (A)	MCA (A)	OCP (A)	DC TYPE	DC FURN	DC INST	DC WIRE	MC TYPE	MC FURN	MC INST	MC WIRE	CN TYPE	CN FURN	CN INST	CN WIRE	AVAILABLE FAULT CURRENT (A)
AC1	AIR COMPRESSOR	208	1										EC	EC	EC	MG	MFR	MFR	MFR	INT	MFR	MFR	MFR	4141
DW1C1	DOMESTIC ELECTRIC WATER COOLER	120	1				370	120				CP	EC	EC	EC	MG	MFR	MFR	MFR	INT	MFR	MFR	MFR	
GD1	GARBAGE DISPOSAL	120	1				9.5					CP	EC	EC	EC	MG	MFR	MFR	MFR	MAN	EC	EC	EC	2697
GW1H	DOMESTIC GAS-FIRED TANK-TYPE WATER HEATER	120	1					5.0					EC	EC	EC	---	---	---	---	INT	MFR	MFR	MFR	5900
RCP1	HOT WATER RECIRCULATING PUMP	120	1			1/12	85	1.3					EC	EC	EC	MG	MFR	MFR	MFR	LINE	PC	PC	PC	5593

ESSENTIAL FACILITY
SEISMIC REQUIREMENTS

SEISMIC BRACING FOR ALL NON-STRUCTURAL COMPONENTS INCLUDING BUT NOT LIMITED TO EQUIPMENT, PIPING, CONDUIT AND DUCTWORK IS REQUIRED FOR THIS PROJECT. THE DESIGN AND INSTALLATION OF THE SEISMIC RESTRAINT DEVICES IS DELEGATED TO THE CONTRACTOR. REFER TO SEISMIC CONTROLS SPECIFICATION FOR DELEGATED DESIGN SUBMITTAL REQUIREMENTS.

KLHENGINEERS

MECHANICAL/ELECTRICAL ENGINEERS

WWW.KLHENGRS.COM

1538 ALEXANDRIA PIKE, SUITE 11

FT. THOMAS, KENTUCKY 41075

800-354-9783

859-442-8050

859-442-8058 FAX

LEXINGTON, KENTUCKY


























LOUISVILLE, KENTUCKY

COLUMBUS, OHIO

NEW YORK, NEW YORK

STATE OF OHIO
PROFESSIONAL ENGINEER
STEPHEN N. FEDERLE
E-75033
SEAL
11/04/19

your trusted advisor
engineers
architects
consultants
planners

TECHNOLOGY LEGEND			
SYMBOL	DESCRIPTION		
TELECOMMUNICATIONS			
	WALL VOICE OUTLET EM = EMERGENCY VOICE OUTLET, W = WALL TELEPHONE OUTLET		
	CEILING DATA OUTLET WAP = WIRELESS ACCESS POINT		
	WALL DATA OUTLET WAP = WIRELESS ACCESS POINT		
	WALL DATA AND RF OUTLET		
	SPECIAL PURPOSE DATA OUTLET BAS = BUILDING AUTOMATION SYSTEM		
AUDIO-VISUAL SYSTEMS			
	CEILING AUDIO VISUAL CONNECTION		
	WALL AUDIO VISUAL CONNECTION		
	WALL RESET CONNECTION		
	WALL VOLUME CONTROL		
	WALL FLAT PANEL DISPLAY		
SECURITY SYSTEMS			
	CEILING SECURITY CAMERA		
	WALL SECURITY CAMERA		
	WALL PROXIMITY READER		
	SECURE DOOR		
CABLE / RACEWAY / SPACE			
	CIRCUIT HOME RUN WITH RACK IDENTIFIER AND PORT NUMBER		
	CABLING / RACEWAY INSTALLED CONCEALED IN WALLS OR ABOVE CEILING		
	CABLING / RACEWAY INSTALLED BELOW FLOOR OR GRADE		
	CABLE TRAY		
	LADDER RACK		
	SERVICE POLE - POWER AND TECHNOLOGY WHERE APPLICABLE.		
	4" CONDUIT SLEEVE UP OR DOWN THROUGH FLOOR		
	CONDUIT SLEEVE THROUGH WALL		
PLAN-VIEW LINE TYPES			
	WORK SHOWN BOLD-CONTINUOUS INDICATES NEW WORK (UNLESS INDICATED OTHERWISE)		
	WORK SHOWN FADED INDICATES EXISTING WORK TO REMAIN OR NEW WORK BY OTHERS AS APPLICABLE (UNLESS INDICATED OTHERWISE)		
	WORK SHOWN BOLD-DASHED INDICATES SELECTIVE DEMOLITION WORK (UNLESS INDICATED OTHERWISE)		
ABBREVIATIONS			
(R)	RELOCATE FIXTURE, EQUIPMENT OR DEVICE	HDMI	HIGH DEFINITION MULTIMEDIA INTERFACE
42"	DISTANCE ABOVE FINISHED FLOOR / GRADE / PAVEMENT	IP	INTERNET PROTOCOL
		LI	LOCAL INPUT
		LO	LOCAL OUTPUT
ACC	ADMINISTRATIVE CONTROL CONSOLE	OFE	OWNER FURNISHED EQUIPMENT
ACD	ACCESS CONTROLLED DOOR	OFCI	OWNER FURNISHED CONTRACTOR INSTALLED
AFF	ABOVE FINISHED FLOOR		
AFG	ABOVE FINISHED GRADE	PBB	PRIMARY GROUNDING BUSBAR
AVR	AUDIO VISUAL SYSTEM EQUIPMENT RACK	PM	PATIENT MONITOR
		PS	PATIENT STATUS
BAS	BUILDING AUTOMATION SYSTEM		
BFC	BELOW FINISHED CEILING	R	ROUGH-IN ONLY
C	CONDUIT	SBB	SECONDARY GROUNDING BUSBAR
CH	COUNTER HEIGHT OR SPECIAL HEIGHT DEVICE	SER	SECURITY SYSTEM EQUIPMENT RACK
		SSR	SOUND SYSTEM EQUIPMENT RACK
DP	DISPLAY PORT	TAAC	TO ABOVE ACCESSIBLE CEILING
DS	DIGITAL SIGNAGE	TAHC	TO ABOVE ACCESSIBLE HALLWAY CEILING
DVI	DIGITAL VIDEO INTERFACE	TR	TELECOMMUNICATIONS ROOM
DVR	DIGITAL VIDEO RECORDER	TBB	TELECOMMUNICATIONS BACKBOARD
EC	ELECTRICAL CONTRACTOR		
EF	ENTRANCE FACILITY	WP	WEATHERPROOF
EMR	ELECTRONIC MEDICAL RECORDS	WG	WIRE GUARD
EQR	EQUIPMENT RACK		
ER	EQUIPMENT ROOM		
ETR	EXISTING TO REMAIN		
EX	EXISTING		

- GENERAL NOTES:
- A. NOTHING SET FORTH IN THESE DRAWINGS SHALL RELEASE ANY CONTRACTOR FROM HIS RESPONSIBILITY TO PROVIDE APPROPRIATE QUANTITIES, FIELD MEASUREMENTS, DIMENSIONAL STABILITY, INSTALLATION, ANCHORAGE, AND COORDINATION WITH OTHER TRADES, OR RELEASE HIM FROM HIS RESPONSIBILITY TO IDENTIFY AND RESOLVE DEVIATIONS FROM THE REQUIREMENTS OF THE CONTRACT DOCUMENTS, OR FREE HIM OF HIS RESPONSIBILITY TO ALERT DESIGNER TO ERRORS OR OMISSIONS.

B. CONTRACTOR SHALL UTILIZE THESE DRAWINGS IN CONJUNCTION WITH THE SPECIFICATIONS TO DETERMINE THE FULL SCOPE, INTENT AND REQUIREMENTS OF THE PROJECT. SPECIFICATIONS AND DRAWINGS ARE INTENDED TO BE COMPLEMENTARY, NOT MUTUALLY EXCLUSIVE. WORK SHOWN ON THE DRAWINGS BUT NOT LISTED IN THE SPECIFICATIONS, AND WORK DESCRIBED IN THE SPECIFICATIONS BUT NOT SHOWN ON THE DRAWINGS SHALL BE INTERPRETED AS THOUGH WORK WERE FULLY DESCRIBED IN BOTH PLACES. THE HIGHER QUANTITY, HIGHER QUALITY, MORE LABOR INTENSIVE AND OVERALL MORE STRINGENT AND MORE COSTLY REQUIREMENT SHALL APPLY UNLESS OTHERWISE CLARIFIED IN WRITING PRIOR TO BID.

C. EACH CONTRACTOR SHALL VERIFY IN THE FIELD ALL EXISTING APPLICABLE CONDITIONS AND DIMENSIONS SHOWN ON THE DRAWINGS AND AS PERTINENT TO THE INTENT OF THESE DRAWINGS. ANY DISCREPANCY DISCOVERED SHALL BE BROUGHT TO THE ATTENTION OF THE DESIGNER PRIOR TO THE COMMENCEMENT OF ANY WORK AFFECTED BY, OR RELATED TO, SUCH DISCREPANCY. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR ALL COSTS ASSOCIATED WITH, OR CAUSED BY HIS FAILURE TO COMPLY WITH THIS REQUIREMENT.

D. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR JOB CLEANLINESS. PROJECT AREAS SHALL BE THOROUGHLY CLEANED AND TRASH DISPOSED OF AT THE END OF EACH WORK DAY. OWNERS FACILITIES SHALL NOT BE USED FOR WASTE DISPOSAL.

E. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTION OF ALL SURFACES AND FINISHES IN THE INTERIOR OR EXTERIOR OF THE FACILITY. DAMAGED SURFACES OR FINISHES RESULTING FROM THE PERFORMANCE OF THE WORK OR NEGLIGENCE SHALL BE REPAIRED AT NO COST TO THE OWNER AND BE MADE TO MATCH THE EXISTING FINISHES OR SURFACES TO THE SATISFACTION OF THE OWNER.

F. FOR COORDINATION PURPOSES, OCCASIONALLY AN ITEM OF WORK WILL BE SHOWN ON THE E SERIES DRAWINGS AND THE T SERIES DRAWINGS. IN ADDITION, THE SAME WORK MAY BE INCLUDED ON MULTIPLE T SERIES DETAIL SHEETS FOR SIMILAR REASONS.

G. FOR MULTI-PHASED PROJECTS, THE CONTRACTOR SHALL MAINTAIN ALL EXISTING UTILITY SERVICES AND BUILDING SYSTEMS. THE CONTRACTOR SHALL COORDINATE WITH THE OWNERS IT REPRESENTATIVE AS NECESSARY TO ALLOW FOR OPERATION ACCEPTABLE TO THE OWNER DURING CONSTRUCTION. THE CONTRACTOR SHALL PROVIDE TEMPORARY WIRING AS NECESSARY.

H. PROVIDE DUST PROTECTION WHEN WORKING IN EXISTING FACILITIES. SEAL OFF ALL WORK AREAS FROM REMAINDER OF THE EXISTING FACILITY.

- GENERAL ROUGH-IN AND PATHWAY NOTES:
- A. PROVIDE PATHWAYS FOR COMMUNICATIONS AND SECURITY SYTEMS CABLING. REFER TO SECTIONS "PATHWAYS FOR COMMUNICATIONS".

B. ROUGH-IN/PATHWAYS SHALL BE CLOSELY REVIEWED AND COORDINATED PRIOR TO INSTALLATION. IT IS THE RESPONSIBILITY OF THE ROUGH-IN PROVIDER TO THOROUGHLY REVIEW AND UNDERSTAND THE REQUIREMENTS OF THE SYSTEMS THAT WILL USE THE PATHWAYS.

C. WHERE CONDUITS ARE SPECIFIED "TAAC" (TO ABOVE ACCESSIBLE CEILING) THIS SHALL MEAN THAT CONDUITS SHALL BE STUBBED INTO AN ACCESSIBLE CEILING CAVITY WITHIN THE SAME ROOM AS THE DEVICE THE CONDUIT SERVES.

D. WHERE DEVICE CONDUITS ARE SPECIFIED "TAHC" (TO ABOVE ACCESSIBLE HALLWAY/CORRIDOR CEILING) THIS SHALL MEAN THAT CONDUITS SHALL BE RUN CONTINUOUS AND STUBBED OUT INTO AN ACCESSIBLE CEILING CAVITY WITHIN THE NEAREST CORRIDOR FEATURING AN ACCESSIBLE CEILING CAVITY.

E. CONDUIT INSTALLER SHALL INSTALL PULL STRINGS IN ALL CONDUITS IMMEDIATELY AFTER INSTALLATION.

F. WHERE CONDUIT IS SHOWN AND/OR SPECIFIED, PROVIDE PULL BOXES SHOWN ON THE DRAWINGS PLUS ADDITIONAL PULL BOXES FOR EVERY 180 DEGREES OF CONDUIT BEND AND 100 FEET OF CONDUIT.

G. PROVIDE COVER PLATES FOR JUNCTION AND PULL BOXES. COORDINATE MATERIAL AND FINISH OF BLANK PLATES TO MATCH SURROUNDING PLATES.

H. WHERE A MOUNTING HEIGHT MEASUREMENT IS APPLIED TO A ROUGH-IN, THE MEASUREMENT SHALL BE REFERENCED TO THE CENTER OF THE ROUGH-IN DEVICE.

I. PATHWAYS SHALL BE INSTALLED IN A CONCEALED MANNER. EXPOSED CONDUIT SHALL NOT BE PERMITTED IN FINISHED AREAS.

J. PROVIDE CODE-COMPLIANT FIRE-STOPPING FOR PATHWAYS THROUGH FIRE-RATED WALLS, FLOORS AND CEILINGS.

K. PROVIDE CONDUITS WITH NYLON END-BUSHINGS. INSTALL BUSHINGS AT THE END OF EACH CONDUIT AND EACH ADDITIONAL LOCATION WHERE CABLES COULD BE DAMAGED WHEN PULLING THEM THROUGH THE CONDUIT.

L. DEVICES TO BE INSTALLED AT COUNTER HEIGHT. CASEWORK OR FURNITURE SHALL BE CLOSELY COORDINATED IN THE FIELD WITH ARCHITECT, CASEWORK AND FURNITURE VENDORS PRIOR TO ROUGH-IN.

M. WHERE FLOORBOXES, POWER POLES AND OTHER DUAL SERVICE PATHWAYS ARE INDICATED ON THE DRAWINGS, PATHWAY DEVICES SHALL BE PROVIDED BY THE EC. SEE ELECTRIC DRAWINGS FOR REQUIREMENTS AND ADDITIONAL INFORMATION.

N. MANY COMMUNICATIONS DEVICES ARE INTENDED TO HAVE ADJACENT POWER OR INTEGRAL RECEPTACLES (MULTI-SERVICE) TO SERVE THE SAME EQUIPMENT. COORDINATE THE LOCATION OF SEPARATE DEVICES SO THAT THEY ARE LOCATED ADJACENT AND AT THE SAME ELEVATION. FACEPLATES SHALL BE COORDINATED TO THE SAME TYPE AND COLOR.

O. CONDUITS STUBBED INTO THE CEILING CAVITY SHALL BE MARKED WITH AN INDELIBLE MARKER INDICATING THE CONDUIT'S INTENDED USE. MARK CONDUIT WITHIN SIX INCHES OF THE CONDUIT BUSHING SO AS TO BE READABLE FROM BELOW.

P. LADDER RACK AND OTHER COMMUNICATION TECHNOLOGY CABLING PATHWAYS DEPICTED ON THE ENLARGED FLOOR PLANS SHALL BE PROVIDED AS INDICATED. ADDITIONAL PRODUCTS NECESSARY FOR PROFESSIONAL WIRE MANAGEMENT WITHIN THE MAIN EQUIPMENT ROOM <ER> AND ALL TELECOMMUNICATION ROOMS <TR> SHALL BE ALSO BE PROVIDED AS NECESSARY.

Q. PROVIDE A MINIMUM OF ONE (1) 2-INCH DIAMETER THROUGH-THE-WALL CONDUIT SLEEVES FOR USE AS COMMUNICATION AND SECURITY CABLE PATHWAYS INTO EACH SPACE CONTAINING COMMUNICATION AND SECURITY DEVICES. ROUTE CONDUITS FROM ABOVE ACCESSIBLE CEILING TO THE NEAREST HALLWAY/CORRIDOR FEATURING AN ACCESSIBLE CEILING CAVITY.

DRAWING IDENTIFICATION:

DRAWING PREFIX

DRAWING TYPE

DISCIPLINE ID


SEQUENCE #

T-501

DRAWING IDENTIFICATION IS INTENDED TO PROVIDE AN ORDERLY FORMAT TO DELIVER PROJECT INFORMATION. A MAJORITY OF DRAWINGS CONTAIN INFORMATION THAT IS REQUIRED OR WILL BE BENEFICIAL TO MULTIPLE DISCIPLINES AND / OR CONTRACTORS. LIKEWISE, EACH SPECIFICATION SECTION MAY REQUIRE INFORMATION ON MULTIPLE DRAWINGS TO COMPLETE THE SYSTEM(S).

DRAWING IDENTIFICATION	
DRAWING PREFIX	1 TECHNOLOGY
DRAWING TYPE	0 LEGEND/INDEX/COMPOSITE
	1 FLOORPLANS
	2 ELEVATIONS
	3 SECTIONALS
	4 ENLARGED FLOORPLANS AND DETAILS
	5 DETAILS
	6 DIAGRAMS
	7 PATHWAY/ROUGH-IN
DISCIPLINE ID	0 INFORMATION TECHNOLOGY - ALL DISCIPLINED
	1 STRUCTURED CABLING
	2 DATA SYSTEMS
	3 TELEPHONE SYSTEM
	4 AV SYSTEMS
	5 DISTRIBUTED COMMUNICATIONS
	6 RESERVED
	7 SECURITY
	8 SITE/OUTDOOR (OSP)
	9 RESERVED
SEQUENCE #	0 RESERVED
	1-9 FIRST NINTH
	A-Z 10-36

SYSTEM DIAGRAM LEGEND



GENERAL CABLING NOTES:

- A. PLENUM CABLE REQUIRED. ALL CABLE THAT WILL NOT BE INSTALLED IN A FULLY ENCLOSED CONDUIT SYSTEM SHALL BE RATED FOR INSTALLATION WITHIN A RETURN AIR PLENUM.

B. ALL INSTALLED CABLING SHALL BE CONTINUOUS AND WITHOUT SPLICES, EXCEPT WHERE OTHERWISE NOTED.

C. COLORS OF CABLING USED FOR ALL TECHNOLOGY WORK SHALL BE REVIEWED AND APPROVED PRIOR TO PROCUREMENT AND INSTALLATION.

SHARONVILLE FIRE STATION 87 RENOVATION

CITY OF SHARONVILLE

11210 READING RD, SHARONVILLE, OH 45241

TECHNOLOGY COVER SHEET

SCALE: As indicated

HORZ:


VERT:

CONTRACT NO:


170636

SHEET

T-001




LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK




DATE	11/20/2019	PCV 0	ISSUE FOR BIDDING AND PERMIT	11/20/2019	CAM
DRAWN BY: _____ MEN					
CHECKED BY: _____ SWS					
APPROVED BY: _____					
F.B. _____ PG. _____					

SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241
TECHNOLOGY DEMOLITION PLAN

SCALE: $1/8" = 1'-0"$
 HORZ:
 VERT:
 CONTRACT NO:
 170636
 SHEET
 T-101



1
T-101 1/8" = 1'-0"



2
T-101
1/8" = 1'-0"

SECOND FLOOR TECHNOLOGY DEMOLITION PLAN

N


1 TECHNOLOGY PLAN - FIRST FLOOR
T-102 / 1/4" = 1'-0"

859-442-8058 FAX
LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK

T2	(1) 2" CONDUIT TO ROOF FOR ANTENNA. PROVIDE WEATHERHEAD. SEE ANTENNA DETAIL. TURN CONDUIT OUT INTO CEILING SPACE OF OFFICE 103.
T3	(1) 4" CONDUIT FOR CATEGORY CABLING. TURN CONDUIT OUT INTO CEILING SPACE OF OFFICE 103.
T4	(1) 1" CONDUIT FOR SPEAKER CABLING. TURN CONDUIT OUT INTO CEILING SPACE OF OFFICE 103.
T5	DUE TO WALL SPACE AVAILABLE DISPLAY SIZE IS LIMITED TO 65" OR LESS.



your trusted advisor
consultants
engineers
architects
planners




DATE:	11/20/2019	REV	0	ISSUE FOR BIDDING AND PERMIT	REVISIONS	DATE	BY
DRAWN BY:	MSN						
CHECKED BY:	SMB						
APPROVED BY:							
FIG NO.	PG.						

SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241
TECHNOLOGY PLAN - FIRST FLOOR

SCALE:	1/4" = 1'-0"
HORZ:	
VERT:	
CONTRACT NO:	
170636	
SHEET	
T-102	

11/14/2019 10:23:40 AM



1
T-103
1/4" = 1'-0"

TECHNOLOGY PLAN - SECOND FLOOR

N


KEYED NOTES

T1 VERIFY FINAL LOCATION WITH MECHANICAL CONTRACTOR.

KLH ENGINEERS
MECHANICAL/ELECTRICAL ENGINEERS
WWW.KLHENGERS.COM

1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8050
859-442-8058 FAX

LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK



your trusted advisor
consultants
engineers
architects
planners

KLH

REV	REVISIONS	DATE	BY
0	ISSUE FOR BIDDING AND PERMIT	11/20/2019	CAM
1			
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			
13			
14			
15			
16			
17			
18			
19			
20			

DATE:	11/20/2019	DATE:	11/20/2019
DRAWN BY:	MSL	CHECKED BY:	SWB
APPROVED BY:		APPROVED BY:	
F.B. NO.		P.G.	

SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241
TECHNOLOGY PLAN - SECOND FLOOR

SCALE: 1/4" = 1'-0"
HORIZ:
VERT:
CONTRACT NO:
170636
SHEET
T-103

TELECOM ROOM NOTES: (THIS SHEET)

- A. STANDARD TELECOMMUNICATIONS BACKBOARDS SHALL BE 4" WIDE BY 8" TALL. EACH BACKBOARD SHALL BE 3/4" A-C GRADE PLYWOOD COATED ON THE EXPOSED FRONT AND ALL EDGES WITH 2 COATS OF WHITE FIRE-RETARDANT PAINT. LEAVE ONE FIRE RETARDANT STAMP VISIBLE NEAR THE TOP OF THE BACKBOARD.
- B. EACH BACKBOARD SHALL BE MOUNTED VERTICALLY UTILIZING THREE BOLTS (TOP, MIDDLE, BOTTOM) OF EACH STUD IN THE WALL (OR A MINIMUM OF 2 COLUMNS IN BLOCK CONSTRUCTION). BACKBOARDS SHALL BE MOUNTED WITH THE BOTTOM EDGE SQUARE AND LEVEL 1/4" ABOVE THE BASEBOARD OR 6" ABOVE FINISHED FLOOR (WHICHEVER IS LOWER) UNLESS OTHERWISE NOTED.
- C. WHERE A FULL-SIZED BACKBOARD CANNOT BE UTILIZED, A STANDARD BACKBOARD SHALL BE CUT TO FIT THE SPACE. ALL EDGES SHALL BE RE-PAINTED.
- D. WHERE BACKBOARDS ARE MOUNTED OVER DEVICES (SUCH AS SWITCHES AND OUTLETS) THE BACKBOARD SHALL BE CUT TO ALLOW THE ENTIRE DEVICE TO BE REVEALED PLUS 1/4" TRIM SPACE ON EACH SIDE.
- E. EACH BACKBOARD SHOWN ON THE ENLARGED FLOOR PLAN SHALL BE NUMBERED AND CORRESPOND TO BACKBOARDS SHOWN ON THE WALL ELEVATION DETAIL. WALL AND/OR BACKBOARDS SHOWN ON THE FLOOR PLANS BUT NOT DETAILED ON THE WALL ELEVATION HAVE NO PLANNED EQUIPMENT MOUNTING REQUIREMENTS UNDER THIS CONTRACT.
- F. EQUIPMENT SHOWN ON BACKBOARDS IS DIAGRAMMATICAL AND IS INTENDED TO SHOW A SPACE ALLOCATION FOR EQUIPMENT THAT MAY BE REQUIRED.

KLH

ENGINEERS

MECHANICAL/ELECTRICAL ENGINEERS

WWW.KLHENGRS.COM

1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8050
859-442-8058 FAX

LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK

STATE OF OHIO

STEPHEN N. FEDERLE

7-76033

11/04/19

your trusted advisor

engineers
architects
planners

REV	DATE	REVISIONS	BY
0	11/20/2019	ISSUE FOR BIDDING AND PERMIT	CAM
1	11/20/2019		
2	11/20/2019		
3	11/20/2019		
4	11/20/2019		
5	11/20/2019		
6	11/20/2019		
7	11/20/2019		
8	11/20/2019		
9	11/20/2019		
10	11/20/2019		
11	11/20/2019		
12	11/20/2019		
13	11/20/2019		
14	11/20/2019		
15	11/20/2019		
16	11/20/2019		
17	11/20/2019		
18	11/20/2019		
19	11/20/2019		
20	11/20/2019		
21	11/20/2019		
22	11/20/2019		
23	11/20/2019		
24	11/20/2019		
25	11/20/2019		
26	11/20/2019		
27	11/20/2019		
28	11/20/2019		
29	11/20/2019		
30	11/20/2019		
31	11/20/2019		
32	11/20/2019		
33	11/20/2019		
34	11/20/2019		
35	11/20/2019		
36	11/20/2019		
37	11/20/2019		
38	11/20/2019		
39	11/20/2019		
40	11/20/2019		
41	11/20/2019		
42	11/20/2019		
43	11/20/2019		
44	11/20/2019		
45	11/20/2019		
46	11/20/2019		
47	11/20/2019		
48	11/20/2019		
49	11/20/2019		
50	11/20/2019		
51	11/20/2019		
52	11/20/2019		
53	11/20/2019		
54	11/20/2019		
55	11/20/2019		
56	11/20/2019		
57	11/20/2019		
58	11/20/2019		
59	11/20/2019		
60	11/20/2019		
61	11/20/2019		
62	11/20/2019		
63	11/20/2019		
64	11/20/2019		
65	11/20/2019		
66	11/20/2019		
67	11/20/2019		
68	11/20/2019		
69	11/20/2019		
70	11/20/2019		
71	11/20/2019		
72	11/20/2019		
73	11/20/2019		
74	11/20/2019		
75	11/20/2019		
76	11/20/2019		
77	11/20/2019		
78	11/20/2019		
79	11/20/2019		
80	11/20/2019		
81	11/20/2019		
82	11/20/2019		
83	11/20/2019		
84	11/20/2019		
85	11/20/2019		
86	11/20/2019		
87	11/20/2019		
88	11/20/2019		
89	11/20/2019		
90	11/20/2019		
91	11/20/2019		
92	11/20/2019		
93	11/20/2019		
94	11/20/2019		
95	11/20/2019		
96	11/20/2019		
97	11/20/2019		
98	11/20/2019		
99	11/20/2019		
100	11/20/2019		

SHARONVILLE FIRE STATION 87 RENOVATION

CITY OF SHARONVILLE

11210 READING RD, SHARONVILLE, OH 45241

TECHNOLOGY PLAN - ENLARGED


SCALE: As indicated

HORIZ:


VERT:

CONTRACT NO: 170636


SHEET T-401




4 TECHNOLOGY PLAN - ENLARGED
T-401 3/4" = 1'-0"




2 TECHNOLOGY PLAN - ENLARGED
T-401 3/4" = 1'-0"



TECHNOLOGY - ROUGH-IN
SCALE: NONE



3 TECHNOLOGY PLAN - ENLARGED
T-401 3/4" = 1'-0"




1 TECHNOLOGY PLAN - ENLARGED
T-401 3/4" = 1'-0"



1538 ALEXANDRIA PIKE, SUITE 11
FT. THOMAS, KENTUCKY 41075
800-354-9783
859-442-8050
859-442-8058 FAX

LEXINGTON, KENTUCKY
LOUISVILLE, KENTUCKY
COLUMBUS, OHIO
NEW YORK, NEW YORK

your trusted advisor
consultants
engineers
architects
planners

[illegible]

SHARONVILLE FIRE STATION 87 RENOVATION
CITY OF SHARONVILLE
11210 READING RD, SHARONVILLE, OH 45241

TECHNOLOGY - DETAILS

SCALE: 1/8" = 1'-0"

HORIZ:


VERT:

CONTRACT NO:

170636

SHEET

T-512




UTILIZE LEVITON 49223-BAK

[illegible]

UTILIZE SECIAL USE ("SU" OR "CAM") PATCH PANEL WHERE SO EQUIPPED.

[X] INDICATES THE CAMERA TYPE; OUTLET ONLY WHERE TYPE NOT INDICATED.

SCALE: NONE



WALL OUTLET

	SCALE: NONE
--	-------------

THE CABLE SHALL HAVE A 20' SERVICE LOOP SUPPORTED BY A J-HOOK DEVICE.

UTILIZE PLENUM RATED HOUSING
COMPLETELY WRAP JACK ASSEM
WITH UNIFRAX FYREWAP 0.5
PLENUM
INSULATION



SEE PROJECT COORDINATION
SCHEDULE FOR COLOR-CODING
AND PROJECT SPECIFIC
INFORMATION


[illegible]

UTILIZE SECIAL USE ("SU" OR "WAP") PATCH PANEL WHERE SO EQUIPPED.

[X] INDICATES THE CAMERA TYPE; OUTLET ONLY WHERE TYPE NOT INDICATED.

	SCALE: NONE
--	-------------

ABOVE CEILING OUTLET



SEE PROJECT COORDINATION
SCHEDULE FOR COLOR-
CODING
AND PROJECT SPECIFIC
INFORMATION


** OUTLET DEVICE LEGEND				
BASE OUTLET/DEVICE				
4" SQUARE BOX, ONE (1) 1" CONDUIT				
SINGLE DEVICE TRIM RING				
SUBSCRIPT	TERMINATION	CABLE	MTG HT	ORIENTATION
NONE	PROXIMITY READER	NONE	48" O.C. AFF	TR TBB PNL
PIN	READER WITH PIN	NO ADDITIONAL		
BIO	BIOMETRIC READER	NO ADDITIONAL		
ADDITIONS TO BASE OUTLET/DEVICE				
NOTE: CABLE FROM DEVICE AND OPENER TO TR TBB PNL				
SUBSCRIPT	TERMINATION	CABLE	MTG HT	ORIENTATION

PIN = PROXIMITY READER WITH PIN PAD

SHOWN FOR ROUGH-IN PURPOSES ONLY. ACCESS CONTROL EQUIPMENT BY OTHERS


SCALE: NONE

SCALE: NONE



WALL OUTLET

	SCALE: NONE
--	-------------



ROUTE CABLES THROUGH ELECTRIC TRANSFER HINGE

COORDINATE WITH
DOOR HARDWARE
SCHEDULE

- INTEGRATED ELECTRIFIED DOOR HARDWARE. REQUEST TO EXIT, ELECTRONIC LOCKET AND STATUS SENSOR

** OUTLET DEVICE LEGEND				
	BASE OUTLET/DEVICE			
	1/2" CONDUIT INTO DOOR FRAME, STUBBED TAAC			
SUBSCRIPT	TERMINATION	CABLE	MTG HT	ORIENTATION
NONE	SENSOR	NONE	DOOR	TR TBB PNL
	ELECTRIC LOCKSET	NONE	DOOR	TR TBB PNL
	REQUEST TO EXIT	NONE	DOOR	TR TBB PNL
ADA	DOOR OPENER	NONE	DOOR	TR TBB PNL
NONE	NON-INTEGRATED LOCKSET, SEPERATE ROUGH-IN FOR PR			
NONE	INTEGRATED LOCKSET, NO ROUGH-IN FOR PR			

PR = PROXIMITY READER

SHOWN FOR ROUGH-IN PURPOSES ONLY. ACCESS CONTROL EQUIPMENT BY OTHERS

SCALE: NONE

SCALE: NONE

SECURE DOOR

